



SAFETY DATA SHEET

1. Identification of Substance and Manufacturer:

#3 Watch Rinsing Solution PCN: 118,119,120

Use: Ultrasonic Watch Rinsing Solution. To be used only for cleaning applications as specified.

Manufacturer: L&R Manufacturing Company, 577 Elm Street, P.O. Box 607 Kearny, NJ 07032-0607 USA.

Publication Date: 11/12/2014

REV: P

Product information call 201-991-5330 www.lrultrasonics.com

For emergencies involving a spill, leak fire or accident contact CHEMTREC 800-424-9300 within the United States. Or (01) 703-527-3887 (USA) for International collect calls.

2. HAZARDS IDENTIFICATION



WARNINGS! FLAMMABLE LIQUID AND VAPOR. MAY BE HARMFUL IF SWALLOWED. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. PROLONG OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

Acute Eyes: Direct contact causes irritation, redness and possible tearing.

Acute Skin: Prolonged or repeated contact causes redness, and drying of the skin.

Acute Inhalation: Breathing high concentrations of vapors or mists may cause irritation to the nose and may cause drowsiness.

B: POTENTIAL HEALTH EFFECTS:

Acute Ingestion: Not known, but expected to cause nausea and diarrhea.

Chronic Effects: This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogen.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Number	Percentage
Mineral Spirits Regular (C ₆ H ₆ < 0.1%), (Stoddard solvent) (Mixture of aliphatic and alicyclic C7-C12 hydrocarbons with maximum content of 25% C7-C12 aromatic hydrocarbons)	8052-41-3	70-80
Solvent Naphtha Light Aliphatic (mixture consisting mainly of straight-chained and cyclic aliphatic having 5 to 9 carbons atoms per molecules.)	64742-89-8	20-30

4. FIRST AID MEASURES

Eye Exposure: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek medical attention.

Skin Exposure: Wash thoroughly with water. If irritation or redness develops, seek medical attention.

Inhalation: If respiratory irritation or distress occurs, move victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

Ingestion: Seek immediate medical attention. DO NOT INDUCE VOMITING.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: Skin contact may aggravate existing skin disease.

5. FIRE FIGHTING MEASURES

FIRE HAZARD DATA:

Suitable Extinguishing Media: Extinguish with dry chemical, CO₂ or a BC/ABC extinguisher.

Unsuitable Extinguishing Media: Do not use a solid stream of water, since the stream will scatter and spread the fire.

Water spray may be used to keep fire exposed containers cool.

Special Fire Fighting Procedures: Wear full protective clothing and self-contained breathing apparatus (SCBA) approved for fire fighting.

Unusual Fire and Explosion Hazards: Closed containers may explode due to build up of pressure when exposed to extreme heat.

Hazardous Decomposition Materials: (under fire conditions) Oxides of nitrogen and carbon.

6. ACCIDENTAL RELEASE MEASURES

Cleanup and Disposal of Spill: Ventilate area of spill. Use non-reactive material to pick up spill. Dispose of in accordance with local, state and federal regulations.

Environmental and Regulatory Reporting: Not required

7. HANDLING AND STORAGE

Minimum/Maximum Storage Temperatures: 39 to 100 ° F.

HANDLING: AVOID CONTACT WITH SKIN, EYES OR CLOTHING

8. EXPOSURE CONTROL/PERSONAL PROTECTION

General: These recommendations provide general guidance for handling of this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. When developing safe handling procedures, do not overlook the need to clean and dispose of the material. Waste resulting from the use of this product should be handled in accordance with Section 13: Disposal Considerations.

Exposure Guidelines: Exposure limits are recommended worker breathing limits. The following limits apply to this material:

<u>INGREDIENTS</u>	<u>LIMITS</u>	<u>INGREDIENTS</u>	<u>LIMITS</u>
Mineral Spirits	100 ppm OSHA/ TWA	Solvent Naphtha	300 ppm OSHA/ ACGIH TWA

Engineering Controls: Provide adequate room ventilation. Keep covered as much as possible. Do not heat.

Respiratory Controls: For reasonable uses of this material, respiratory protection should not be necessary. If you are going to use a respirator use one with an organic vapor cartridge.

Eye/Face Protection: Safety glasses to protect from splashing.

Skin Protection: Wear Rubber or plastic gloves to avoid drying and irritation to the skin.

Work Practice Control: Normal hygiene in the work area should be taken when working with or handling this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Clear Liquid

Color: Water White

Odor: Bland Solvent.

pH: Not Established

Specific Gravity: 0.758

Odor Threshold: Not available

Water Solubility: Not Soluble

Density: 0.764 g/cm³ @ 77° F

Evaporation Rate: 1 Ethyl Ether

Freezing Point Range: Not Established

Boiling Point: 185 ° F /85 ° C

Partition Coefficient; n-octanol / water: Not available

Vapor Pressure: 226.666 hPa @ 100 ° F/37.8 ° C Calculated

Decomposition Temperature: Not available

Flash Point: 88 ° F/31° C **Method:** Tag Closed

Auto Ignition Temperature: Not available

Flammability limits (vol/vol %): Lower: 1% Upper: 8%

Relative Vapor Density: (>) 1 Air=1

Percent volatile by volume: Approx. 100 % by volume **V.O.C. (calculated):** 5.67 lbs/gal or 679.7 g/l

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to be avoided: Keep away from heat and open flames

Materials/Chemicals to be avoided: Strong Acids.

Hazardous Decomposition Products: Thermal Oxides of carbon and nitrogen

Possibility of Hazardous Reactions: WILL NOT OCCUR

11. TOXICOLOGICAL INFORMATION

Acute Eye Irritation: Irritating to eyes.

Acute Skin Irritation: No test data found for product.

Acute Dermal Toxicity: No test data found for product.

Acute Respiratory Irritation: No test data found for product.

Acute Inhalation Toxicity: No test data found for product.

Acute Oral Toxicity LD50 (rat): Mineral Spirits > 5 gm/kg Solvent Naphtha > 8,000 mg / kg

Chronic Toxicity: This product does not contain any substances that are considered by OSHA, NTP, IARC OR

ACGIH to be a probable or suspected human carcinogen. No additional test data was found for this product.

12. ECOLOGICAL INFORMATION

Ecotoxicological Information: No data found.

13. DISPOSAL CONSIDERATIONS

This material is a flammable liquid and must be disposed in accordance with all local, state and federal regulations.
IT CAN NOT BE DISPOSED OF IN A SANITARY SEWER SYSTEM.

14. TRANSPORTATION INFORMATION

For containers over one gallon and for export or air: Flammable liquid n.o.s. (Contains Naphtha, Petroleum), 3 UN 1993, Packing groups III. Limited Quantities for containers of one gallon or less shipped by domestic ground transportation. Do not stack cartons more than five high.

15. REGULATORY INFORMATION

Inventory Issues: All components of this product are listed on the U.S. TSCA, Canadian DSL, European EINECS/ELINS chemical listings

16. OTHER INFORMATION

National Fire Protection Association

Hazard Rating, NFPA

Health

Flammability

Reactivity

Special

1

3

0

--

MSDS CHANGES

REV

O

P

DATE

8/12/2014

11/12/2014

DESCRIPTION OF CHANGE

SDS Format

Update

Disclaimer: The information herein is given in good faith but no warranty expressed or implied is made. This #3 Watch Rinsing Solution SDS has been prepared by L&R Manufacturing Company.