

Fuelling Industrial Decarbonisation – Hydrogen and Alternative

Philipp Schönberger
- SAACKE GmbH




FERF
FUEL AND ENERGY RESEARCH FORUM

SAACKE – sustainable combustion technology for industry and marine applications.

SAACKE is the **world's leading provider of industrial combustion technology.**

We develop and produce innovative solutions capable of utilizing all types of fuels exceptionally efficiently, thus helping our customers to reduce their ecological footprints and minimize CO₂ emissions.



In use all over the world for maximum efficiency in challenging settings.



About the Person




Philipp Schönberger

- Dipl.-Ing. Process Engineer & Author
- Since 2009 with SAACKE
- Since 2023 Managing Partner- Consulting and Engineering



Motivation


Carbon Emissions



Carbon emissions include CO₂ emissions from energy use, industrial processes, natural gas flaring, methane emissions from energy production and the incomplete combustion of traditional bioenergy

—○— Current Trajectory
—○— Below 2°

Low carbon hydrogen demand By sector




Transport (hydrogen-derived fuels) includes hydrogen used to produce methanol, ammonia, and synthetic fuels consumed in the transport sector.

Associations with hydrogen



H2 combustion: long term experience



1981

2019



2024



A comparison of hydrogen and natural gas


Hydrogen as a fuel

Feature	Natural gas H	Hydrogen
Calorific value	35.82 MJ/m ³	10.82 MJ/m ³
Standard density	0.78 kg/m ³	0.09 kg/m ³
Wobbe Index	46.1 MJ/m ³ Natural gas L: 39.5 MJ/m ³	40.98 MJ/m ³
Adiabatic combustion temperature	2044 °C	2252 °C
Laminar flame speed	0.39 m/s	2.81 m/s
Air requirement	9.55 m ³ /m ³ _{LuftBS} 959.8 m ³ /h/MW _{Luft}	2.38 m ³ /m ³ _{LuftBS} 791.9 m ³ /h/MW _{Luft}

Technical challenge 1: Wear

Wear due to high temperature load


- Minimize thermal load through special burner design
- Parts in contact with the flame made of heat-resistant steel
- External exhaust gas recirculation → Also reduces NOx emissions



Technical challenge 2: Flame monitoring


Flame monitoring

- UV flame scanners are tried and tested
- OH- radicals



Technical challenge 3: NO_x emissions

Hydrogen and Natural Gas



Source: iGF final report - Investigation of the effect of hydrogen admixture into the natural gas grid on industrial firing processes in thermoprocessing plants, 2017

Combustion plant 1

Natural gas + Hydrogen on steam boiler

Task

- Steam generation with natural gas or hydrogen fuel + mixed firing
- 30 t/h flame tube boiler
- Burner type SSBGG 200.02
- Fuels: Hydrogen / natural Gas

Technical data

Firing capacity:	20,7 MW
Control range:	H2: 1:5 NG: 1:7
Emissions:	H2: NOx <80 mg/Nm ³ @3% NG: NOx <75 mg/Nm ³ @3%



Combustion plant 2


Hydrogen on paint dryer

Task

- Heat generation for Paint dryer
- Burner type SSBGG micro
- Fuels: Hydrogen / Natural Gas

Technical data

Firing capacity: 250-500 kW
Customer: BMW Leipzig




Alternatives to fossil fuels



Dusty

Wood dust
Coating powder dust
Coffee dust
Grain husk dust
Synthetic dusts



Gaseous

Hydrogen
Solvent fumes
Reffinery Gas
LPG
Alcohols
Pyrolysis Gas
C2-C4
Tailgas
Formalin-Gas
Process waste gases
Bio-Gas



Liquid

Solvents
Waste water
Naphta
Bio-fuels
Pyrolysis oils
Vinasse/Molasse
Liquid wastes
Animal fat
Synthetic fuels
Process wastes

Combustion plant 3

Natural gas + waste gas + liquid waste fuel + hydrogen

Task

- Utilization of production waste gases
- Utilization of liquid production residues that would otherwise be expensive to dispose of
- Compliance with emission regulations when incinerating these production residues with a high nitrogen and dust content
- Expansion of steam capacity at the site with flexible fuel utilization

Technical data

Boiler output:	14 t/h
Mass flow of liquid residue:	1.200 kg/h
Process gas volume flow:	600 Nm ³ /h
Emissions:	<200 mg/Nm ³ @11%



Engineering Expertise



*Large-scale thermal utilization
of hydrogen and alternative
fuels is proven and safe.
The decarbonisation of
production processes has
begun.*

THANK YOU FOR YOUR ATTENTION.

Philipp Schönberger

p.schoenberger@saacke.com

+49 421 64955288

Südweststraße 13

28237 Bremen, Germany

saacke.com