



Stalwart Safety

ANSI A2 HPPE-Nylon PU Coated

Application

Assembly Line Production, Construction, Masonry, Metal Stamping, HVAC, Material Handling, Recycling, Automotive Manufacturing, Glass Handling and many other material handling applications requiring cut and abrasion resistance.

Description

- HPPE-Nylon yarns provide high cut and abrasion levels
- Seamless knit construction fully protects hands while maintaining comfort and dexterity
- White Polyurethane coating provides additional abrasion resistance and grip
- White color shows soiling reducing transference issues.

Product Code: R199W

Technical Data

- ANSI Cut Level: A2
- ASTM F2992-15: 715g
- EN388 Abrasion: 4
- EN388 Cut: 3
- EN388 Tear: 4
- EN388 Puncture: 2

Construction

- Shell: HPPE Nylon plait knit, 13 gauge knit
- Coating: Polyurethane
- Wrist: Integrated knit wrist
- Thumb: Ambidextrous, right/left formed due to coating

Care Guidelines

Launder in warm water (40°C/104°F) using mild detergent, tumble dry at low temperature (60°C/140°F).

Packaging

- 12 pair/polybag
- 72 pair/carton



Sizes

Size	6	7	8	9	10	11
Fit	X-Small	Small	Medium	Large	X-Large	2XL



STALWART SAFETY | 1010 University Ave. W. Windsor ON | www.stalwartsafety.com
Phone: 844.945.5050 | Fax: 519.968.9707 | customerservice@stalwartsafety.com