



Stalwart Safety

ANSI Cut Level A2 HPPE-Nylon Polyurethane Coated Glove

Application

Assembly Line Production, Construction, Masonry, Metal Stamping, HVAC, Material Handling, Recycling, Automotive Manufacturing, Glass Handling and many other material handling applications requiring cut and abrasion resistance.

Description

- HPPE-Nylon yarns provide high cut and abrasion levels
- Seamless knit construction fully protects hands while maintaining comfort and dexterity
- Grey Polyurethane coating provides additional abrasion resistance and grip
- Open breathable knit back for added comfort

Product Code: 200

Technical Data

- ANSI Cut Level: A2
- ASTM F2992-15: 923g
- EN388 Abrasion: 4
- EN388 Cut: 3
- EN388 Tear: 4
- EN388 Puncture: 3
- ANSI Abrasion: 4
- ANSI Puncture: 4

Construction

- Shell: HPPE Nylon yarn, 13 gauge knit
- Coating: Polyurethane
- Wrist: Integrated knit wrist
- Thumb: Ambidextrous knit with right & left hand formed coating

Care Guidelines

Launder in warm water (40°C/104°F) using mild detergent, tumble dry at low temperature (60°C/140°F).

Packaging

- 12 pair/polybag
- 72 pair/carton

Sizes

Size	6 	7 	8 	9 	10 	11 	12 
Fit	X-Small	Small	Medium	Large	X-Large	2XL	3XL



STALWART SAFETY | 1010 University Ave. W. Windsor ON | www.stalwartsafety.com
Phone: 844.945.5050 | Fax: 519.968.9707 | customerservice@stalwartsafety.com