



Stalwart Safety

ANSI Cut Level A2 High Dexterity HPPE-Nylon Polyurethane Coated Glove

Application

Assembly line production, construction, metal fabrication & stamping, HVAC, recycling, aerospace/automotive manufacturing, and many other material handling applications requiring cut and abrasion resistance along with extreme dexterity. This glove should not be used where sparks or flames are present.

Description

- HPPE-Nylon yarns provide good cut and abrasion levels.
- Thin 18 gauge seamless knit fully protects hands while maintaining comfort and extreme dexterity.
- Black Polyurethane coating provides additional abrasion resistance and grip.
- Open breathable knit back for added comfort.

Product Code: 218

Technical Data

- ANSI Cut Level - A2
- ASTM F2992-15 - 565g
- EN388 Abrasion - 4
- EN388 Cut - 3
- EN388 Tear - 4
- EN388 Puncture - 2

Construction

- Shell: HPPE 18 Gauge Nylon Plait Yarn
- Wrist: Integrated Knit Wrist
- Thumb: Ambidextrous Knit w/Right & Left Hands Formed Due to Coating
- Coating: Polyurethane

Care Guidelines

Laundry in warm water (40°C/104°F) using mild detergent, tumble dry at moderate temperature (60°C/140°F).

Packaging

- 12 pair/polybag
- 72 pair/carton



Sizes

Size	6	7	8	9	10	11
Fit	X small	Small	Medium	Large	X-Large	2XL



STALWART SAFETY | 1010 University Ave. W. Windsor ON | www.stalwartsafety.com
Phone: 844.945.5050 | Fax: 519.968.9707 | insidesales@stalwartsafety.com