



Stalwart Safety

ANSI Cut Level A6 Aramid-HPPE Blend Polyurethane Coated Glove

Application

Metal Fabrication & Stamping, HVAC & Sheet Metal Handling, Recycling, Aerospace/Automotive Manufacturing, Glass Handling and many other material handling applications requiring high cut resistance.

Description

- Aramid-HPPE fiber yarns provide high cut and abrasion levels
- Seamless knit fully protects hands while maintaining comfort and good dexterity
- Open breathable knit back of hand provides additional comfort
- Black Latex coating provides additional abrasion resistance and good grip.

Product Code: 525LX

Technical Data

- ANSI Cut Level: A6
- ASTM F2992-15: 3643g
- EN388 Abrasion: 5
- EN388 Cut: 5
- EN388 Tear: 4
- EN388 Puncture: 4

Construction

- Shell: Aramid-HPPE composite yarn, nylon yarn, 13 gauge knit
- Coating: Latex Wrinkle
- Wrist: Integrated knit wrist
- Thumb: Ambidextrous knit with right & left hand formed coating

Care Guidelines

Launder in warm water (40°C/104°F) using mild detergent, tumble dry at low temperature (60°C/140°F). No bleach or oxidizers.

Packaging

- 12 pair/polybag
- 72 pair/carton



Sizes

Size	6	7	8	9	10	11
Fit	X-Small	Small	Medium	Large	X-Large	2XL



STALWART SAFETY | 1010 University Ave. W. Windsor ON | www.stalwartsafety.com
Phone: 844.945.5050 | Fax: 519.968.9707 | insidesales@stalwartsafety.com