



Stalwart Safety

ANSI Cut Level A2 HPPE-Nylon Polyurethane Coated Glove

Application

Assembly Line Production, Construction, Masonry, Metal Stamping, HVAC, Material Handling, Recycling, Automotive Manufacturing, Glass Handling and many other material handling applications requiring cut and abrasion resistance.

Description

- HPPE-Nylon yarns provide high cut and abrasion levels
- Seamless knit construction fully protects hands while maintaining comfort and dexterity
- Grey Polyurethane coating provides addition abrasion resistance and grip
- Open breathable knit back for added comfort

Product Code: A2EPU

Technical Data

- ANSI Cut Level: A2
- ASTM F2992-15: 563g
- EN388 Abrasion: 4
- EN388 Cut: 3
- EN388 Tear: 4
- EN388 Puncture: 2

Construction

- Shell: HPPE Nylon plait knit, 13 gauge knit
- Coating: Polyurethane
- Wrist: Integrated knit wrist
- Thumb: Ambidextrous, right/left formed due to coating

Care Guidelines

Laundry in warm water (40°C/104°F) using mild detergent, tumble dry at low temperature (60°C/140°F).

Packaging

- 12 pair/polybag
- 72 pair/carton



Sizes

Size	6	7	8	9	10	11
Fit	X-Small	Small	Medium	Large	X-Large	2XL



STALWART SAFETY | 1010 University Ave. W. Windsor ON | www.stalwartsafety.com
Phone: 844.945.5050 | Fax: 519.968.9707 | customerservice@stalwartsafety.com