



Stalwart Safety

ANSI Cut Level A6 $\frac{3}{4}$ Nitrile Coated Glove

Application

Glass Handling, Metal Fabrication & Stamping, Aerospace/Automotive Manufacturing, Steel Mills, Lumber Handling and many other material handling applications requiring high cut resistance.

Description

- Spun HPPE-Blended fiber yarns provide high cut and abrasion levels.
- Seamless knit fully protects hands while maintaining comfort and good dexterity.
- The $\frac{3}{4}$ Nitrile Coating provides greater coverage to increase protection.
- Reinforced Thumb Web increases the efficacy and longevity of the glove.

Product Code: AG34N

Technical Data

- ANSI Cut Level: A6
- ASTM F2992-15: 3529g
- ANSI ABR 6
- EN388 Abrasion: 4
- EN388 Cut: 5
- EN388 Tear: 4
- EN388 Puncture: 4

Construction

- Shell: HPPE Nylon plait knit, 10 gauge knit
- Coating: Nitrile foam
- Wrist: Integrated knit wrist
- Thumb: Ambidextrous, right/left formed due to coating

Care Guidelines

Launder in warm water (40°C/104°F) using mild detergent, tumble dry at low temperature (60°C/140°F).

Packaging

- 12 pair/polybag
- 72 pair/carton

Sizes

Size	7	8	9	10	11
Fit	Small	Medium	Large	X-Large	2XL



STALWART SAFETY | 1010 University Ave. W. Windsor ON | www.stalwartsafety.com
Phone: 844.945.5050 | Fax: 519.968.9707 | insidesales@stalwartsafety.com