

HUNTER Engineering Company

TCX & SWE MODELS IN STOCK

Models currently in-stock:

- TCX50E
- TCX50H
- TCX51E
- TCX51H
- TCX53E
- TCX53H
- SWE00
- SWE02
- Accessories
- Consumables

		TCX59Pro	TCX58	TCX53PRO	TCX53PLS	TCX51	TCX51PLS	TCX50	TCX51C
	POWER REQUIREMENTS	220	220	220	220-110-AIR	220-110-AIR	220	220-110-AIR	220
	HUNTERNET Connectivity	Requires Accessory	Requires Accessory	Requires Accessory	Requires Accessory*	Requires Accessory*	Requires Accessory	Requires Accessory*	
OEM STANDARD	Standard								
	Truck/SUV	Plus FastBlast	Plus FastBlast				Plus FastBlast		Plus FastBlast
	Low-Profile								
	Car								
OEM RUN-FLATS	Van/SUV								
	High-Performance								
	Aftermarket Single Piece								
AFTERMARKET	Aftermarket Mudder	Plus FastBlast	Plus FastBlast				Plus FastBlast		Plus FastBlast
	Aftermarket 2 & 3 Piece								
MOTORCYCLE/ATV	Golf Cart	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories
	ATV	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories
	Motorcycle	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories	Requires Accessories
THICK-BEAD	Skid Steer								
	19.5 in.								Requires Accessories
	22.5/Widebase								

Power Requirements	196-253V, 10 amp, 50/60 Hz, 1 ph NEMA L6-20 plug included
Air Supply Requirements	100-175 psi (7 - 12 bar)**
Approximate Air Consumption	4 CFM (110 Liters/Minute)
Rim Width Range	1.5 in to 20.5 in (38 mm to 521 mm)*
Rim Diameter Range	10 in to 30 in (254 mm to 762 mm)*
ALU	14 in to 40 in (356 mm to 1016 mm)*
Max. Tire Diameter	44 in (1118 mm)
Max. Tire Width	20 in (508 mm)
Max. Tire Weight	175 lbs (79 kg)
Radial & Lateral Runout Accuracy	0.002 in (0.051 mm)
Imbalance Resolution	± 0.01 oz (0.28 g)
Placement Accuracy	512 positions, ± 0.35°
Balancing Speed	300 rpm
Motor	Programmable drive system and DC motor
Usable Power Cord Length	~138 in. (3505 mm)

*Extreme wheel sizes may require manual data entry.

**Only wheel lift models and SpeedClamp®

	33	32	31	30	23	22	21	20	13	12	11	10	03	02	01	00
Wheel Lift	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SpeedClamp®	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
TDC Laser	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Printer & Shelf	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Width (W)	72 in 1829 mm	64 in 1626 mm	72 in 1829 mm	64 in 1626 mm	65 in 1651 mm	60.5 in 1537 mm	65 in 1651 mm	57 in 1448 mm	72 in 1829 mm	64 in 1626 mm	72 in 1829 mm	64 in 1626 mm	65 in 1651 mm	60.5 in 1537 mm	65 in 1651 mm	57 in 1448 mm
Height (H)	88.5 in 2248 mm	88.5 in 2248 mm	71 in 1804 mm	71 in 1804 mm	88.5 in 2248 mm	88.5 in 2248 mm	71 in 1804 mm	71 in 1804 mm	88.5 in 2248 mm	88.5 in 2248 mm	71 in 1804 mm	71 in 1804 mm	88.5 in 2248 mm	88.5 in 2248 mm	71 in 1804 mm	71 in 1804 mm
Depth (D)	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm	63.5 in 1613 mm
Weight	575 lb 261 kg	522 lb 237 kg	525 lb 238 kg	472 lb 214 kg	474 lb 215 kg	421 lb 191 kg	424 lb 192 kg	371 lb 169 kg	575 lb 261 kg	522 lb 237 kg	525 lb 238 kg	472 lb 214 kg	474 lb 215 kg	421 lb 191 kg	424 lb 192 kg	371 lb 169 kg

Contact you local Union
Auto Parts representative
today for more
information!

