


imageRUNNER C3326i

RELIABILITY, SECURITY AND HIGH PRODUCTIVITY FROM A COLOUR A3 MULTIFUNCTION PRINTER

MAIN CONFIGURATION OPTIONS



This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the [online product configurator](#)

TECHNICAL SPECIFICATIONS

imageRUNNER C3326i

MAIN UNIT		Direct Print	Supported file types: RUI: PDF, EPS, TIFF/JPEG, XPS USB Memory: PDF, TIFF/JPEG, XPS Network Place: PDF, TIFF/JPEG, XPS
Machine type	A3 Colour Laser Multifunctional	Printing from mobile and cloud	AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and Universal Print by Microsoft A range of software solutions is available to provide printing from mobile devices and cloud-based services depending on your requirements. Please contact your sales representative for further information
Core functions	Print, Copy, Scan, Send and Optional Fax	OS Standard Printing	Android/Windows* 10/Windows* 11/Chrome OS/macOS (11.2.2 or later), iOS (15.2 or later), iPadOS
Processor	1.6 GHz Dual Core Processor	Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2 *1 Requires optional PCL INTERNATIONAL FONT SET-A1 *2 Requires optional BARCODE PRT KIT-D1
Control Panel	17.8 cm/7 inch TFT LCD WVGA Colour Touch panel	Print Features	Secure Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/ Orientations, Toner Reduction, Poster Printing, Forced hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer
Memory	Standard: 2.0GB RAM	Operating System	UFR II: Windows*10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, MAC OS X (10.13 or later) PCL: Windows*10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, MAC OS X (10.13 or later) PS: Windows*10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, MAC OS X (10.13 or later) PPD: Windows*10/11, MAC OS X (10.13 or later)
Storage	Standard: (eMMC) 64GB Optional: (SSD) 256GB	COPY SPECIFICATIONS	
Interface Connection	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE802.11b/g/n) OTHERS Standard: USB 2.0 (Host) x 2, USB 2.0 (Device) x 1	Copy Speed	1-sided (BW/CL): Up to 26/26 ppm (A4, A5, A5R, A6R), Up to 20/20 ppm (A4R), Up to 15/15 ppm (A3) 2-sided (BW/CL): Up to 13/13 ppm (A4, A5R), Up to 10/10 ppm (A4R), Up to 7/7 ppm (A3) (A4, BW/CL): Approx. 7.0 / 8.7 seconds or less 600 × 600 Up to 999 copies Automatic or Manual (9 Levels) 25% - 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%, 141%, 200%, 400%
Paper Supply capacity (A4, 80gsm)	Standard: 1,200 Sheets Maximum: 2,300 Sheets (with optional Cassette Feeding Unit-AW1)	First-Copy-Out Time	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Sort, Job Build, N on 1, Different Size Originals, Sharpness, Erase Frame, Copy ID Card, Skip Blank Pages, Free Size Original, Colour Mode, Reserved copy, Copy Sample
Paper output capacity (A4, 80gsm)	Standard: 250 Sheets Maximum: 650 Sheets (with optional Inner Finisher-L1 and Copy Tray-T1)	Copy resolution (dpi)	
Finishing capabilities	Collate, Group, Offset, Staple, Hole Punch, Eco Staple, Staple On Demand * Finishing capabilities vary, depending on the options selected	Multiple Copies	Up to 999 copies
Supported Media Types	Multi-purpose Tray: Thin, Plain, Heavy*, Recycled, Coated, Colour, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Envelope * SRA3 is unsupported for Coated (257-300gsm) and Heavy (257-300gsm) paper Upper Cassette: Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope* * Envelope Feeder Attachment Kit B (standard) is required. Lower Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Letterhead, Envelope* * Envelope Attachment Kit A (standard) is required.	Copy Density	Automatic or Manual (9 Levels)
Supported media sizes	Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm Envelopes: COM10 No.10, Monarch, ISO-C5, DL Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm Upper Cassette: Standard size: A4, A5, A5R, A6R, B5 Custom size: 105.0 x 148.0 mm to 297.0 x 215.9 mm Envelope: ISO-C5 * Envelope Feeder Attachment Kit B (standard) is required. Lower Cassette: Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 105.0 x 148.0 mm to 304.8 x 457.2 mm Envelope*: COM10 No.10, Monarch, DL * Envelope Attachment Kit A (standard) is required.	Magnification	25% - 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%, 141%, 200%, 400%
Supported media weights	Multi-purpose tray: 52 to 300 gsm Upper/Lower Cassette: 52 to 256 gsm Duplex: 52 to 220 gsm 4 Seconds or Less* *Time from device power on to when copy icon appears and is enabled to operate on the touch panel display From Sleep Mode: 10 Seconds or Less 10 Seconds or Less* *Time from device power on, until copy ready (not print reservation)	Copy Features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Sort, Job Build, N on 1, Different Size Originals, Sharpness, Erase Frame, Copy ID Card, Skip Blank Pages, Free Size Original, Colour Mode, Reserved copy, Copy Sample
Warm-Up Time (Quick start mode:ON)	4 Seconds or Less* *Time from device power on to when copy icon appears and is enabled to operate on the touch panel display From Sleep Mode: 10 Seconds or Less 10 Seconds or Less* *Time from device power on, until copy ready (not print reservation)	SCAN SPECIFICATIONS	
Dimensions (W x D x H)	565 x 687 x 891 mm	Type	Standard: Duplexing Automatic Document Feeder [2-sided to 2-sided] Optional: Platen Cover-Y3 Up to 100 sheets
Installation Space (W x D)	1168 x 1116 mm	Document Feeder Paper Capacity (80 gsm)	Up to 100 sheets
Weight	Approx. 74.7 kg including toner	Acceptable Originals and weights	Platen: Sheet, Book and 3-Dimensional objects Document Feeder media weight : 1-sided scanning: 30 to 128 gsm (BW), 64 to 128 gsm (CL) 2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL) Platen: max. scanning size: 297.0 x 431.8 mm Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6 Custom size: 128.0 x 139.7 mm to 297.0 x 431.8 mm
PRINT SPECIFICATIONS		Supported media sizes	Platen: max. scanning size: 297.0 x 431.8 mm Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6 Custom size: 128.0 x 139.7 mm to 297.0 x 431.8 mm
Print Speed	1-sided (BW/CL): Up to 26/26 ppm (A4, A5, A5R, A6R), Up to 20/20 ppm (A4R), Up to 15/15 ppm (A3) 2-sided (BW/CL): Up to 26/26 ipm (A4, A5R), Up to 20/20 ipm (A4R), Up to 15/15 ipm (A3)		
Print Resolution (dpi)	Up to 1200 x 1200		
Page description languages	Standard: UFR II, PCL6 Optional: Adobe* PostScript*3™		

TECHNICAL SPECIFICATIONS

imageRUNNER C3326i

Scan Speed	DADF (ipm: BW/CL, A4): 1-sided Scanning: 70/70 (300 dpi, send), 51/42 (600 dpi, copy) 2-sided Scanning: 35/35 (300 dpi, send), 25.5/25.5 (600 dpi, copy)	SECURITY SPECIFICATIONS	
Scan Resolution (dpi)	Scan for Copy: up to 600 x 600 Scan for Send: (Push,BW) up to 600 x 600, (Pull,BW) up to 600 x 600, (Push,CL) up to 300 x 300, (Pull,CL) up to 300 x 300 Scan for Fax: up to 600 x 600	Authentication and Access Control	User Authentication (Picture Login, Picture and PIN Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
Pull Scan Specifications	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows®10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022	Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print*), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS*), Send Data Security (Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support) *Requires optional uniFLOW Online / uniFLOW **Requires optional Universal Send Digital User Signature Kit-C1
Scan Method	PushScan, PullScan, Scan to Network, Scan to USB Memory Key, Scan to Mobile device, Scan to cloud-based services (uniFLOW Online/Online Express)	Network Security	TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, WPA3 support, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling/Enabling (Network Protocols/Applications, Remote UI, USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Scan and Send -Virus Concerns for E-mail Reception
SEND SPECIFICATIONS		Device Security	Standard Storage Initialize, Job Log Conceal Function, Protecting MFP Software Integrity, Checking MFD Software Integrity & Platform Firmware Resiliency (NIST SP800-193) with Automatic System Recovery (Verify System at Startup, Runtime Intrusion Detection enabled with McAfee Embedded Control),
Destination	Standard: E-mail/Internet FAX (SMTP), SMB3.1.1, FTP, WebDAV, Optional: Super G3 FAX	Device Management and Auditing	Administrator Password, Digital Certificate and Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Security Policy Setting, Remote Management Two-factor Authentication
Address Book	LDAP (2,000)/ Local (1,600) /Speed dial (200)	ENVIRONMENTAL SPECIFICATIONS	
Send resolution (dpi)	Push: 100 x 100, 150 x 150, 200 x 100 (Normal), 200 x 200 (Fine), 200 x 400*(SuperFine), 300 x 300, 400 x 400*(UltraFine), 600 x 600* Pull: 75 x 75, 100 x 100, 150 x 150, 200 x 200, 300 x 300, 400 x 400*, 600 x 600* *Colour mode is black and white only	Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80% RH (Relative Humidity)
Communication protocol	File: FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV Email/iFax: SMTP (send), POP3 (receive)	Power source	220-240V 50/60Hz 4A
File Format	Standard: TIFF (MMR), JPEG *, PDF (Compact, Searchable, PDF/A-1b, Encrypted), XPS (Compact, Searchable), PDF/XPS (Device Signature, Office Open XML (PowerPoint, Word) Optional: PDF (Trace & Smooth), PDF/XPS (User Signature) *Single page only	Power consumption	Maximum: Approx. 1,500 W Standby: Approx. 44 W*1 Sleep mode: Approx. 2.0W*2, Approx. 1.0W*3 *1 Reference value: measured one unit *2 Wireless LAN power save mode OFF *3 Wireless LAN power save mode ON **2*3 Sleep mode is not available in all circumstances due to certain settings.
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation	Noise levels (BW/CL)	Typical Electricity Consumption (TEC)*: 0.32 kWh Note: As per US Energy Star 3.0 For detailed information relating to Erp:Lot6/26 regulation, please go to: https://www.canon-europe.com/for_work/lot26/ Sound Power Level (LWA.m) Active (1-sided) : 6.0B*1, 0.3B*1 Sound Pressure Level (LpAm) Bystander's position: Active (1-sided) : 46 dB*1 *1 Reference value: measured only one unit with ISO7779, described with ISO9296:2017
FAX SPECIFICATIONS		Standards	Blue Angel (Applied for)
Maximum Number of Connection Lines	1	CONSUMABLES	
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps	Toner Cartridge	C-EXV 65 Toner BK/C/M/Y
Compression Method	MH, MR, MMR, JBIG	Toner Yield	(Estimated Yield @ 5% Coverage) C-EXV 65 Toner BK: 17,500 pages C-EXV 65 Toner C/M/Y: 11,000 pages
Resolution (dpi)	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine), 200 x 100 (Normal)		
Sending/Receiving Size	Sending: A3, A4, A4R, A5*1, A5R*1, B4, B5*2, B5R*1 Receiving: A3, A4, A4R, A5R, B4, B5, B5R *1 Sent as A4 *2 Sent as B4 short		
FAX memory	Up to 30,000 pages		
Speed dials	Max. 200		
Group dials/destinations	Max. 199 dials		
Sequential broadcast	Max. 256 addresses		
Memory backup	Yes		
Fax Features	Sender's Name (TTI), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox		
STORE SPECIFICATIONS			
Memory Media	Standard: USB Memory		

TECHNICAL SPECIFICATIONS

imageRUNNER C3326i

SOFTWARE AND PRINTER MANAGEMENT

Tracking and reporting
Remote management tools

uniFLOW Online Express
iW Management Console
eMaintenance
Content Delivery System
ScanGear

Scanning software

PAPER SUPPLY OPTIONS

Cassette Feeding

Cassette Feeding Unit-AW1:

Paper Capacity: 550 sheets x 2 (1,100 sheets) (80 gsm)
Paper Type: Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead
Paper Size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R,
Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm
Paper Weight: 52 to 256 gsm
Power Source: From the Main Unit
Dimensions (W x D x H): 565 x 635 x 248 mm
Weight: Approx. 16.0 kg

OUTPUT OPTIONS

Inner Tray

Inner 2way Tray-M1:

Tray Capacity (80 gsm paper)
Upper tray: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R: 100 sheets
Lower tray (standard tray): A4, A5, A5R, A6R, B5, B5R: up to 250 sheets
SRA3, A3, A4R, B4: up to 100 sheets
Paper Weight: 52 to 300 gsm
Dimensions (W x D x H): 428 x 405 x 88 mm
Weight: Approx. 0.7 kg

Copy Tray

Copy Tray-T1:

Capacity (with 80gsm paper):
A4, A5R, B5, B5R: 100 sheets
A3, A4R, B4: 75 sheets
Dimensions (W x D x H): 442 x 373 x 176 mm (attached to the main unit, when the extension tray is extended) Weight: Approx. 0.5kg

Inner Finisher

Inner Finisher-L1:

Tray Capacity (with 80gsm paper):
Upper Tray: A4, A5, A5R, B5: approx. 50 sheets
SRA3, A3, A4R, A6R, B4, B5R: approx. 50 sheets
Lower Tray: A4, A5, A5R, B5: approx. 500 sheets
SRA3, A3, A4R, B4, B5R: 250 sheets
A6R: 30 sheets
Envelope: 10 sheets
Paper Weight: 52 to 300 gsm
Staple Position: Corner, Double
Staple Capacity:
A4, B5: 50 sheets (52 to 90 gsm)
A4R : 40 sheets (52 to 90 gsm)
A3, B4: 30 sheets (52 to 90 gsm)
Eco Staple:
A3, A4, B4, B5: 10 sheets (52 to 64 gsm)
8 sheets (65 to 81.4 gsm)
6 sheets (82 to 105 gsm)
Staple On Demand: approx. 40 sheets (80 gsm)
Dimensions (W x D x H): 575 x 525 x 225 mm (when the extension tray is extended)
Weight: Approx. 9.1 kg

Inner 2/4 Hole Puncher

Inner 2/4 Hole Puncher-D1 (Requires Inner Finisher-L1):
Two or Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size:
Two holes: A3, A4, A4R, A5, B4, B5, B5R,
Four holes: A3, A4

Inner 4 Hole Puncher

Inner 4 Hole Puncher-D1 (Requires Inner Finisher-L1):
Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size: A3, A4, A4R, A5, B4, B5, B5R

HARDWARE ACCESSORIES

Card Readers
Others

IC Card Reader Attachment-B4
Platen Cover-Y3

SYSTEM AND CONTROLLER OPTIONS

Print Accessories

PCL International Font Set-A1
PS Printer Kit-CS1

Data Storage

Optional Data Storage Kit-A1

Send Options

Universal Send Trace & Smooth PDF Kit-A1
Universal Send Digital User Signature Kit-C1

Barcode Printing

Barcode Printing Kit-D1

System Accessories

Copy Control Interface Kit-D1

Fax Accessories

Super G3 FAX Board-BN1
Remote Fax Kit-A1

OTHER OPTIONS

Accessibility Accessories

ADF Access Handle-A1
Media Adjustment kit-A1

Staple Cartridges

Staple-P1

Software & Solutions



Compatibility



Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2052525
canon.ie

Canon (UK) Ltd
The Bower
4 Roundwood Avenue
Stockley Park
Uxbridge
UB11 1AF

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2023