



## imageRUNNER ADVANCE DX 719/619/529 Series

# CONNECT SECURELY, TRANSFORM DIGITALLY

INNOVATIVE SCAN TECHNOLOGY AND SMART SOFTWARE WORK HAND-IN-HAND

The future of business is digital. Canon imageRUNNER ADVANCE DX is a new generation of smart multifunction devices, designed to support and accelerate every step of your digital transformation. Built with Canon's imageRUNNER ADVANCE DNA, state-of-the-art technology and software work hand-in-hand to digitise, automate and optimise content-centric workflows.

Canon's imageRUNNER ADVANCE DX 719/619/529 Series offers smart and secure A4 mono multifunction devices with all-in-one toner cartridges; maximising efficiency, minimising downtime and delivering 360° security. Innovative scanning technology ensures accurate, streak-free scanning at speed, while uniFLOW Online Express (uFOE) cloud software offers streamlined device management and enhanced cloud connectivity as standard. Versatile design supports flexibility and space saving, with counter-top or floor-standing placement suitable for offices with small footprints and high productivity needs.



**CLOUD  
CONNECTIVITY**



**PRODUCTIVITY**



**SERVICEABILITY**



**SECURITY** **Trellix**



**SUSTAINABILITY**

# Canon

---

# imageRUNNER ADVANCE DX 719/619/529 Series



## CLOUD CONNECTIVITY

- Cloud-based software-as-standard uniFLOW Online Express (uFOE) offers a single integrated solution to increase device security and simplify print management
- Securely scan and print documents from anywhere, with enhanced cloud connectivity
- Re-usable print formats allow easy access to documents in the cloud
- Canon's MEAP platform optimises processes by integrating with document capture and output management solutions such as uniFLOW Online\*
- Device offers native applications such as AirPrint, Mopria, Universal Print by Microsoft and Canon PRINT Business App



## SECURITY

- Verify System at Start-up supporting Platform Firmware Resiliency (NIST SP800-193) and Automatic Recovery, SIEM support and McAfee Embedded Control analyse the device in real-time to detect and prevent external attacks
- TPM 2.0 (Trusted Platform Module) comes as standard and securely stores encryption keys, such as passwords
- Set up device authentication, two-factor authentication and device function restrictions for

both device and cloud-based security measures

- Encrypted SSD storage extends data protection and is more resistant to vibration and shock for increased reliability
- Upgrade to uniFLOW Online\* for enhanced secure printing, mobile printing, and guest printing from any device
- Data privacy across your network is ensured with IPsec, port filtering and TLS 1.3 & WPA3 support
- Step-up security further with easy-to-programme Security Navigator or let Canon's experts create best solution for your business environment



## PRODUCTIVITY

- Print and scan up to 71 ppm and 190 ipm
- Automatically file documents with cloud-based Filing Assist from uniFLOW Online\*
- Alleviate concerns for physical device operation, without compromising user experience, by applying optional antimicrobial film to all common touch points
- Efficiently digitise documents with one-touch workflows and shortcut buttons on the Home screen
- Enable flexible hybrid working and minimise device interaction with continuous user experience through the Canon PRINT Business app
- Boost productivity with stapling of up to 50 sheets with the optional Instant Stapler accessory – small enough to fit on top of devices or desks, anywhere in the office, home or co-working space



## SUSTAINABILITY

- Edit print settings at device-level for accurate scan output
- Quiet operation and reduced paper hitting sounds during scanning is enabled thanks to technologies such as digital registration and a smooth ADF internal structure
- Eco Recovery mode decreases power consumption to save energy and lower running costs
- Automated and digitised processes minimise paper usage for a paperless office
- Reduce waste with high-quality scanning, including digital deskewing and advanced stain-resistant glass



## SERVICEABILITY

- Save costs and increase device uptime with innovative enhancements to frequently replaced hardware components as part of our evolving imageRUNNER ADVANCE DX portfolio
- Reduce technician visits with quick, safe, and accurate user replacement of consumable parts
- Long-life parts reduce the frequency of replacement while screw-free fastenings allow parts to be replaced faster and more efficiently

\*uniFLOW Online is available as a Device Based Cloud Subscription for Document Output and Capture Management. Based on business needs, users can upgrade to uniFLOW Online to unlock a range of advanced benefits including: increased security with user authentication methods; personalised workflows to enhance productivity; reduced wastage by releasing jobs at the device; an intuitive cloud dashboard to leverage real-time data; greater control over access and usage to reduce print costs.

NOTE – Certain features are only enabled with the combination of IR ADV DX and uniFLOW Online

## QUICK FACTS



- **Format:** Mono A4
- **Paper Supply Capacity (Max):** 3,200 sheets
- **Warm-up time:** 4 seconds or less
- **Finishing Capabilities:** Collate, Group, Offset\*, Staple\* (\*only available with Finisher models. Offset available with upper tray)
- **Supported File Types:** PDF, EPS, TIFF, JPEG, and XPS




- **Print speed:** 52-71 ppm (A4)
- **Scan speed:** 190 ipm (A4)



- **Print Languages:** UFR II, PCL6, Adobe® PostScript 3™
- **Print Resolution:** 600 x 600 to 1,200 x 1,200 (equivalent)

- Enhanced cloud connectivity enables collaborative document access from anywhere, with re-usable formats for easy handling
- Accurate, high-speed scanning is facilitated by Canon's innovative new paper feeding mechanism and stain-resistant glass
- Efficient workflow automation means documents are intuitively scanned, searched and stored with applications including OneDrive, SharePoint, Concur and Dropbox
- Verify System at Start-up, McAfee Embedded Control software, alongside other security features, offers complete peace of mind and 360° protection covering document, network and device
- Simplified print management is enabled with centrally-managed print settings and device usage analysis, provided through native uniFLOW Online Express (uFOE)
- Quiet ADF operation, low energy consumption and reduced emissions lower environmental impacts
- Easy, simplified maintenance is enabled with the all-in-one toner cartridge
- Versatile design with counter-top or floor-standing options to fit in any space

## TAILORED SOLUTIONS TO MEET EVERY CHALLENGE



Canon's Digital Transformation Services (DTS), bring together our leading hardware and software into an integrated technology ecosystem, designed to support your transformation journey. This offering combines Managed Print Services and Workspace Collaboration solutions, to help you gain transparency and control over the entire document lifecycle.



Canon Ireland  
3006 Lake Drive  
Citywest, Saggart  
Co. Dublin, Ireland  
Telephone No: 01 2052400  
Facsimile No: 01 2052525  
canon.ie

Canon (UK) Ltd  
The Bower  
4 Roundwood Avenue  
Stockley Park  
Uxbridge  
UB11 1AF

Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
© Canon Europa N.V., 2023


# EVOLVE YOUR BUSINESS' PRINT ENVIRONMENT WITH SMART, HIGH-SPEED, MONO A4 MULTIFUNCTION DEVICES



Canon Europe Ltd.  
BLI 2023-2024 Most Reliable A3 Brand

## MAIN CONFIGURATION OPTIONS

Choice of paper supply options\*



\*Paper supply options include up to three additional cassettes for non finisher models (i series) and up to two additional cassettes for finisher models (iZ series)

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the [online product configurator](#).

The Unified Firmware Platform (UFP) ensures that the latest feature upgrades and protection are available, for an enhanced user experience across the entire IR ADVANCE DX portfolio.

# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE DX 719/619/529 Series

<b>MAIN UNIT</b>		<b>Fonts</b>	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2 *1 Optional PCL International Font Set-A1 is required. *2 Optional Barcode Printing Kit-D1 is required.
<b>Machine type</b>	A4 Monochrome Laser Multifunctional	<b>Print Features</b>	Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Toner Reduction, Poster Printing, Forced Hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer
<b>Core functions</b>	Print, Copy, Scan, Send and optional Fax	<b>Operating System</b>	UFRIL: Windows® 8.1/10/11/Server2012/Server2012 R2/ Server2016/Server2019/Server2022, Mac OS X (10.11 or later)  PCL: Windows® 8.1/10/11/Server2012/Server2012 R2/ Server2016/Server2019/Server2022  PS: Windows® 8.1/10/11/Server2012/Server2012 R2/ Server2016/Server2019/Server2022, Mac OS X (10.11 or later)  PPD: Windows® 8.1/10/11, Mac OS X (10.11 or later)
<b>Processor</b>	1.8GHz Dual Core Processor	<b>COPY SPECIFICATIONS</b>	
<b>Control Panel</b>	10.1" TFT LCD WSVGA Color Touch panel	<b>Copy Speed*</b>	iR-ADV DX 719i/719iZ 71 ppm (A4), 113 ppm (A5), 40 ppm (A5R, A6) iR-ADV DX 619i/619iZ 61 ppm (A4), 99 ppm (A5), 35 ppm (A5R, A6) iR-ADV DX 529i/529iZ 52 ppm (A4), 80 ppm (A5), 35 ppm (A5R, A6) *1-sided
<b>Memory</b>	Standard: 3.5GB RAM	<b>First-Copy-Out Time (A4)</b>	Approx. 5 seconds or less
<b>Hard Disk drive</b>	Standard: (SSD) 256 GB	<b>Copy resolution (dpi)</b>	600 x 600
<b>Interface Connection</b>	Network Standard: 1000Base-T/100Base-TX/10Base-T, Optional: Wireless LAN (IEEE 802.11b/g/n)  Others Standard: USB 2.0 x 2 (Host), USB 3.0 x 1 (Host), USB 2.0 x 1 (Device) Optional: Copy Control Interface	<b>Multiple Copies</b>	Up to 9,999 copies
<b>Paper Supply Capacity (A4, 80 gsm)</b>	Standard: 650 sheets 100-sheets Multi-purpose tray 550-sheets Paper cassette x 1 Maximum: 3,200 sheets (with High Capacity Cassette Feeding Unit-D1)	<b>Copy Density</b>	Automatic or Manual (9 Levels)
<b>Paper Output Capacity (A4, 80 gsm)</b>	Standard model (iR-ADV DX 719i/619i/529i): 500 sheets Finisher model (iR-ADV DX 719iZ/619iZ/529iZ): 1,000 sheets	<b>Magnification</b>	Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%(1:1), 141%, 200%, 400%
<b>Finishing Capabilities</b>	Standard model (iR-ADV DX 719i/619i/529i): Collate, Group Finisher Model (iR-ADV DX 719iZ/619iZ/529iZ): Collate, Group, Offset*, Staple *available with upper tray	<b>Copy Features</b>	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Two-sided Original, Job Build, N on 1, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Copy ID Card, Skip Blank Pages, Reserved copy, Copy Sample
<b>Supported Media Types</b>	Multi-purpose tray: Thin, Plain, Recycled, Heavy, Color, Transparency, Bond, Envelope Paper Cassette: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched	<b>SCAN SPECIFICATIONS</b>	
<b>Supported Media Sizes</b>	Multi-purpose tray: Standard size: A4, A5, A5R, A6, B5 Custom size: 76.2 x 127.0 mm to 216.0 x 355.6 mm Envelope: COM10 No.10, Monarch, DL, ISO-C5 Paper Cassette: Standard size: A4, A5, A5R, A6, B5 Custom size: 99.0 x 148.0 mm to 216.0 x 297.0 mm	<b>Standard type</b>	Single-pass Duplexing Automatic Document Feeder* [2-sided to 2-sided (Automatic)] * Detect Feeder Multi Sheet Feed is supported.
<b>Supported Media Weights</b>	Multi-purpose tray: 60 to 199 gsm Paper Cassette: 60 to 135 gsm Duplex: 60 to 120 gsm	<b>Document Feeder Paper Capacity (80 gsm)</b>	100 Sheets
<b>Warm-up Time</b>	Quick Startup Mode: 4 Seconds or less* *Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display. From Sleep Mode: 10 Seconds or less From Power On: 10 Seconds or Less* **Time from device power on, until copy ready (not print reservation)	<b>Acceptable Originals and Weights</b>	Platen: Sheet, Book, and 3-Dimensional Objects Document Feeder media weight: 1-sided scanning: 42 to 128 gsm (BW), 64 to 128 gsm (CL) 2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL) Note: Business card: 80 to 220 gsm Original width narrower than A6: 50 to 128 gsm
<b>Dimensions (W x D x H)</b>	Standard model (iR-ADV DX 719i/619i/529i): 500 x 598 x 617 mm Finisher model (iR-ADV DX 719iZ/619iZ/529iZ): 502 x 598 x 814 mm	<b>Supported Media Sizes</b>	Platen scanning size: up to 216.0 x 355.6 mm Document Feeder media size: A4, A5R, A6, B5, Custom size: 48.0 x 128.0 mm to 216.0 x 355.6 mm Business card: 48.0 x 85.0 mm to 55.0 x 91.0 mm
<b>Installation Space(W x D)</b>	Standard model/ Finisher model: 1,052 x 823 mm (with left CRG door open + right door open + the cassette drawer open)	<b>Scan Speed (ipm; BW/CL, A4)</b>	Send (300 x 300 dpi): up to 95/190 when Automatic Colour Select "OFF": 1-sided Scanning: 95 2-sided Scanning: 190 Automatic Color Select "ON": 1-sided Scanning: 50 2-sided Scanning: 100 Copy (600 x 600 dpi, BW only): 1-sided Scanning: 95 2-sided Scanning: 140
<b>Weight</b>	Standard model (iR-ADV DX 719i/619i/529i): Approx. 37 kg including toner Finisher model (iR-ADV DX 719iZ/619iZ/529iZ): Approx. 46 kg including toner	<b>Scan Resolution (dpi)</b>	Scan for Copy: up to 600 x 600 Scan for Send: (Push) up to 600 x 600 (SMB/FTP/ WebDAV/IFAX), (Pull) up to 600 x 600 Scan for Fax: up to 600 x 600
<b>PRINT SPECIFICATIONS</b>		<b>Pull Scan Specifications</b>	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows®7/ 8.1/ 10/ Server2008/ Server2008 R2/ Server2012/ Server2012 R2/ Server 2016 As of Feb. 2020
<b>Print Speed*</b>	iR-ADV DX 719i/719iZ 71 ppm (A4), 113 ppm (A5), 40 ppm (A5R, A6) iR-ADV DX 619i/619iZ 61 ppm (A4), 99 ppm (A5), 35 ppm (A5R, A6) iR-ADV DX 529i/529iZ 52 ppm (A4), 80 ppm (A5), 35 ppm (A5R, A6) *1-sided	<b>Scan Method</b>	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Space, Scan to Network, Scan to USB Memory Key, Scan to Mobile devices, Scan to cloud (uniFLOW Online - Optional)
<b>Print Resolution (dpi)</b>	600 x 600 to 1,200 x 1,200 (equivalent)		
<b>Duplex Print Speed (A4/LTR)</b>	719i/719iZ: 58ipm/62ipm 619i/619iZ: 50ipm/53ipm 529i/529iZ: 50ipm/53ipm		
<b>Page description languages</b>	Standard: UFR II, PCL6, Adobe® PostScript®3™		
<b>Direct Print</b>	Supported file types: TIFF, JPEG, PDF, EPS, and XPS		
<b>Printing from mobile and cloud</b>	AirPrint, Mopria, Universal Print by Microsoft, Canon PRINT Business, and uniFLOW Online (optional) A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.		

# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE DX 719/619/529 Series

## SEND SPECIFICATIONS

<b>Destination</b>	Standard: E-mail/Internet FAX (SMTP), SMB3.1.1, FTP, WebDAV, Mail Box Optional: G3 FAX, IP Fax
<b>Address Book</b>	LDAP (2,000)/Local (1,600)/Speed dial (200)
<b>Send resolution (dpi)</b>	Push: up to 600 x 600 Pull: up to 600 x 600
<b>Communication protocol</b>	File: FTP(TCP/IP), SMB3.1.1 (TCP/IP), WebDAV E-mail/I-Fax: SMTP, POP3
<b>File Format</b>	Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
<b>Universal Send Features</b>	Original Type Selection, Two-sided Original, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages

## FAX SPECIFICATIONS

<b>Maximum Number of Connection Lines</b>	(Optional) 1
<b>Modem Speed</b>	Super G3: 33.6 kbps G3: 14.4 kbps
<b>Compression Method</b>	MH, MR, MMR, JBIG
<b>Resolution (dpi)</b>	400x400 (Ultra Fine), 200x400 (Super Fine), 200x200 (Fine), 200x100 (Normal)
<b>Sending/Receiving Size</b>	A4, A5*, A6* and B5* / A4, A5, B5 *Sent as A4
<b>FAX memory</b>	Up to 30,000 pages (2,000 jobs)
<b>Speed dials</b>	Max. 200
<b>Group dials/destinations</b>	Max. 199 dials
<b>Sequential broadcast</b>	Max. 256 addresses
<b>Memory backup</b>	Yes
<b>Fax Features</b>	Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log

## STORE SPECIFICATIONS

<b>Mail Box (Number supported)</b>	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes Maximum 30,000 Pages (2,000 jobs) Stored
<b>Advanced Space</b>	Communication Protocol: SMB or WebDAV Supported Client PC: Windows® 8.1/10 Concurrent Connections (Max.): SMB: 64, WebDAV: 3
<b>Advanced Space available disc space</b>	Standard: 16 GB
<b>Advanced Space Features</b>	Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to public, URI TX, Backup/Restore

## SECURITY SPECIFICATIONS

<b>Authentication and Access Control</b>	User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
<b>Document Security</b>	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print*), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) *1 Requires uniFLOW Online / uniFLOW

## Network Security

<b>Network Security</b>	TLS 1.3, FTPS, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), WPA3 support, Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Space in the MFP, Scan and Send -Virus Concerns for E-mail Reception
<b>Device Security</b>	Protecting SSD Data [SSD Data Encryption (FIPS 140-2/140-3)], SSD Lock, Standard SSD Initialize, Trusted Platform Module (TPM 2.0), Job Log Conceal Function, Protecting MFP Software Integrity, Checking MFD Software Integrity & Platform Firmware Resiliency (NIST SP800-193) with Automatic System Recovery (Verify System at Start-up, Runtime Intrusion Detection enabled with McAfee Embedded Control), HCD-PP Common Criteria Certification *validation pending
<b>Device Management and Auditing</b>	Administrator Password, Remote Management Two-factor Authentication, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting Device administration and Security administration Passwords

## ENVIRONMENTAL SPECIFICATIONS

<b>Operating Environment</b>	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity) 220-240 V, 50/60 Hz, 4.8 A
<b>Power source</b>	Maximum: Approx. 1,500 W Copying (with DADF continuous scan): iR-ADV DX 719i/719iZ: 827.5 W*1 iR-ADV DX 619i/619iZ: 784.6 W*1 iR-ADV DX 529i/529iZ: 783.1 W*1
<b>Power consumption</b>	Network Printing: iR-ADV DX 719i/719iZ: 828.3 W*1 iR-ADV DX 619i/619iZ: 793.4 W*1 iR-ADV DX 529i/529iZ: 728.5 W*1 Standby: Approx. 28.92 W*2 Sleep mode: Approx. 1.0 W*2 *1 Reference value: measured one unit *2 1.0 W is not available in all circumstances due to certain settings.
	Typical Electricity Consumption (TEC)* rating iR-ADV DX 719i/719iZ: 0.73 kWh iR-ADV DX 619i/619iZ: 0.59 kWh iR-ADV DX 529i/529iZ: 0.49 kWh *As per USA Energy Star 3.0

## Noise levels

<b>Noise levels</b>	For detailed information relating to Erp:Lot6/26 regulation, please go to: <a href="https://www.canon-europe.com/for_work/lot26/">https://www.canon-europe.com/for_work/lot26/</a> Sound Power Level (LWA, m)* Active (1-sided) iR-ADV DX 719iZ/719i: 7.0 B, Kv 0.3 B /6.9 B, Kv 0.3 B iR-ADV DX 619iZ/619i: 6.8 B, Kv 0.3 B /6.8 B, Kv 0.3 B iR-ADV DX 529iZ/529i: 6.8 B, Kv 0.3 B /6.7 B, Kv 0.3 B *Reference value: measured only one unit with ISO7779, described with ISO9296 (2017) Sound Pressure (LpAm)* Bystander's position: Active(BW) (1-sided): iR-ADV DX 719i/719iZ: 56 dB iR-ADV DX 619i/619iZ: 55 dB iR-ADV DX 529i/529iZ: 54 dB Stand-by iR-ADV DX 719iZ/619iZ/529iZ: 25 dB iR-ADV DX 719i/619i/529i: 21 dB *Reference value: Measured only one unit with ISO7779, described with ISO9296 (2017) Blue Angel
---------------------	--

## Standards

## CONSUMABLES

<b>Toner Cartridges</b>	T03 Black
<b>Toner Yield</b>	Black: 51,500 pages Toner Cartridge yield in accordance with ISO/IEC 19752.

## SOFTWARE AND PRINTER MANAGEMENT

<b>Tracking and reporting</b>	For detailed information please visit our website <a href="https://www.canon-europe.com/business/">https://www.canon-europe.com/business/</a> Universal Login Manager (ULM) uniFLOW Online Express* * For more information, please refer to <a href="#">uniFLOW Online Express</a> <a href="#">uniFLOW Online</a>
<b>Remote management tools</b>	iW Management Console eMaintenance Content Delivery System
<b>Scanning software</b>	Network ScanGear
<b>Platform</b>	MEAP (Multifunctional Embedded Application Platform)
<b>Document Publishing</b>	Kofax PowerPDF (optional)



# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE DX 719/619/529 Series

## PAPER SUPPLY OPTIONS

### Cassette Module-AG1

Paper Capacity: 550 sheets (80 gsm)  
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched  
 Paper Size: A4, A5, A5R, A6, B5,  
 Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm  
 Paper Weight: 60 to 135 gsm  
 Power Source: From the Main Unit  
 Dimensions (W x D x H): 484 x 450 x 127 mm  
 (attached to the main unit)  
 Weight: Approx. 7 kg

### Envelope Cassette Module-A1

Paper Capacity: 75 Envelopes  
 Envelope Size: COM10 No.10, Monarch, DL, ISO-C5  
 Paper Weight: 80 to 100 gsm  
 Power Source: From the Main Unit  
 Dimensions (W x D x H): 484 x 450 x 127 mm  
 (attached to the main unit)  
 Weight: Approx. 7 kg

### Cassette Feeding Unit-AX1

Paper Capacity: 1,650 sheets (80 gsm)  
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched  
 Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm  
 Paper Weight: 60 to 135 gsm  
 Power Source: From the Main Unit  
 Dimensions (W x D x H): 642 x 657 x 456 mm  
 (attached to the main unit)  
 Weight: Approx. 45 kg

### Cassette Feeding Unit-AR1

Paper Capacity: 550 sheets (80 gsm)  
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched  
 Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm  
 Paper Weight: 60 to 135 gsm  
 Power Source: From the Main Unit  
 Dimensions (W x D x H): 642 x 657 x 456 mm  
 (attached to the main unit)  
 Weight: Approx. 19 kg

### High Capacity Cassette Feeding Unit-D1

Upper cassette:  
 Paper Capacity: 550 sheets (80 gsm)  
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched  
 Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm  
 Paper Weight: 60 to 135 gsm

Lower cassette:  
 Paper Capacity: 2,000 sheets (80 gsm)  
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Bond, Pre-punched  
 Paper Size: A4  
 Paper Weight: 60 to 135 gsm  
 Power Source: From the Main Unit  
 Dimensions (W x D x H): 642 x 657 x 456 mm  
 (attached to the main unit)  
 Weight: Approx. 27 kg

## OUTPUT FEATURES\*

### Finisher Model (IR-ADV DX 719IZ/ 619IZ/ 529IZ)

\*Paper capacity may vary with different paper type/size.

Tray Capacity (80 gsm):  
 Upper Tray: A4, A5R, B5: 400 sheets  
 Lower Tray: A4, A5R, B5: 100 sheets  
 Main unit output tray: A4, A5, A5R, A6, B5: 500 sheets  
 Paper Type: Thin, Plain, Recycled, Heavy, Color, Bond, Transparency\*, Envelope\*  
\*only for Main Unit Output tray  
 Staple Paper Weight: 60 to 120 gsm  
 Staple Position: Corner  
 Staple Paper Size: A4, Custom size (210.0 x 279.4 mm to 216.0 x 355.6 mm)  
 Staple Capacity: 30 sheets (60 to 90 gsm), 20 sheets (91 to 120 gsm)

## HARDWARE ACCESSORIES

### Card Readers

Various card readers available e.g. MiCard Plus. Please contact local Canon Office for more details.  
 Copy Card Reader-F1  
 Copy Card Reader Attachment-B5

## SYSTEM AND CONTROLLER OPTIONS

### Print Accessories

PCL International Font Set-A1

### Barcode Printing

Barcode Printing Kit-D1

### System Accessories

Copy Control Interface Kit-A1  
 Wireless LAN Board-D1

### FAX Accessories

Super G3 FAX Board-BM1  
 Remote Fax Kit-A1  
 IP FAX Expansion Kit-B1

## OTHER OPTIONS

### Accessibility Accessories

ADF Access Handle-A1

### Consumables

Staple-P1

## Software & Solutions



## Certifications and compatibility



**Canon Ireland**  
 3006 Lake Drive  
 Citywest, Saggart  
 Co. Dublin, Ireland  
 Telephone No: 01 2052400  
 Facsimile No: 01 2052525  
 canon.ie

**Canon (UK) Ltd**  
 The Bower  
 4 Roundwood Avenue  
 Stockley Park  
 Uxbridge  
 UB11 1AF

**Canon Inc.**  
 canon.com  
**Canon Europe**  
 canon-europe.com  
 English edition  
 © Canon Europa N.V., 2023