

COMPACT A4 MULTIFUNCTION DEVICES THAT CONTAIN ALL THE ESSENTIAL FEATURES YOU NEED FOR SMOOTH PRINTING AND SCANNING.

Compact yet powerful A4 colour multifunction devices, delivering all the essential features you need for reliable printing and scanning.

imageFORCE C1333 Series



MAXIMISED PRODUCTIVITY

Fast print and scan speeds with mobile and cloud connectivity will help you maximise business productivity. Quick machine warm-up time and fast printout time means you'll get the output you need in seconds.

360-DEGREE SECURITY

Keep documents, devices, and network safe with advanced security designed to simplify protection. Built-in tools make it easy to manage settings, whilst Canon's unique Security Settings Navigator helps minimise the need for IT support.

IMPROVED SUSTAINABILITY

Make a conscious effort to help the environment with devices that are built with recycled plastic and feature low energy consumption. Their lightweight size means they also have a low carbon footprint.

SMOOTH USER EXPERIENCE

An intuitive user interface helps with seamlessly carrying out print and scan workflows. Self-maintenance is simplified via an all-in-one toner cartridge, while for further help an online manual can easily be accessed via a QR code.

TECHNICAL SPECIFICATIONS

imageFORCE C1333 Series

MAIN UNIT	
Machine Type	A4 Color Laser Multifunctional
Core Functions	C1333F: Print, Copy, Scan, Send and Fax C1333: Print, Copy, Scan, Send
Processor	1.2GHz Single Core Processor
Control Panel	5" LCD Colour Touch Screen
Memory	RAM: 1.0GB
Storage	eMMC: 4.0GB
Interface Connection	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T Wireless LAN (IEEE 802.11b/g/n) OTHERS Standard: USB 2.0 (Host) x 2, USB 2.0 (Device) x 1 Optional: Copy Control Interface
Paper Supply Capacity (A4, 80gsm)	Standard: 250 sheets 50-sheet Multi-purpose tray x 1 550-sheet Paper cassette x 1 Maximum: 850 sheets (with 1 x Paper Feeder PF-K1)
Paper output capacity (A4, 80gsm)	150 sheets
Supported Media Types	Thin, Plain, Recycled, Color, Heavy, Bond, Label, Pre-Punched, Letterhead, Envelope
Supported Media Sizes	Multi-purpose tray: Standard size: A4, A5, A5R, A6, B5 Custom size: 76.0 x 127.0 mm to 216.0 x 356.0 mm Envelopes: COM10 No.10, Monarch, DL, ISO-C5 Envelope custom size: 76.0 x 127.0 mm to 216.0 x 356.0 mm Paper Cassette: Standard size: A4, A5, A5R, A6, B5 Custom size: 98.0 x 148.0 mm to 216.0 x 356.0 mm
Supported Media Weights	Multi-purpose tray: 60 to 176 gsm (Up to 200gsm with Coated Paper) Paper Cassette: 60 to 163 gsm (Up to 200gsm with Coated Paper) Duplex: 60 to 200 gsm
Warm-up Time	14 Seconds or less From Sleep Mode: 5.3 Seconds or less
Dimensions (W x D x H)	425 x 461 x 430 mm
Installation Space (W x D)	625 x 1117 mm
Weight*	C1333F: Approx. 23.5 Kg C1333: Approx. 23.3 Kg

*including regular toner

PRINT SPECIFICATIONS	
Print Speed (BW and CL)	1-sided: Up to 33 ppm (A4), Up to 44.9 ppm (A5R), Up to 60 ppm (A5) 2-sided: Up to 29.5 ipm (A4)
Print Resolution (dpi)	Up to 1,200 x 1,200
Page Description Languages	Standard: UFR II, PCL6, PCL5*, Adobe® PostScript®3™ *Commands supported only. Third party driver or direct printing from application required.™
Direct Print	Supported file types: PDF, TIFF/JPEG (From USB Memory)
Printing From Mobile And Cloud	AirPrint, Mopria, IPP Everywhere, Canon PRINT, uniFLOW Online, Universal Print
OS Standard Printing	Android/Windows® 10/Windows® 11/Chrome OS/macOS (11.2.2 or later) /iOS /iPadOS
Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, Barcode fonts*1 *1 Optional Barcode Printing Kit-D1 is required.
Print Features	Secured Print, Encrypted Secured Print, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Toner Reduction, Poster Printing, Print Date
Operating System	UFR II: Windows® 10/11/Server2016/Server2019/Server2022/Server2025, macOS (10.15 or later) PCL: Windows® 10/11/Server2016/Server2019/Server2022/Server2025 PS: Windows® 10/11/Server2016/Server2019/Server2022/Server2025, macOS (10.15 or later) PPD: Windows® 10/11, macOS (10.15 or later) As of June, 2025
COPY SPECIFICATIONS	
Copy Speed (BW and CL)	1-sided: Up to 33 ppm (A4) 2-sided: Up to 29 ipm (A4)
First-Copy-Out Time (A4, BW/CL)	ADF (A4): Colour Approx. 8.8 seconds or less Mono Approx. 7.6 seconds or less Platen (A4): Colour Approx. 9.4 seconds or less Mono Approx. 8.3 seconds or less
Copy Resolution (dpi)	600 x 600
Multiple Copies	Up to 999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	Variable zoom: 25% to 400% (1% Increments)
Copy Features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Two-sided Original, Sort, N on 1, Sharpness, Erase Frame, Copy ID Card, Copy Passport, Color Mode, Reserved copy

TECHNICAL SPECIFICATIONS

imageFORCE C1333 Series

SCAN SPECIFICATIONS	
Type	Single-pass Duplexing Automatic Document Feeder [2-sided to 2-sided (Automatic)]
Document Feeder Paper Capacity (80 gsm)	up to 50 Sheets
Document Feeder Acceptable Paper Weight	Document Feeder media weight: 50 to 105 gsm
Supported Media Sizes	Platen scanning size: up to 215.9 x 297 mm Document Feeder media size: A4, A5R, A6, B5 Custom size: 48.0 x 85.0 mm to 216.0 x 355.6 mm
Scan Speed (ipm: A4)	Send (300 x 300 dpi): 1-sided Scanning: 50 (BW), 40 (CL) 2-sided Scanning: 100 (BW), 80 (CL) Copy: Scan Speed Priority (300x600dpi: default) 1-sided Scanning: 40 (BW), 20 (CL) 2-sided Scanning: 80 (BW), 40 (CL) Image Quality Priority (600x600dpi) 1-sided Scanning: 20 (BW), 10 (CL) 2-sided Scanning: 40 (BW), 20 (CL)
Scan Resolution (dpi)	600 x 600
Pull Scan Specifications	ScanGear MF and MF Scan Utility for both TWAIN and WIA Supported OS: Windows® 10/11/Server 2016/Server 2019/Server 2022/Server 2025 As of June, 2025
Scan Method	Push Scan, Pull Scan, Scan to Network, Scan to USB Memory Key, Scan to cloud (Application Library/uniFLOW Online)

SEND SPECIFICATIONS	
Destination	Standard: E-mail/Internet FAX (SMTP*), SMB, FTP, WebDAV, Mail Box Optional: Super G3 FAX, IP Fax * Available OAuth 2.0 authentication method on Microsoft 365 and Google Workspace
Address Book	LDAP (50)/Local (300)/Speed dial (281)
Communication Protocol	File: FTP (TCP/IP), SMB3.1.1 (TCP/IP) E-mail/I-Fax: SMTP, POP3
File Format	TIFF, JPEG, PDF (Compact, Searchable, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature)
Universal Send Features	Original Type Selection, Two-sided Original, Density Adjustment, Sharpness, Preview, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals

FAX SPECIFICATIONS	
Maximum Number Of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400x400 (Ultra Fine), 200x400 (Super Fine), 200x200 (Fine), 200x100 (Normal)
Sending/Receiving Size	Sending: A4, A5R*, A6*, B5* Receiving: A4, A5, A5R, B5 * Sent as A4
FAX Memory	Up to 512 pages (90 jobs)
Speed Dials	Max. 281
Group Dials/Destinations	Max. 299 dials
Sequential Broadcast	Max. 310 addresses
Memory Backup	Yes
Fax Features	Sender's Name (TTI), Direct Send, Preview, TX Report, Sequential Broadcasting

SECURITY SPECIFICATIONS	
Authentication And Access Control	Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online/uniFLOW*1(PIN Login, Card Login, Card and PIN Login) *1 Optional
Document Security	Print Security (Secure Print, Encrypted Secure Print, uniFLOW Secure Print*1), Scan Security (Encrypted PDF, Device Signature PDF/XPS), Send Data Security (Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History) *1 Optional
Network Security	TLS 1.3, IPSec (FIPS140-3), IEEE802.1X authentication, SNMPv3, Firewall Functionality (IP/MAC Address Filtering), WPA3 support (Wi-Fi), Enabling/Disabling (Network Applications, Remote UI, USB Interface), G3 FAX separation from LAN, USB Port separation from LAN
Device Security	Job Log Conceal Function, Protecting MFP Software Integrity: Verify System at Startup (NIST SP800-193: Protection), Checking MFP Software Integrity & Platform Firmware Resiliency: Automatic System Recovery (NIST SP800-193: Recovery)
Device Management And Auditing	Administrator Password, Digital Certificate And Key Management, Cooperating with External Security Audit System (Security Information and Event Management), Security Policy Setting

TECHNICAL SPECIFICATIONS

imageFORCE C1333 Series

ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity/No condensation)
Power Source	220-240V(±10%) 50/60Hz (±2Hz)
Power Consumption	Maximum: Approx. 1,380 W Active printing: Approx. 700W Sleep mode: Approx. 1.0 W Typical Electricity Consumption (TEC): 0.30 kWh/week (230V) For detailed information relating to Lot26 regulation, please go to: https://www.canon-europe.com/business/lot26/
Noise Levels (BW/CL)	Sound Pressure: Active: Simplex 51dB / Duplex 51dB (BW), 50dB (CL) Standby: 29 dB Sound Power: Active: 65dB or less Standby: 41dB or less
Standards	Blue Angel
CONSUMABLES	
Toner Cartridges	TONER T12 Black (7,400 pages*) TONER T12 Cyan (5,300 pages*) TONER T12 Magenta (5,300 pages*) TONER T12 Yellow (5,300 pages*) *Based on ISO/IEC 19798
SOFTWARE AND PRINTER MANAGEMENT	
Tracking and Reporting	uniFLOW Online
Remote Management Tools	iW Enterprise Management Console Monitoring Service
Scanning Software	ScanGear MF and MF Scan Utility
Optimisation Tools	Canon Driver Configuration Tool Application Library
PAPER SUPPLY OPTIONS	
PAPER FEEDER PF-K1	Paper Capacity: 550 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Color, Heavy, Bond, Label, Pre-Punched, Letterhead Paper Size: A4, A5, A5R, A6, B5 Custom size: 100.0 x 148.0 mm to 216.0 x 356.0 mm Paper Weight: 60 to 163 gsm (Up to 200gsm with Coated Paper)

HARDWARE ACCESSORIES	
Others	MiCard Attachment Kit-B1
SECURITY OPTIONS	
Data Security	Send PDF Security Feature Set-E1
SYSTEM & CONTROLLER OPTIONS	
Print Accessories	Barcode Printing Kit-E1E
System Accessories	Copy Control Interface Kit-C1
Fax Accessories	TEL 6 Kit Long Cord* (Telephone handset) *Only available for C1333F



Certifications and compatibility



Canon UK Ltd.
4 Roundwood
Avenue
Stockley Park
Uxbridge
UB11 1AF
canon.co.uk

Canon Ireland Ltd.
3090 Lake Drive
Citywest Business Campus
Saggart, Co. Dub
D24 XN47
canon.ie