

Ordering code

Example: Fuzo-RD-5-20-T-188-1D-Black

Fuzo round series 5"	Pole Height	Pole Thickness	Tenon Mounting	Drilling Mounting	Finish
 Fuzo-RD-5	10 FT	T-188	T Tenon 2-3/8"	1D 1 drilling	Black
	15 FT	T-250	TC Custom tenon	2D 2 drillings at 180°	Bronze
	20 FT			2D90 2 drillings at 90°	Gray
	24 FT			3D120 3 drillings at 120°	White
	30 FT			4D 4 drillings at 90°	RAL / custom
				DC Custom drilling	

EPA

Height (ft)	Bolt Circle (mm)	L-Shaped Anchor Bolts (in)	Bolt Projection (in)	Thickness (in)	Weight (kg)	100 Km/h 62.14 MPH (ft²)	120 Km/h 74.56 MPH (ft²)	140 Km/h 86.99 MPH (ft²)
10	255	1 x 33 + 5 HDG	4 ½	0,188	43,87	44,96	31,01	22,58
15	255	1 x 33 + 5 HDG	4 ½	0,188	65,81	29,03	19,80	14,20
20	255	1 x 33 + 5 HDG	4 ½	0,188	87,74	20,85	13,97	9,78
24	255	1 x 33 + 5 HDG	4 ½	0,188	105,29	16,65	10,94	7,44
30	255	1 x 33 + 5 HDG	4 ½	0,188	131,62	12,30	7,74	4,94

