

Ordering code

Example: Fuzo-SQ-5-20-T-188-1D-Black

Fuzo square series 5"	Pole Height	Pole Thickness	Tenon Mounting	Drilling Mounting	Finish
 Fuzo-SQ-5	10 FT	T-188	T Tenon 2-3/8"	1D 1 drilling	Black
	15 FT	T-250	TC Custom tenon	2D 2 drillings at 180°	Bronze
	20 FT			2D90 2 drillings at 90°	Gray
	24 FT			4D 4 drillings at 90°	White
	30 FT			DC Custom drilling	RAL / custom

EPA

Height (ft)	Bolt Circle (mm)	L-Shaped Anchor Bolts (in)	Bolt Projection (in)	Thickness (in)	Weight (kg)	100 Km/h 62.14 MPH (ft ²)	120 Km/h 74.56 MPH (ft ²)	140 Km/h 86.99 MPH (ft ²)
10	255	1 x 33 + 5 HDG	4 ½	0,188	55,86	75,83	52,02	37,65
15	255	1 x 33 + 5 HDG	4 ½	0,188	83,79	48,44	32,63	23,06
20	255	1 x 33 + 5 HDG	4 ½	0,188	111,72	34,20	22,37	15,19
24	255	1 x 33 + 5 HDG	4 ½	0,188	134,06	26,76	16,91	10,92
30	255	1 x 33 + 5 HDG	4 ½	0,188	167,58	18,94	11,03	6,20

