





O White

| TECHNICAL INFORMATION |   |                  |                             |
|-----------------------|---|------------------|-----------------------------|
| Homologation          | L1e-B (comparable to a 50cc.)                   | Loading capacity | 84 units                    |
| Engine                | Vmoto   | LxWxH            | 1940 mm*730 mm*1160 mm      |
| Rated power           | 2.0 kW  | Wheelbase        | 1327 mm                     |
| Max power             | 2.4 kW  | Ground clearance | 145 mm                      |
| Battery model         | Polymer lithium battery                         | Seat height      | 780 mm                      |
| Battery capacity      | 60 V/45 Ah                                      | Rims             | Fr. 1.85-16 / Rr. 2.5-14    |
| Charging time         | 3.5 h (Fast Charger) - 6 h (Normal Charger)     | Tires            | Fr. 90/80-16 / Rr. 90/90-14 |
| Charging power        | 1000 W (Fast Charger)<br>600 W (Normal Charger) | Suspension       | Hydraulic damping system    |
| Range*                | 80 Km*  | Weight           | 101 Kg                      |
| Max speed             | 45 Km/h   | Brakes           | CBS                         |
| Climbing angle        | 14°   | Colours          | White                       |

<sup>\*</sup>WMTC Stage 3

Attention: In e photos and technical information contained in this catalog may refer to prototypes subject to changes during production and are for purely illustrative and reference purposes, therefore they are not binding for vimoto international. Who to be held responsible for any printing and/or translation errors. This catalog is transnational and therefore some products may not be available and/or their characteristics may vary according to local laws. Not all colors and versions are available in every country. Who reserves the right to make changes and improvements to any product without prior notice or to make such changes to products already sold. Further characteristics of the products are contained in the relevant user manuals. The products represented are final versions and are therefore subject to significant changes at the discretion of Vimoto without notice. The photographs published in this catalogs show only professional drivers in controlled road conditions. Do not try to initiate this driving behavior as it could be danger rous for you or other people on the road. This catalogue, including, but not limited to, trademarks, logos, texts, images, graphics and table of contents, constitutes the intellectual property of Vimoto, or in any case Vimoto has the right to reproduce it. Any total or partial reproduction, modification or other use of the catalog or its contents is prohibited, including publication on the Internet without the prior written consent of Vimoto. Actual battery consumption may vary based on many factors, including, but not limited to, riding style, maintenance performed, weather conditions, surface characteristics, tire pressure, load, rider weight and the passenger, the accessories. Curb weights are considered with all operating fluids, standard equipment and battery. For more information visit www.Vimotoscoccom

