

Kinusaiga Instructions

1. Choose your pre-cut design

If you want to paint the wooden frame, do this first and allow it to dry completely.

2. Peeling the yellow backing paper

Work on one section at a time. Peel away one piece of the yellow backing paper to reveal the adhesive, ready for your chosen material.

3. Cutting the fabric pieces

Cut the matching fabric approximately **5 mm (½ cm) larger** than the section you have uncovered where joins are and **10mm (1cm)** where the shape touches an outside edge.

4. Positioning the fabric

Position the fabric over the matching section and press it gently onto the adhesive.

5. Stroke / Tuck the edges

Using a seam ripper or a darning needle, gently stroke the fabric edges into the seams around the section. Work slowly and a little at a time so you don't tear the fabric. Cutting any excess material away if needed.

TIP: Take your time, especially around curves and small sections, and handle the fabric gently for a neat finish

6. Work from the centre outwards

Continue section by section, working from the centre of the design towards the outside. Build up the design a little at a time carefully.

7. Finish the outside

When the design is complete, peel the backing from the double-sided tape at the bottom of the frame. Position the foam neatly into the frame.

8. Tuck and tidy edges

Use the seam ripper or darning needle one last time to tuck the outer fabric edges securely into place.

(Tip: you could trim the outer pieces to make them the same all the way around, but don't trim less than 5mm else they'll not tuck properly.)

KINUSAIGA

NO SEW QUILT PICTURES

STEP BY STEP INSTRUCTIONS



1. Choose your pre-cut design



2. Peel off one piece of yellow backing paper at a time.



3. Use backing paper as a template, cutting 5mm bigger on joining edges and 1cm bigger on outer edges.



4. Place & press the cut fabric centrally on to revealed sticky area.



5. Gently stroke edges/joins with the seam ripper or a darning needle. Trim off any excess material if needed making sure all edges are tucked into the grooves.



6. Repeat to all areas, working from the inside pieces outwards.



7. Place finished design in to frame and gently stroke an tuck all edges.



8. Sit back & admire your creation
(tip: if you want to paint your frame do so before you start, allowing it to dry.)