

# SILTWORM SD

## SILTWORM SD NETTING SPECIFICATIONS - 12 INCH

Material	Tubular Knit	
Fiber Material	Multi-filament Polypropylene	
Color	Black	
Melting Point	250°C	482°F
UV Protection	Photodegradable/UV Stabilized	
UV Resistance ASTM D4355	1000 Hours: 100%	
Approximate Life Expectancy	24 months	
Chemical Reaction	Inert to most soil chemicals including Alkaline, weak acids, and salt.	
Strength Properties	Static Puncture ASTM D6241	96 PSI
Mesh Opening	1/16 inch	
Weight per Roll (lbs)	60 lbs	
Actual Relaxed Roll Length (ft)	800 ft	
Applied Length (yield)	704 ft	

## FILL MATERIAL SPECIFICATIONS

Grind Sizing	90% 1.5 – 2-inch grind, 10% fine grind
Wood Source	Recycled wood fiber
Properties	Weed, seed, disease- and bark-free, 100% recycled wood filler material, pH balanced, 100% biodegradable
Saturated Weight	19.5 lbs per lineal foot
Dry Weight	7.9 lbs per lineal foot
Approximate Life Expectancy	18 – 24 months
Packaging	Shrink-wrapped & palletized

Weights and packaging may vary slightly in different production runs. All rolls can be shipped individually or combined on a pallet.

\*Life Expectancy will vary with your type of applications, region and local climactic conditions, and should be used as a guide only.

\*\*Measurements are obtained from tests done in lab conditions and vary depending on accuracy of infield applications.

All information supplied is considered to be true and accurate. Any non-standard conditions that may affect the applications of the materials should be consulted with Siltworm, Inc.