

SILTWORM SD

SILTWORM SD NETTING SPECIFICATIONS - 9 INCH

Material	Tubular Knit	
Fiber Material	Multi-filament Polypropylene	
Color	Black	
Melting Point	250°C	482°F
UV Protection	Photodegradable/UV Stabilized	
UV Resistance ASTM D4355	1000 Hours: 100%	
Approximate Life Expectancy	24 months	
Specific Gravity	0.918g	
Chemical Reaction	Inert to most soil chemicals including Alkaline, weak acids, and salt.	
Strength Properties	Static Puncture ASTM D6241	96 PSI
Mesh Opening	1/16 inch	
Weight per Roll (lbs)	36 lbs	
Actual Relaxed Roll Length (ft)	1060 ft	
Applied Length (yield)	933 ft	

FILL MATERIAL SPECIFICATIONS

Grind Sizing	90% 1.5 – 2-inch grind, 10% fine grind
Wood Source	Recycled wood fiber
Properties	Weed, seed, disease- and bark-free, 100% recycled wood filler material, pH balanced, 100% biodegradable
Saturated Weight	10 lbs per lineal foot
Dry Weight	4 lbs per lineal foot
Approximate Life Expectancy	18 – 24 months
Packaging	Shrink-wrapped & palletized

Weights and packaging may vary slightly in different production runs. All rolls can be shipped individually or combined on a pallet.

*Life Expectancy will vary with your type of applications, region and local climactic conditions, and should be used as a guide only.

**Measurements are obtained from tests done in lab conditions and vary depending on accuracy of infield applications.

All information supplied is considered to be true and accurate. Any non-standard conditions that may affect the applications of the materials should be consulted with Siltworm, Inc.