

# Safety Data Sheet

Issue Date: 30-Oct-2008

Revision Date: 13-Aug-2015

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** BB-99 BLACK BITUMINOUS PIPE COATING LOW VOC

### Other means of identification

**SDS #** WOHL-010

**Product Code** BB99V3.5

**UN/ID No** UN1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** Metal pipe coating. For use by professional painters and applicators only.

### Details of the supplier of the safety data sheet

#### Supplier Address

Wohl Coatings Co.  
6161 Maple Ave.  
St. Louis, MO 63130

### Emergency Telephone Number

**Company Phone Number** 314-725-3400  
**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** Black liquid

**Physical State** Liquid

**Odor** Characteristic of solvents

### Classification

Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

### Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin  
May be harmful if swallowed

### Signal Word

**Danger**

**Hazard Statements**

Causes skin irritation  
May cause genetic defects  
May cause cancer  
Suspected of damaging fertility or the unborn child  
May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not breathe dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
If skin irritation occurs: Get medical advice/attention  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do not induce vomiting  
IN CASE OF FIRE: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other Hazards**

Very toxic to aquatic life with long lasting effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Benzin	8030-30-6	35-40
Bitumen	64742-93-4	20-25
N-Heptane	142-82-5	15-20
Toluene	108-88-3	10-15
Xylene	1330-20-7	1-5
Petroleum Asphalt	8052-42-4	1-5

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST-AID MEASURES

#### First Aid Measures

<b>General Advice</b>	If exposed or concerned: Get medical advice/attention.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical advice/attention.
<b>Skin Contact</b>	Wash skin with soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. Call a physician immediately.
<b>Ingestion</b>	Do not induce vomiting. Call a physician or poison control center immediately. Aspiration of material into lungs can cause chemical pneumonitis, which can be fatal.

#### Most important symptoms and effects

<b>Symptoms</b>	May cause irritation to the mucous membranes and upper respiratory tract. Prolonged breathing of vapors may cause nausea, headache, weakness and/or dizziness. May cause nausea, vomiting, stomach ache, and diarrhea. If you are allergic or have been sensitized to: epoxies, amines, isocyanates, detergents, or other chemicals, see a physician prior to use. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure.
-----------------	--

#### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

### 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>). Dry chemical. Foam. Treat as a Class B fire.

**Unsuitable Extinguishing Media** Water spray may be ineffective. If water is used, fog nozzles are preferable.

#### Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Closed containers may explode due to buildup of pressure when exposed to extreme heat. Vapors may travel to source of ignition and flash back. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite/explode.

**Hazardous Combustion Products** Nitric acid. Ammonia. Nitrogen oxides (NOx). Nitrogen oxide can react with water vapors to form corrosive nitric acid. Carbon monoxide. Carbon dioxide (CO2). Aldehydes. Flammable hydrocarbon fragments. Nitrosamine. Organic acid vapors.

**Sensitivity to Static Discharge** Take precautionary measures against static discharge.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

<b>Personal Precautions</b>	Use personal protective equipment as required. Remove all sources of ignition. Before responding to a spill or leak of this product, review each section of this SDS and follow the recommendations of each section. Ventilate affected area. Use non-sparking tools.
<b>Environmental Precautions</b>	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

**Methods and material for containment and cleaning up**

<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so.
<b>Methods for Clean-Up</b>	Contain and collect with an inert absorbent and place into an appropriate container for disposal.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

<b>Advice on Safe Handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use spark-proof tools and explosion-proof equipment. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Do not reuse this container. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. For use by professional painters and applicators only.
--------------------------------	---

**Conditions for safe storage, including any incompatibilities**

<b>Storage Conditions</b>	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep locked up and out of reach of children. Store away from heat, sparks, flame. Do not store at temperatures above 120°F. Do not transfer contents to bottles or other unlabeled containers. Store large quantities in buildings designed to comply with OSHA 1910.106.
<b>Packaging Materials</b>	Do not reuse container.
<b>Incompatible Materials</b>	Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Benzin 8030-30-6	-	TWA: 100 ppm TWA: 400 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 400 mg/m <sup>3</sup>	IDLH: 1000 ppm TWA: 100 ppm TWA: 400 mg/m <sup>3</sup>
N-Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m <sup>3</sup>	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 85 ppm TWA: 350 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Petroleum Asphalt 8052-42-4	TWA: 0.5 mg/m <sup>3</sup> benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m <sup>3</sup> fume 15 min

**Appropriate engineering controls****Engineering Controls**

Apply technical measures to comply with the occupational exposure limits. Eyewash stations. Showers.

**Individual protection measures, such as personal protective equipment****Eye/Face Protection**

Wear safety glasses with side shields (or goggles). Refer to 29 CFR 1910.133 for eye and face protection regulations.

**Skin and Body Protection**

Wear appropriate clothing to prevent repeated or prolonged skin contact. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

**Respiratory Protection**

All workers and bystanders must be protected from exposure above established limits. Avoid breathing vapors, spray mist or sanding dust. Application by brush, roller, squeegee, or trowel will result in the lowest release of hazardous materials. When spray applied in outdoor or open areas with unrestricted ventilation, and during sanding or grinding operations, use NIOSH/MSHA approved mechanical filter respirator to remove solid airborne particles of over spray or sanding dust. When used in restricted areas, wear NIOSH/MSHA approved chemical/mechanical filters designed to remove a combination of particulates and vapor. When used in confined areas, wear NIOSH/MSHA approved air supply respirators or hoods. Use NIOSH/MSHA approved respirators when flame cutting, welding, brazing and sanding material coated with this product. The fumes from these operations can be hazardous. Do not breathe them. Always use adequate ventilation. Whenever using respirators refer to OSHA 1910.134 for proper respirator use and safety program. The applicator determines the type of area in which the application is being made (unrestricted, restricted, or confined). The best determination of respirator type to use in a particular application is to monitor for the hazardous materials during actual application. The applicator should contact a qualified safety engineer for proper selection of safety equipment based on the application conditions.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid	<b>Odor</b>	Characteristic of solvents
<b>Appearance</b>	Black liquid	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Black		

<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks • Method</u></b>
<b>pH</b>	Not determined	
<b>Melting Point/Freezing Point</b>	Not determined	
<b>Boiling Point/Boiling Range</b>	Not available	
<b>Flash Point</b>	-9 °C / 15 °F	Setaflash
<b>Evaporation Rate</b>	Slower than ether	
<b>Flammability (Solid, Gas)</b>	Liquid-not applicable	
<b>Upper Flammability Limits</b>	Not determined	
<b>Lower Flammability Limit</b>	Not determined	
<b>Vapor Pressure</b>	Not determined	
<b>Vapor Density</b>	Heavier than air	
<b>Specific Gravity</b>	Not determined	
<b>Water Solubility</b>	Negligible	
<b>Solubility in other solvents</b>	Not determined	
<b>Partition Coefficient</b>	Not determined	
<b>Auto-ignition Temperature</b>	Not determined	
<b>Decomposition Temperature</b>	Not determined	
<b>Kinematic Viscosity</b>	Not determined	
<b>Dynamic Viscosity</b>	Not determined	
<b>Explosive Properties</b>	Not determined	
<b>Oxidizing Properties</b>	Not determined	
<b>Additional Information</b>	Percent Volatile: 65.45 by volume	
<b>VOC Content</b>	3.34 lbs/gal (411 g/L)	
	VOC less water and exempt solvents: 5.03 lbs/gal (602 g/L)	
<b>Density</b>	6.78 lbs/gal	

**10. STABILITY AND REACTIVITY****Reactivity**

Not reactive under normal conditions.

**Chemical Stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization**

Hazardous polymerization does not occur.

**Conditions to Avoid**

Mixed product should not be kept in quantities greater than 3-6 pounds weight (approx. 1 quart to 1/2 gallon volume) longer than 25 to 35 minutes at high ambient temperatures. The product reacts quickly when in large mixed masses and develops heat quickly. It is possible for the mass to reach decomposition temperatures and give off dangerous gases. Always pour the material out in thin thickness (1/4 inch or less) to avoid the mass reaction.

**Incompatible Materials**

Strong oxidizing agents.

**Hazardous Decomposition Products**

Nitric acid. Ammonia. Nitrogen oxides (NOx). Nitrogen oxide can react with water vapors to form corrosive nitric acid. Carbon monoxide. Carbon dioxide (CO2). Aldehydes. Flammable hydrocarbon fragments. Nitrosamine. Organic acid vapors.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure****Product Information**

<b>Eye Contact</b>	Avoid contact with eyes.
<b>Skin Contact</b>	Causes skin irritation. May be harmful in contact with skin.
<b>Inhalation</b>	Avoid breathing vapors or mists.
<b>Ingestion</b>	May be harmful if swallowed.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Benzin 8030-30-6	> 5 g/kg ( Rat )	> 3 g/kg ( Rabbit )	-
Bitumen 64742-93-4	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-
N-Heptane 142-82-5	-	= 3000 mg/kg ( Rabbit )	= 103 g/m <sup>3</sup> ( Rat ) 4 h
Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
Xylene 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit ) > 1700 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
Petroleum Asphalt 8052-42-4	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-

**Information on physical, chemical and toxicological effects**

<b>Symptoms</b>	Please see section 4 of this SDS for symptoms.
-----------------	--

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Germ cell mutagenicity</b>	May cause genetic defects.
<b>Carcinogenicity</b>	May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Bitumen 64742-93-4		Group 2A		X
Toluene 108-88-3		Group 3		
Xylene 1330-20-7		Group 3		
Petroleum Asphalt 8052-42-4		Group 2B		X

**Legend**

**IARC (International Agency for Research on Cancer)**

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.
<b>STOT - single exposure</b>	May cause drowsiness or dizziness.
<b>STOT - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.

**Numerical measures of toxicity**

Not determined

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Benzin 8030-30-6	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50	9.2: 96 h Lepomis macrochirus mg/L LC50 static		
Bitumen 64742-93-4	56: 72 h Pseudokirchneriella subcapitata mg/L EC50			
N-Heptane 142-82-5		375.0: 96 h Cichlid fish mg/L LC50		10: 24 h Daphnia magna mg/L EC50
Toluene 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi- static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	EC50 = 19.7 mg/L 30 min	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
Xylene 1330-20-7		13.4: 96 h Pimephales promelas mg/L LC50 flow- through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 780: 96 h Cyprinus carpio mg/L LC50 semi-static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 19: 96 h Lepomis macrochirus mg/L LC50 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50

**Persistence/Degradability**

Not determined.



**Bioaccumulation**

Not determined.

**Mobility**

Chemical Name	Partition Coefficient
N-Heptane 142-82-5	4.66
Toluene 108-88-3	2.65
Xylene 1330-20-7	2.77 - 3.15
Petroleum Asphalt 8052-42-4	>6

**Other Adverse Effects**

Not determined

### 13. DISPOSAL CONSIDERATIONS

**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**US EPA Waste Number**

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Xylene 1330-20-7		Included in waste stream: F039		U239

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
---------------	-----------------------------------

Benzin 8030-30-6	Toxic of petroleum or coal tar origin Ignitable of petroleum or coal tar origin
N-Heptane 142-82-5	Toxic Ignitable
Toluene 108-88-3	Toxic Ignitable
Xylene 1330-20-7	Toxic Ignitable

#### 14. TRANSPORT INFORMATION

##### Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

##### DOT

UN/ID No UN1263  
 Proper Shipping Name Paint  
 Hazard Class 3  
 Packing Group II

##### IATA

UN/ID No UN1263  
 Proper Shipping Name Paint  
 Hazard Class 3  
 Packing Group II

##### IMDG

UN/ID No UN1263  
 Proper Shipping Name Paint  
 Hazard Class 3  
 Packing Group II  
 Marine Pollutant This material may meet the definition of a marine pollutant

#### 15. REGULATORY INFORMATION

##### International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Benzin	Present	X		Present			X	Present	X	X
Bitumen	Present	X		Present		Present	X	Present	X	X
N-Heptane	Present	X		Present		Present	X	Present	X	X
Toluene	Present	X		Present		Present	X	Present	X	X
Xylene	Present	X		Present		Present	X	Present	X	X
Petroleum Asphalt	Present	X		Present		Present	X	Present	X	X

##### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

##### US Federal Regulations

**CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene 108-88-3	1 lb		RQ 1 lb final RQ RQ 0.454 kg final RQ
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Toluene - 108-88-3	108-88-3	10-15	1.0
Xylene - 1330-20-7	1330-20-7	1-5	1.0

**CWA (Clean Water Act)**

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene	1000 lb	X	X	X
Xylene	100 lb			X

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Toluene - 108-88-3	Developmental Female Reproductive

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Benzin 8030-30-6	X	X	X
Bitumen 64742-93-4	X		
N-Heptane 142-82-5	X	X	X
Toluene 108-88-3	X	X	X
Xylene 1330-20-7	X	X	X
Petroleum Asphalt 8052-42-4	X	X	X

**16. OTHER INFORMATION****NFPA****Health Hazards**

Not determined

**Flammability**

Not determined

**Instability**

Not determined

**Special Hazards**

Not determined

**HMIS****Health Hazards**

1

**Flammability**

3

**Physical Hazards**

0

**Personal Protection**

Not determined

**Issue Date:** 30-Oct-2008  
**Revision Date:** 13-Aug-2015  
**Revision Note:** New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**