

Safety Data Sheet

Issue Date: 08-Nov-2006

Revision Date: 13-Aug-2015

Version 1

1. IDENTIFICATION

Product Identifier

Product Name DD-59 WATER BASED CLEAR OR BLACK

Other means of identification

SDS # WOHL-014

Product Code DD59

Recommended use of the chemical and restrictions on use

Recommended Use Metal pipe coating. For use by professional painters and applicators only.

Details of the supplier of the safety data sheet

Supplier Address

Wohl Coatings Co.
6161 Maple Ave.
St. Louis, MO 63130

Emergency Telephone Number

Company Phone Number 314-725-3400
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Black or Clear Liquid

Physical State Liquid

Odor Mild characteristic Solvent

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

Other Hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

The product contains no substances which, at their given concentration, are considered to be hazardous to health. However, additional component information is available in subsequent sections of this SDS.

4. FIRST-AID MEASURES

First Aid Measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical attention.

Skin Contact Wash skin with soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. Seek medical attention.

Inhalation	Remove to fresh air. Get medical attention if symptoms develop and persist.
Ingestion	Do not induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and effects

Symptoms	Direct contact may cause skin or eye irritation. Prolonged breathing of vapors may cause nausea, headache, weakness and/or dizziness. No effects anticipated from ingestion incidental to normal use. Larger quantities may cause distress of the digestive tract and nausea. If you are allergic or have been sensitized to: epoxies, amines, isocyanates, detergents, or other chemicals, see a physician prior to use.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Dry chemical. Foam. Treat as a Class B fire.

Unsuitable Extinguishing Media Water spray may be ineffective. If water is used, fog nozzles are preferable.

Specific Hazards Arising from the Chemical

Closed containers may explode due to buildup of pressure when exposed to extreme heat.

Hazardous Combustion Products Nitric acid. Ammonia. Nitrogen oxides (NO_x). Nitrogen oxide can react with water vapors to form corrosive nitric acid. Carbon monoxide. Carbon dioxide (CO₂). Aldehydes. Flammable hydrocarbon fragments. Nitrosamine. Organic acid vapors.

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protective equipment as required. Before responding to a spill or leak of this product, review each section of this SDS and follow the recommendations of each section. Ventilate affected area. Use non-sparking tools.
Environmental Precautions	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Contain and collect with an inert absorbent and place into an appropriate container for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

For use by professional painters and applicators only. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection recommended in Section 8. Do not reuse this container. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Do not transfer contents to bottles or other unlabeled containers. Keep out of the reach of children. Do not store above 110°F. Keep from freezing.

Packaging Materials

Do not reuse container.

Incompatible Materials

Mineral acids. Amines. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Eyewash stations. Showers.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Wear safety glasses with side shields (or goggles). Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection

Wear appropriate clothing to prevent repeated or prolonged skin contact. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection

All workers and bystanders must be protected from exposure above established limits. Avoid breathing vapors, spray mist or sanding dust. Application by brush, roller, squeegee, or trowel will result in the lowest release of hazardous materials. When spray applied in outdoor or open areas with unrestricted ventilation, and during sanding or grinding operations, use NIOSH/MSHA approved mechanical filter respirator to remove solid airborne particles of over spray or sanding dust. When used in restricted areas, wear NIOSH/MSHA approved chemical/mechanical filters designed to remove a combination of particulates and vapor. When used in confined areas, wear NIOSH/MSHA approved air supply respirators or hoods. Use NIOSH/MSHA approved respirators when flame cutting, welding, brazing and sanding material coated with this product. The fumes from these operations can be hazardous. Do not breathe them. Always use adequate ventilation. Whenever using respirators refer to OSHA 1910.134 for proper respirator use and safety program. The applicator determines the type of area in which the application is being made (unrestricted, restricted, or confined). The best determination of respirator type to use in a particular application is to monitor for the hazardous materials during actual application. The applicator should contact a qualified safety engineer for proper selection of safety equipment based on the application conditions.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Mild characteristic
Appearance	Black or Clear Liquid		Solvent
Color	Black or Clear	Odor Threshold	Not determined
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	Not determined		
Melting Point/Freezing Point	Not determined		
Boiling Point/Boiling Range	Not available		
Flash Point	None		
Evaporation Rate	Slower than ether		
Flammability (Solid, Gas)	Liquid-not applicable		
Upper Flammability Limits	Not determined		
Lower Flammability Limit	Not determined		
Vapor Pressure	Not determined		
Vapor Density	Heavier than air		
Specific Gravity	Not determined		
Water Solubility	Not miscible Floats on water		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Auto-ignition Temperature	Not determined		
Decomposition Temperature	Not determined		
Kinematic Viscosity	Not determined		
Dynamic Viscosity	Not determined		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		
Additional Information	Percent Volatile: 77.45 by volume		
VOC Content	0.58 lbs/gal (69 g/L) VOC less water and exempt solvents: 1.94 lbs/gal (232 g/L)		
Density	8.11 lbs/gal		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Mixed product should not be kept in quantities greater than 3-6 pounds weight (approx. 1 quart to 1/2 gallon volume) longer than 25 to 35 minutes at high ambient temperatures. The product reacts quickly when in large mixed masses and develops heat quickly. It is possible for the mass to reach decomposition temperatures and give off dangerous gases. Always pour the material out in thin thickness (1/4 inch or less) to avoid the mass reaction.

Incompatible Materials

Mineral acids. Amines. Strong bases.

Hazardous Decomposition Products

Nitric acid. Ammonia. Nitrogen oxides (NOx). Nitrogen oxide can react with water vapors to form corrosive nitric acid. Carbon monoxide. Carbon dioxide (CO2). Aldehydes. Flammable hydrocarbon fragments. Nitrosamine. Organic acid vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Avoid contact with eyes.
Skin Contact	Avoid contact with skin.
Inhalation	Avoid breathing vapors or mists.
Ingestion	Do not ingest.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2,2,4-Trimethyl-1,3-pentanediol monoisobutyrate 25265-77-4	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	-

Information on physical, chemical and toxicological effects

Symptoms	Please see section 4 of this SDS for symptoms.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity	Based on the information provided, this product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.
------------------------	---

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
2,2,4-Trimethyl-1,3-pentanediol monoisobutyrate 25265-77-4	18.4: 72 h Pseudokirchneriella subcapitata mg/L EC50	30: 96 h Pimephales promelas mg/L LC50		95: 96 h Daphnia magna mg/L LC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
2,2,4-Trimethyl-1,3-pentanediol monoisobutyrate 25265-77-4	3.47

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

Not regulated

IATA

Not regulated

IMDG**Marine Pollutant**

This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION**International Inventories**

Not determined

US Federal Regulations**SARA 313**

Not determined

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Not determined

16. OTHER INFORMATION**NFPA****Health Hazards****Flammability****Instability****Special Hazards****HMIS****Health Hazards****Flammability****Physical Hazards****Personal Protection**Not determined
1Not determined
0Not determined
0Not determined
Not determined

Issue Date: 08-Nov-2006
Revision Date: 13-Aug-2015
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet