

SAFETY DATA SHEET

Issue Date 20-May-2015

Revision Date 23-Jul-2015

Version 2

1. IDENTIFICATION

Product identifier**Product Name**

Gray Phenolic Primer

Other means of identification**Product Code**

UP101 (H20E710)

Other Information

This product is intended for use by properly trained and qualified professionals after having familiarized themselves with this SDS and understand all hazards to themselves and the environment through a comprehensive training program according to the Hazard Communication Standard 29 CFR 1910.1200, and the Occupational Safety and Health adoption of the Global Harmonization Standard (GHS). It is not intended for general public use.

Recommended use of the chemical and restrictions on use**Recommended Use**

Coatings.

Uses advised against

Restricted to professional users

Details of the supplier of the safety data sheet**Manufacturer Address**

Kempen Paint Company
2500 State Street
East Carondelet, IL 62240
(618) 286-5292

Wohl Coatings Company
6161 Maple Ave.
St. Louis, MO 63130
314-725-3400

Emergency telephone number**24 Hour Emergency Phone Number** Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2

Label elements**Emergency Overview****Danger****Hazard statements**

Causes skin irritation
May cause an allergic skin reaction
Suspected of causing cancer

May cause damage to organs through prolonged or repeated exposure
Highly flammable liquid and vapor

**Appearance** liquid paint**Physical state** liquid**Odor** Aromatic**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ ventilating / lighting/ non-sparking/ equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Toxic to aquatic life with long lasting effects Toxic to aquatic life

Unknown acute toxicity

1.0769% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical Name	CAS No.	Weight-%
calcium carbonate	471-34-1	33
xylene	1330-20-7	15.37
titanium dioxide	13463-67-7	13.5
n-butyl acetate	123-86-4	8.4072
ethylbenzene	100-41-4	3.344
Carbon black	1333-86-4	0.5

zinc oxide	1314-13-2	0.24
Omg ASA	96-29-7	0.1

4. FIRST AID MEASURES

Description of first aid measures

General advice	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
Eye contact	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
Skin contact	Wash skin with soap and water.
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
Ingestion	Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Do NOT induce vomiting.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms	Symptoms may include headache, dizziness, thirst, cramping, coughing, and nausea. these symptoms may be delayed. Repeated or prolonged exposure may cause kidney, liver, neurological, central nervous system, eye and skin disorders.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Keep victim warm and quiet.
---------------------------	-----------------------------

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO₂, water spray or regular foam. Water spray, fog or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable extinguishing media ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Substance may be transported hot.

Hazardous combustion products Phenols. Hydrocarbons. Carbon dioxide (CO₂). Carbon monoxide.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Keep away from sources of ignition. Prevent fire fighting water from entering surface water or groundwater. Cool containers with spray water from a safe distance. Never use welding or cutting torch on or near container (even empty) because product may ignite explosively.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Do not store together with acids, oxidizing substances, strong alkalis, or heavy-metal compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
calcium carbonate 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
n-butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³	IDLH: 800 ppm TWA: 100 ppm

		(vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
zinc oxide 1314-13-2	STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ fume (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) STEL: 10 mg/m ³ fume	IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear nitrile or natural rubber gloves to protect hands from contact. Butyl gloves are best for prolonged contact.
Impervious protective clothing as Tyvek(R) coveralls for light protection or Saranex 23-P(R) for moderate exposure.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. Adequate ventilation should be used as the first measure to ensure airborne thresholds listed in section 8 of this SDS are not exceeded. If respirators are used, they should be used in accordance with the Hazard Communication Standard.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Aromatic
Appearance	liquid paint	Odor threshold	No information available
Color	gray		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	7		
Melting point / freezing point	No information available		
Boiling point / boiling range	101 °C / 214 °F		
Flash point	22 °C / 72 °F		
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limit in Air			

Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor pressure	No information available
Vapor density	No information available
Relative density	No information available
Water solubility	No information available
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content	420 g/L
Non-Volatile (%)	71
Density	12.1 lbs/gal
Bulk density	No information available
Specific Gravity	1.45

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization	None under normal processing.
---------------------------------	-------------------------------

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong bases. Do not store together with acids, oxidizing substances, strong alkalis, or heavy-metal compounds.

Hazardous Decomposition Products

Carbon oxides. Nitrogen oxides (NOx). Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May be harmful if inhaled.
Eye contact	May cause eye irritation with susceptible persons.
Skin contact	Irritating to skin.
Ingestion	May be harmful if swallowed.

Chemical Name	Acute toxicity - Oral	Acute toxicity - Dermal	Acute toxicity - Inhalation (Gases)
xylene 1330-20-7		Category 4	
Omg ASA 96-29-7		Category 4	

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
calcium carbonate 471-34-1	= 6450 mg/kg (Rat)	-	-
xylene 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
n-butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	-	-
Omg ASA 96-29-7	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h

Chemical Name	NIOSH - Target Organs	STOT - single exposure	Target Organ Systemic Toxicant - Repeated exposure	Aspiration toxicity
calcium carbonate	eyes,respiratory system,skin			
xylene	-	H336 - May cause drowsiness or dizziness Category 3		
titanium dioxide	respiratory system in animals: lung tumors	H335 - May cause respiratory irritation		
n-butyl acetate	eyes,CNS,respiratory system,skin	H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness Category 3		
ethylbenzene	eyes,CNS,respiratory system,skin	H335 - May cause respiratory irritation	Category 2	Category 1
Carbon black	eyes,respiratory system lymphatic cancer in presence of PAHs			
zinc oxide	respiratory system			

Chemical Name	Non-additive, corrosive chemical type	Non-additive, irritant ingredient	Skin corrosion/irritation	Skin corrosion	Eyes
xylene 1330-20-7			Category 2		
Omg ASA 96-29-7					Category 1

Chemical Name	Respiratory sensitization	Skin sensitization	Mutagenicity	Mutagenic category 1
Omg ASA 96-29-7		Category 1		

Information on toxicological effects

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation

Irritating to skin.

Sensitization

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
xylene 1330-20-7	-	Group 3	-	-
titanium dioxide 13463-67-7	-	Group 2B	-	X

ethylbenzene 100-41-4	A3	Group 2B	-	X
Carbon black 1333-86-4	A3	Group 2B	-	X

Reproductive toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 7,941.00 mg/kg
ATEmix (dermal) 10,281.00 mg/kg
ATEmix (inhalation-dust/mist) 8.00 mg/l
ATEmix (inhalation-vapor) 4,639.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

51.0824 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient	DOT Marine Pollutant	DOT Severe Marine pollutant
xylene 1330-20-7	3.15		
n-butyl acetate 123-86-4	1.81		
ethylbenzene 100-41-4	3.118		
Omg ASA 96-29-7	0.65		

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging

Do not reuse container. Disposal should be in accordance with applicable regional, national and local laws and regulations. This material and its containers, if discarded, would be regulated as a hazardous waste under RCRA. Treatment and disposal must be completed at a RCRA permitted treatment, storage, and disposal facility (TSD). The storage and transportation of RCRA hazardous wastes are also regulated by the U.S. EPA.

US EPA Waste Number

D001 U220 U239

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
---------------	-----------------------------------

xylene 1330-20-7	Toxic Ignitable
n-butyl acetate 123-86-4	Toxic
ethylbenzene 100-41-4	Toxic Ignitable
zinc oxide 1314-13-2	Toxic

14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II
 Reportable Quantity (RQ) Ethylbenzene RQ: 1,000 lbs, Xylene RQ: 100 lbs, Butyl acetate RQ: 5,000 lbs
 Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28
 Description UN1263, Paint, , 3, II, RQ

 Emergency Response Guide Number 128

TDG

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II
 Description UN1263, Paint, , 3, II

MEX

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II
 Description UN1263, Paint, 3, II

ICAO (air)

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II
 Special Provisions A3, A72
 Description UN1263, Paint, 3, II

IATA

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II
 ERG Code 3L
 Special Provisions A3, A72, A192
 Description UN1263, Paint, 3, II

IMDG

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II
 EmS-No. F-E, S-E
 Special Provisions 163
 Description UN1263, Paint, Marine Pollutant, 3, II, (22°C c.c.)

RID

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1263, Paint, , 3, II

ADR

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Classification code	F1
Tunnel restriction code	(D/E)
Special Provisions	163, 640C, 650, 367
Description	UN1263, Paint, , 3, II, (D/E)
Labels	3

ADN

Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Classification code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, , 3, II
Hazard label(s)	3
Limited quantity (LQ)	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
xylene - 1330-20-7	1.0
ethylbenzene - 100-41-4	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CAA (Clean Air Act)

The following component(s) are listed in the Clean Air Act.

Chemical Name	Hazardous air pollutants (HAPs) content
---------------	---

xylene 1330-20-7	Present
ethylbenzene 100-41-4	Present

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
xylene 1330-20-7	100 lb	-	-	X
n-butyl acetate 123-86-4	5000 lb	-	-	X
ethylbenzene 100-41-4	1000 lb	X	X	X
zinc oxide 1314-13-2	-	X	-	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
n-butyl acetate 123-86-4	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
titanium dioxide - 13463-67-7	Carcinogen
ethylbenzene - 100-41-4	Carcinogen
Carbon black - 1333-86-4	Carcinogen
toluene - 108-88-3	Developmental Female Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
xylene 1330-20-7	X	X	X
titanium dioxide 13463-67-7	X	X	X
n-butyl acetate 123-86-4	X	X	X
ethylbenzene 100-41-4	X	X	X
Carbon black 1333-86-4	X	X	X
toluene 108-88-3	X	X	X
Cobalt Neodecanoate 27253-31-2	X	-	X
pentan-2-one 107-87-9	X	X	X

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**Prepared By**

This SDS was prepared by Kempen Paint Company using The WerCS (R) software of Underwriters Laboratories utilizing ChemAdvisor LOLI database. The SDS was provided to Wohl Coatings Company for use January 01, 2016.

Issue Date 20-May-2015

Revision Date 23-Jul-2015

Revision Note

SDS sections updated

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet