


HYDRAULIC POWER ANGLE VEE SNOW PLOUGH MODEL VU 300

WORK POSITIONS



TECHNICAL SPECIFICATIONS

- SHOCKPROOF VALVES;
- SILENT BLOCK URETHANE RUBBER WEARING EDGES FOR LOW TEMPERATURES, DESIGNED TO PROTECT THE FRAME FROM ANY OBSTACLES AND TO ENSURE LOW NOISE LEVEL AND LONG WORKING LIFE;
- HIGH YIELD STEEL FRAME;
- SELF-LUBRICATING BUSHINGS AT MAJOR STRESS POINTS;
- EASY ACCESS TO NON-SELF-LUBRICATING POINTS FOR MAINTENANCE;
- HIGH PRESSURE, QUICK-LOCK, HYDRAULIC HOSE PIPES;
- MARKER LAMPS WITH LED LIGHTS;
- HERMETICALLY SEALED ELECTRICAL SYSTEM;
- QUICK -LOCK COUPLING;
- VERTICAL SCROLL SYSTEM WITH SIDE SWIVEL;
- INTERCHANGEABLE SCRAPER BLADE EDGES;
- WIDE RANGE OF ACCESSORIES.

RUSTPROOF TREATMENTS

- SAND-BLASTING;
- KILN PAINTING, THERMOSETTING POWDER;
- POLYURETHANE PAINT TOPCOAT.

TECHNICAL

- **Height:** at wing 1800 mm. - at nose 1120 mm.
- **Maximum standard width** 3250 mm.
- **Minimum standard width** 3000 mm.
- **Weight without couplings** 1700 Kg.

