

# ESY-L0802

8" Android Rugged Tablet

## Features

- Integrated with MTK MT6789 (Octa Core, Octa Threads; 2.2 GHz)
- Operation System: Android 13
- Memory & Storage: 8GB/256GB
- Display: 8-inch, 1200x1920, IPS
- 10-Point Touch with Glove Touch & Wet Touch Support
- Battery: 10000 mAh with Fast Charging
- Protection Level : IP65, Drop Resistance 1.2 meters
- Design to Meet MIL-STD-810G, ISO-9001, CE, FCC, 3C

## Appearance





# ESY-L0802

8" Android Rugged Tablet

## Revision Table

Date	Revision	Content	By
2025/9/10	0.1	First Draft	Elio

ACT POWER TAIWAN  
Preliminary

# ESY-L0802

8" Android Rugged Tablet

## Specification

CPU Processor	MTK MT6789 (Octa Core, Octa Threads, 2.2GHz)
GPU	Mali-G57 MC2
Memory & Storage	8GB / 256GB
Display	LCD 8-inch
Resolution	800 x 1280, 1000 nits
Touch	10-Point Touch, Support Glove Touch & Wet Touch
Camera	Front Camera: 5MP Rear Camera: 13MP (with Flash Light)
Battery	7800 mAh 3.8V (Can Customize to 10000 mAh with Fast Charging)
WWAN	4G LTE, 3G WCDMA, GSM
GPS	BDS, GPS, GLONASS
WIFI	802.11a/b/g/n/ac Wireless Internet Wireless AP (Mobile AP) 2.4G, 5G
Bluetooth	5.0 Version
NFC	13.56 MHz, Distance: 1-3cm
MIC	Sensitivity: -32±2d Output Impedance: 2.2kΩx1
Speaker	8Ω 1.5 Watt
Sensor	1. Light Sensor 2. Magnetic Sensor 3. Pressure Sensor 4. G-Sensor 5. Distance Sensor 6. Acceleration Sensor 7. Gyroscope 8. Motor

# ESY-L0802

8" Android Rugged Tablet

## Specification

1D/2D Barcode	Optional
UHF RFID	M-500 / M-301 (Optional)
Fingerprint	Optional
Interface In/Out Port	1. 1 x Type-C ,OTG 2. 1 x SIM Card Slot 3. 1 x TF Card Slot 4. 1 x Earphone 5. 1 x DC; 3.5 x 15mm 6. 2 x USB 2.0 7. 1 x RS232 (Mini-USB)
Button	1 x Volume +/-, 1 x Power, 1 x Barcode Scan(F)
<b>Physical Characteristics</b>	
Dimension	234 x 144 x 16.8 mm
Weight	630 ± 20g
Accessories	Standard: DC Charger (5V 3A), Wrist Strap, Screw Additional: Hand Strap + Shoulder Strap

## Environment Compliance

Operating Temp	-20°C to +60°C
Storage Temp	-25°C to +80°C
IP Level	IP65
Drop Test	Dropping Resistance 1.2m
Certifications	Design to Meet MIL-STD-810G, CE, FCC, 3C

Environmental performance may vary according to the integration method or final integration scenario.

# ESY-L0802

8" Android Rugged Tablet

## Reference Drawing



# ESY-L0802

8" Android Rugged Tablet

## Deliverables

1	8" Android Rugged Tablet
2	Standard Accessories
3	Additional Accessories (Optional)

## Ordering Information

Model Name	Description	Unit
ESY-L0802	8" Android Rugged Tablet	1

### Disclaimer

This datasheet is for informational purposes only and does not constitute professional advice, a contractual obligation, or a guarantee of any kind. While efforts have been made to ensure accuracy, ACT POWER TAIWAN makes no representations or warranties, express or implied, regarding its completeness or reliability. ACT POWER TAIWAN reserves the right to update, modify, or withdraw this document at any time without prior notice. Users should verify the suitability of the product for their specific application through independent testing and validation. ACT POWER TAIWAN shall not be liable for any direct, indirect, or consequential damages arising from the use of this document. This document is governed by the laws of Taiwan, and any disputes shall be subject to the exclusive jurisdiction of the Taiwan courts.