5.5" Rugged RTK GNSS Data Controller

Features

- 5.5" RTK Handheld Terminal
- Android 12 OS
- With Four-Wall Helical Antenna
- 1080P Resolution, 500 nits Brightness
- Durable Corning Glass Screen, Scratch-Resistant
- Battery 9000mAh Battery
- Supports Dual-Band Wifi and 4G
- Slim and Lightweight Design, Sunlight-Readable Display

Appearance





5.5" Rugged RTK GNSS Data Controller

Revision Table

Date	Revision	Content	Ву
2025/8/21	0.1	First Draft	Elio

5.5" Rugged RTK GNSS Data Controller

Specification

System	
OS	Android 12
CPU	Qualcomm SDM 662 Octa-Core 2.0 GHz
RAM	4GB SDRAM
Flash Memory	64GB
Memory Card	Micro SDHC Up to 128GB
Physical	
Dimension (LxWxH)	228 mm x 96 mm x 21 mm
Weight	420g (Including Battery)
Keypad	QWERT KEY
GNSS Accuracies	
Channel	1408
Constellation	BDS: B1l, B2l, B3l, B1C, B2a, B2b
	GPS: L1C/A, L1C, L2P (Y), L2C, L5
	GLONASS: L1,L2
	Galileo: E1,E5a,E5b, E6*
	QZSS: L1, L2, L5, L6*
	SBAS*: L1,L5
RTK	2cm HRMS
SBAS	<1 m HRMS
Communication	
SIM Card Type	Nano-SIM Card
Wifi	802.11a/b/g/n/ac

5.5" Rugged RTK GNSS Data Controller

Specification

Network Modem	GSM: 850/900/1800/1900
	WCDMA: B1/B2/B4/B5/B8
	LTE-TDD: B34/B38/B39/B40/B41
	LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13/B17/B20/B25/ B26/B28
Bluetooth	V5.0
USB	Type C, OTG Supported
NFC	Support
Electrical	
Li-Ion Battery Capacity	9000mAh
Operation Time	22 Hours
Charging Time	4 Hours (Typical)
Others	
Sensors & Multimedia	13MP Rear Camera with Auto-Focus and Flash
	GNSS (BDS, GPS, GLONASS) A-GPS Support
	G-Sensor
	Gyroscope
	E-Compass
	Light Sensor
	Speaker
	Microphone

5.5" Rugged RTK GNSS Data Controller

Environment Compliance

Operating Temp	-20°C to +65°C
Working Temp	-30°C to +70°C
Humidity	5% - 95% (Non-Condensing)
IP Level	IP68
Shock & Vibration	1.2m Fall on Concrete

Environmental performance may vary according to the integration method or final integration scenario.

Reference Drawing



5.5" Rugged RTK GNSS Data Controller

Deliverables

1 5.5" Rugged RTK GNSS Data Controller

Ordering Information

Model Name	Description	Unit
ESY-U0605	5.5" Rugged RTK GNSS Data Controller	1

Disclaimer

This datasheet is for informational purposes only and does not constitute professional advice, a contractual obligation, or a guarantee of any kind. While efforts have been made to ensure accuracy, ACT POWER TAIWAN makes no representations or warranties, express or implied, regarding its completeness or reliability. ACT POWER TAIWAN reserves the right to update, modify, or withdraw this document at any time without prior notice. Users should verify the suitability of the product for their specific application through independent testing and validation. ACT POWER TAIWAN shall not be liable for any direct, indirect, or consequential damages arising from the use of this document. This document is governed by the laws of Taiwan, and any disputes shall be subject to the exclusive jurisdiction of the Taiwan courts.