Motherboard Intel® BayTrail-D J1900

Features

- Intel Baytrail J1900 Processor
- Multiple Display: HDMI, VGA, eDP or LVDS
- 2x Intel i211 Gigabit LAN
- 1x mSATA SSD
- 1x Mini PCle
- 1x SIM
- 1x USB3.0 + 5x USB2.0 Header

Appearance



Motherboard Intel® BayTrail-D J1900

Revision Table

Date	Revision	Content	Ву
2025/3/6	0.1	Mother Board Datasheet	Mark

Motherboard Intel® BayTrail-D J1900

Specification

	Specification	
Mother board	d	
CPU	Intel® BayTrail-D J1900 2.0GHz Quad Core	
Memory	1x On Board Memory 2G or 4G	
Graphics	Intel® UHD Graphics Based on CPU	
Ethernet	2x Intel i211 Gigabit Network Ports	
Storage	1x SATA 2.0 HDD Interface 1x mSATA 1x eMMC (Optional)	
Audio	HD ALC662	
Chipset	Integrated	
Rear Port	1x HDMI Display Interface 1x VGA Display Interface 1x USB3.0 Port 1x USB2.0 Port 2x RJ-45 Gigabit Network Ports 1x 2-in-1 Audio jack 1x DC Power Input Interface	
Internal Connector	1x 24bit Dual Channel LVDS or 1x eDP 1x Micro SIM Slot 1x Full Mini PCle (for m-SATA) 1x Full Mini PCle (for USB + PCle + 3G) 8x GPIO 6x F_COM (4x RS232, 2x RS485) 4x F_USB2.0	

Motherboard Intel® BayTrail-D J1900

Specification

Form Factor	146 x 102 mm
Power Input	9-24V, DC

Disclaimer

This datasheet is for informational purposes only and does not constitute professional advice, a contractual obligation, or a guarantee of any kind. While efforts have been made to ensure accuracy, ACT POWER TAIWAN makes no representations or warranties, express or implied, regarding its completeness or reliability. ACT POWER TAIWAN reserves the right to update, modify, or withdraw this document at any time without prior notice. Users should verify the suitability of the product for their specific application through independent testing and validation. ACT POWER TAIWAN shall not be liable for any direct, indirect, or consequential damages arising from the use of this document. This document is governed by the laws of Taiwan, and any disputes shall be subject to the exclusive jurisdiction of the Taiwan courts.