

# MIC-D1012

10.4" Resistive Touch LCD Module with UV

## Features

- 10.4" LCD Size
- 1024 x 768 Resolution
- Resistive Touch Screen
- AG Strengthen Touch Glass
- 700 nits Brightness
- EMI Mesh, Optical Bonding
- UV Function

## Appearance





# MIC-D1012

10.4” Resistive Touch LCD Module with UV

## Revision Table

Date	Revision	Content	By
2025/6/20	0.1	First Draft	Mark

# MIC-D1012

10.4" Resistive Touch LCD Module with UV

## Specification

LCD Panel	
LCD Size	10.4" TFT LCD
Backlight	LED
Resolution	1024 x 768
Interface	LVDS
View Angle	$\pm 88^{\circ}$ (H), $\pm 88^{\circ}$ (V)
Luminance	800 nits (After Bonding)
Contrast Ratio	1000:1
Aspect Ratio	4:3
Response Time	25 (Tr+Tf) ms
No. of Colour	16.7 Million (8 Bit/Colour)
Active Area	210.432 x 157.824 mm
Pixel Pitch	0.0685 (H) x 0.2055 (V)
LED Life Time	50,000 Hrs
Touch Screen	
Touch Type	5-Wire Resistive Touch
Active Area	210.4 x 157.8 mm
Touch Interface	USB
Touch Glass	AG Strengthen Glass
EMI Mesh	Yes
Optical Bonding	Yes
Touch Drives	Support Windows, Linux, Mac, etc.

# MIC-D1012

## 10.4" Resistive Touch LCD Module with UV

UV	
Transmittance	> 90%
Haze	< 0.7%
UV Blocking Rate	> 99%
Refractive Index	1.48 ± 0.02

## Environment Compliance

Operating Temp.	-40°C to +60°C
Storage Temp.	-40°C to +60°C
Humidity	Ta≤40°C, 90%RH, Non-Condensing
Shock	Design to Meet MIL-STD-810F
Vibration	Design to Meet MIL-STD-810E
EMI/EMC	Design to Meet MIL-STD461E/F

Environmental performance may vary according to the integration method or final integration scenario.

## Deliverables

1	10.4" Resistive Touch LCD Module with UV
2	USB Touch Control Board

## Ordering Information

Model Name	Description	Unit
MIC-D1012	10.4" Resistive Touch LCD Module with UV	1

### Disclaimer

This datasheet is for informational purposes only and does not constitute professional advice, a contractual obligation, or a guarantee of any kind. While efforts have been made to ensure accuracy, ACT POWER TAIWAN makes no representations or warranties, express or implied, regarding its completeness or reliability. ACT POWER TAIWAN reserves the right to update, modify, or withdraw this document at any time without prior notice. Users should verify the suitability of the product for their specific application through independent testing and validation. ACT POWER TAIWAN shall not be liable for any direct, indirect, or consequential damages arising from the use of this document.