10.4" Resistive Touch LCD Module with UV

### **Features**

- 10.4" LCD Size
- 1024 x 768 Resolution
- Resistive Touch Screen
- AG Strengthen Touch Glass
- 800 nits Brightness
- EMI Mesh, Optical Bonding
- Anti-UV Film


## **Appearance**



10.4" Resistive Touch LCD Module with UV

## **Revision Table**

Date	Revision	Content	Ву
2025/7/1	0.1	First Draft	Zoe You



10.4" Resistive Touch LCD Module with UV

## **Specification**

LCD Panel	
LCD Size	10.4-inch TFT LCD
Backlight	LED
Resolution	1024 x 768
Interface	LVDS
View Angle	± 88° (H), ±88° (V)
Luminance	800 nits (after Bonding)
Contrast Ratio	1000:1
Aspect Ratio	4:3
Response Time	25 (Tr+Tf) ms
No. of Colour	16.7 Million (8 Bit/Colour)
Active Area	210.432 x 157.824 mm
Pixel Pitch	0.0685 (H) x 0.2055 (V)
LED Life Time	50,000 Hrs
Surface Treatment	Anti-UV Film
Touch Screen	
Touch Type	5-Wire Resistive Touch
Active Area	211.58 x 158.75 mm
Touch Interface	USB
Touch Glass	AG Strengthen Glass
EMI Mesh	Yes
Optical Bonding	Yes
Touch Drives	Support Windows, Linux, Mac, etc.



#### 10.4" Resistive Touch LCD Module with UV

AD Board	
I/O	LVDS, DVI, VGA, Keyboard
Power Input	12VDC
Accessories	
Boards	USB Touch Control Board, OSD Keyboard
Cables	LVDS Cable
Optical Bonding	Yes
Touch Drives	Support Windows, Linux, Mac, etc.

# **Environment Compliance**

Operating Temp.	-30°C to +85°C
Storage Temp.	-30°C to +85°C
Humidity	Ta≦40°C, 90%RH, Non-Condensing
Shock	Design to Meet MIL-STD-810F
Vibration	Design to Meet MIL-STD-810E
EMI/EMC	Design to Meet MIL-STD461E/F

Environmental performance may vary according to the integration method or final integration scenario.

10.4" Resistive Touch LCD Module with UV

#### **Deliverables**

1	10.4" Resistive Touch LCD Module with UV
2	ADM-0202 USB Touch Control Board
3	AD Board
4	OSD Keyboard
5	LVDS Cable
6	OSD Keyboard with Cable

## **Ordering Information**

Model Name	Description	Unit
MIC-D1013	10.4" Resistive Touch LCD Module with UV	1

#### Disclaimer

This datasheet is for informational purposes only and does not constitute professional advice, a contractual obligation, or a guarantee of any kind. While efforts have been made to ensure accuracy, ACT POWER TAIWAN makes no representations or warranties, express or implied, regarding its completeness or reliability. ACT POWER TAIWAN reserves the right to update, modify, or withdraw this document at any time without prior notice. Users should verify the suitability of the product for their specific application through independent testing and validation. ACT POWER TAIWAN shall not be liable for any direct, indirect, or consequential damages arising from the use of this document. This document is governed by the laws of Taiwan, and any disputes shall be subject to the exclusive jurisdiction of the Taiwan courts.