

MIC-D1507

15.6" Resistive Touch LCD Module with EMI Mesh & Optical Bonding

Features

- 15.6" LCD Size
- 1920 x 1080 Resolution
- Resistive Touch Screen
- AR/AG Strengthen Touch Glass
- 1000 nits Brightness
- EMI Mesh, Optical Bonding

Appearance





MIC-D1507

15.6” Resistive Touch LCD Module with EMI Mesh & Optical Bonding

Revision Table

Date	Revision	Content	By
2024/4/23	0.1	First Draft	Dennis

MIC-D1507

15.6" Resistive Touch LCD Module with EMI Mesh & Optical Bonding

Specification

LCD Panel	
LCD Size	15.6" TFT LCD
Backlight	LED
Resolution	1920 x 1080
Interface	LVDS
View Angle	± 89° (H), ±89° (V)
Luminance	1000 nits (After Bonding)
Contrast Ratio	800:1
Aspect Ratio	16:9
Response Time	25ms (TR+TF, Typ.)
No. of Colour	16.7M
Active Area	344.16(H) x 293.59(V) mm
Pixel Pitch	0.17925 (H) x 0.17925 (V)
LED Life Time	50,000 Hrs
Touch Screen	
Touch Type	Resistive Multi Touch
Active Area	345.16(H) x 294.59(V) mm
Touch Interface	USB
Touch Glass	AR/AG Strengthen Glass
EMI Mesh	Yes
Optical Bonding	Yes
Touch Drives	Support Windows, Linux, Mac, etc.

MIC-D1507

15.6" Resistive Touch LCD Module with EMI Mesh & Optical Bonding

Environment Compliance

Operating Temp.	-30°C to +70°C
Storage Temp.	-40°C to +75°C
Humidity	Ta≤40°C, 90%RH, Non-Condensing
Shock	Design to meet MIL-STD-810F
Vibration	Design to meet MIL-STD-810E
EMI/EMC	Design to meet MIL-STD461E/F

Note 1: Environmental performance may vary according to the integration method or final integration scenario.

Note 2: Follow the industrial quality standard this LCD panel will include minimum 3 bright or dead pixels on viewable area and maxium total 5 bright or dead pixels on whole LCD panel.

Deliverables

1	15.6" Resistive Touch LCD Module with EMI Mesh & Optical Bonding
2	USB Touch Control Board
3	USB Touch Cable

Ordering Information

Model Name	Description	Unit
MIC-D1507	15.6" Resistive Touch LCD Module with EMI Mesh & Optical Bonding	1

Disclaimer

This datasheet is for informational purposes only and does not constitute professional advice, a contractual obligation, or a guarantee of any kind. While efforts have been made to ensure accuracy, ACT POWER TAIWAN makes no representations or warranties, express or implied, regarding its completeness or reliability. ACT POWER TAIWAN reserves the right to update, modify, or withdraw this document at any time without prior notice. Users should verify the suitability of the product for their specific application through independent testing and validation. ACT POWER TAIWAN shall not be liable for any direct, indirect, or consequential damages arising from the use of this document. This document is governed by the laws of Taiwan, and any disputes shall be subject to the exclusive jurisdiction of the Taiwan courts.