

MIC-D1508

15.6" Capacitive Touch LCD Kits with EMI Mesh & Optical Bonding

Features

- 15.6" LCD Size
- 1920 x 1080 Resolution
- 400 nits Brightness (After Bonding)
- -30 to + 80°C Operating Temperature
- Capacitive Touch Screen
- EMI Mesh, Optical Bonding
- AD Board with HDMI & VGA Output, 12VDC Input

Appearance





MIC-D1508

15.6” Capacitive Touch LCD Kits with EMI Mesh & Optical Bonding

Revision Table

Date	Revision	Content	By
2025/3/10	0.1	First Draft	Dennis

MIC-D1508

15.6" Capacitive Touch LCD Kits with EMI Mesh & Optical Bonding

Specification

LCD Panel	
LCD Size	15.6" TFT LCD
Backlight	LED
Resolution	1920 x 1080
No. of Colours	16.2M
View Angle	$\pm 85^{\circ}$ (H), $\pm 85^{\circ}$ (V)
Luminance	400 nits (After Bonding)
Contrast Ratio	800:1
Pixel Pitch	0.17925 x 0.17925mm
Aspect Ratio	16:9
LCD Panel Life time	50,000 Hrs.
Interface	LVDS
Response Time	25ms (Tr+Tf)
Active Area	344.16(W) x 193.59(H) mm
Touch Glass	
EMI Mesh	Yes
Optical Bonding	Yes
Cover Glass	Capacitive Multi-Touch Glass
Interface	USB
Glass Surface Hardness	$\geq 5H$

MIC-D1508

15.6" Capacitive Touch LCD Kits with EMI Mesh & Optical Bonding

Specification

AD Board (ADM-H1201)	
Power Input	12VDC
Input Sources	VGA, HDMI, Audio Input
Audio Output	1.4W + 1.4W at Ohm Speaker
OSD	Multi Language OSD Menu; Buttons: Power ON/OFF, Menu, Adjust -, Adjust +

Environment Compliance

Operating Temp.	-30°C to +80°C
Storage Temp.	-40°C to +85°C
Humidity	Ta≤40°C, 90%RH, Non-Condensing
Shock	Design to meet MIL-STD-810G
Vibration	Design to meet MIL-STD-810G
EMI/EMC	Design to meet MIL-STD461E/F

Environmental performance may vary according to the integration method or final integration scenario.



MIC-D1508

15.6” Capacitive Touch LCD Kits with EMI Mesh & Optical Bonding

Deliverables

1	15.6” Capacitive Touch LCD Kits with EMI Mesh & Optical Bonding
2	ADM-H1201 AD Board (1xHDMI, 1xVGA)
3	LVDS Cable
4	Backlight Cable
5	USB Touch Control Board
6	USB Touch Cable
7	OSD Cable
8	OSD Keyboard

Ordering Information

Model Name	Description	Unit
MIC-D1508	15.6” Capacitive Touch LCD Kits with EMI Mesh & Optical Bonding	1

Disclaimer

This datasheet is for informational purposes only and does not constitute professional advice, a contractual obligation, or a guarantee of any kind. While efforts have been made to ensure accuracy, ACT POWER TAIWAN makes no representations or warranties, express or implied, regarding its completeness or reliability. ACT POWER TAIWAN reserves the right to update, modify, or withdraw this document at any time without prior notice. Users should verify the suitability of the product for their specific application through independent testing and validation. ACT POWER TAIWAN shall not be liable for any direct, indirect, or consequential damages arising from the use of this document. This document is governed by the laws of Taiwan, and any disputes shall be subject to the exclusive jurisdiction of the Taiwan courts.