


# MIC-D1508-OF

15.6" Capacitive Touch Military LCD Monitor Open Frame

## Features

- 15.6" LCD Size
- 1920 x 1080 Resolution
- 400 nits Brightness (after Bonding)
- -30 to + 80°C Operating Temperature
- Capacitive Touch Screen
- EMI Mesh, Optical Bonding
- D38999 Types Connectors for Interfaces
- Open Frame Design

## Appearance





# MIC-D1508-OF

15.6” Capacitive Touch Military LCD Monitor Open Frame

## Revision Table

Date	Revision	Content	By
2025/3/27	0.1	First Draft	Dennis

ACT POWER TAIWAN  
PRELIMINARY

# MIC-D1508-OF

15.6" Capacitive Touch Military LCD Monitor Open Frame

## Specification

LCD Panel	
LCD Size	15.6 inch TFT LCD
Backlight	LED
Resolution	1920 x 1080
No. of Colours	16.2M
View Angle	± 85° (H), ±85° (V)
Luminance	400 nits (after Bonding)
Contrast Ratio	800:1
Pixel Pitch	0.17925 x 0.17925mm
Aspect Ratio	16:9
LCD Panel Life time	50,000 hrs.
Interface	LVDS
Response Time	25ms (Tr+Tf)
Active Area	344.16(W) x 193.59(H) mm
Touch Glass	
EMI Mesh	Yes
Optical Bonding	Yes
Cover Glass	Capacitive Multi-Touch Glass
Interface	USB
Glass Surface Hardness	≥5H

# MIC-D1508-OF

15.6" Capacitive Touch Military LCD Monitor Open Frame

## Specification

Interfaces	
Power Input	1x 12VDC Input Connector: D38999/20WA98PN Cap: D38999/33W9N
Input Sources	1x VGA Input Connector: D38999/20WD19SN Cap: D38999/33W15N  1x HDMI Connector: D38999/20WD19SN Cap: D38999/33W15N
Touch Interface	1x USB Connector: USBFTV21G Cap: D38999/33W15N
OSD Keypad	Membrane Type
OSD Keys	Multi Language OSD Menu; Buttons: Power ON/OFF, Menu, Select, Adjust -, Adjust +
Mechanical	
Material	Aluminium Alloy
Design	Open Frame with Front Handle
Dimension	Approx. 430 x 290 x 40mm (Exclude Connectors Height)

## Environment Compliance

Operating Temp.	-30°C to +80°C
Storage Temp.	-40°C to +85°C
Humidity	Ta≤40°C, 90%RH, Non-Condensing
Shock	Design to meet MIL-STD-810G
Vibration	Design to meet MIL-STD-810G
EMI/EMC	Design to meet MIL-STD461E/F

Environmental performance may vary according to the integration method or final integration scenario.


# MIC-D1508-OF

15.6” Capacitive Touch Military LCD Monitor Open Frame

## Deliverables

1	15.6” Capacitive Touch Military LCD Monitor Open Frame
2	External Cables (Optional – to be Customized)

## Reference Drawings



## Ordering Information

Model Name	Description	Unit
MIC-D1508-OF	15.6” Capacitive Touch Military LCD Monitor Open Frame	1

### Disclaimer

This datasheet is for informational purposes only and does not constitute professional advice, a contractual obligation, or a guarantee of any kind. While efforts have been made to ensure accuracy, ACT POWER TAIWAN makes no representations or warranties, express or implied, regarding its completeness or reliability. ACT POWER TAIWAN reserves the right to update, modify, or withdraw this document at any time without prior notice. Users should verify the suitability of the product for their specific application through independent testing and validation. ACT POWER TAIWAN shall not be liable for any direct, indirect, or consequential damages arising from the use of this document. This document is governed by the laws of Taiwan, and any disputes shall be subject to the exclusive jurisdiction of the Taiwan courts.