

MIC-D2406

24" LCD Module with EMI Mesh & Optical Bonding

Features

- 24" LCD Size
- 1920 x 1200 Resolution
- AR/AF Strengthen Touch Glass
- 700nits Brightness
- EMI Mesh, Optical Bonding

Appearance





MIC-D2406

24” LCD Module with EMI Mesh & Optical Bonding

Revision Table

Date	Revision	Content	By
2023/11/21	0.1	First Draft	Dennis

MIC-D2406

24" LCD Module with EMI Mesh & Optical Bonding

Specification

LCD Panel	
LCD Size	24 inch TFT LCD
Backlight	LED
Resolution	1920 x 1200
Interface	LVDS
View Angle	$\pm 89^{\circ}$ (H), $\pm 89^{\circ}$ (V)
Luminance	700 nits
Contrast Ratio	1000:1
Aspect Ratio	16:10
Response Time	14ms
No. of colour	1.07B
Active Area	518.4.(H) x 324(V) mm
Pixel Pitch	0.270 (H) x 0.270 (V)
LED Life time	50,000 hrs
Cover Glass	
Touch Type	-
Active Area	-
Touch Interface	-
Cover Glass	AR/AF Strengthen Glass
EMI Mesh	Yes
Optical Bonding	Yes
Touch Drives	-

MIC-D2406

24” LCD Module with EMI Mesh & Optical Bonding Environment Compliance

Operating Temp.	-20°C to +70°C ** +70°C surface temperature subject to complete housing design for heat dissipation.
Storage Temp.	-30°C to +70°C
Humidity	Ta≤40°C, 90%RH, non-condensing
Shock	Design to meet MIL-STD-810F
Vibration	Design to meet MIL-STD-810E
EMI/EMC	Design to meet MIL-STD461E/F

Note 1: Environmental performance may vary according to the integration method or final integration scenario.
 Note 2: Follow the industrial quality standard this LCD panel will include minimum 3 bright or dead pixels on viewable area and maxium total 5 bright or dead pixels on whole LCD panel.

Deliverables

1	24” LCD Module with EMI Mesh & Optical Bonding
2	AD Board
3	LVDS Cable
4	Backlight Power Cable
5	Power Convert Unit
6	AD Board Power Cable
7	OSD Keyboard
8	OSD Cable



MIC-D2406

24” LCD Module with EMI Mesh & Optical Bonding

Ordering Information

Model Name	Description	Unit
MIC-D2406	24” LCD Module with EMI Mesh & Optical Bonding	1

Disclaimer

This datasheet is for informational purposes only and does not constitute professional advice, a contractual obligation, or a guarantee of any kind. While efforts have been made to ensure accuracy, ACT POWER TAIWAN makes no representations or warranties, express or implied, regarding its completeness or reliability. ACT POWER TAIWAN reserves the right to update, modify, or withdraw this document at any time without prior notice. Users should verify the suitability of the product for their specific application through independent testing and validation. ACT POWER TAIWAN shall not be liable for any direct, indirect, or consequential damages arising from the use of this document.