

SLM-MR240K-E

24" Resistive Touch LCD Kit with EMI Mesh & Optical Bonding

Features

- Operating Temperature: -20°C to $+60^{\circ}\text{C}$
- Storage Temperature: -30°C to $+70^{\circ}\text{C}$
- Optical Bonding: EMI Mesh with Optical Bonding
- LED Life Time: 50,000 Hours (Min)
- EMI/EMC Is Designed to Meet MIL-STD-461E/F
- Shock Is Designed to Meet MIL-STD-810D
- Vibration Is Designed to Meet MIL-STD-810E

Appearance





SLM-MR240K-E

24” Resistive Touch LCD Kit with EMI Mesh & Optical Bonding

Revision Table

Date	Revision	Content	By
2025/2/14	0.1	New datasheet update	Mark

SLM-MR240K-E

24" Resistive Touch LCD Kit with EMI Mesh & Optical Bonding

Specification

LCD Panel	
LCD Size	24 inch TFT
Backlight	LED
Resolution	1920 x 1080
Interface	LVDS
View Angle	$\pm 89^{\circ}$ (H), $\pm 89^{\circ}$ (V)
Luminance	700 nits(after bonding)
Contrast Ratio	1000:1
Aspect Ratio	16:10
Response Time	14 ms
No. of color	1.07 B
Active Area	518.4 (H) x 324 (V) mm
Pixel Pitch	0.270 (H) x 0.270 (V)
LED Life time	50,000 Hrs
EMI Mesh	Yes
Optical Bonding	Yes
Touch Panel	
Touch Type	5-wires Resistive Touch
Active Area	518.4 x 324 mm
Touch Interface	USB
Cover Glass	AR/AG Strengthen Glass
Touch Drives	Support Linux, Windows, Mac, etc.

SLM-MR240K-E

24" Resistive Touch LCD Kit with EMI Mesh & Optical Bonding

Specification

AD Board	
Support VGA signal	Color : 24 bit / Hor. Frequency : 30-80KHz / Ver. Frequency : 50-75Hz
Support DVI/HDMI signal	Color : 24 bit / Hor. Frequency : 30-80KHz / Ver. Frequency : 50-75Hz
Input Interface	VGA / DVI / HDMI (1.3/1.4) / USB / Audio
Output Interface	41Pin / 0.5mm LVDS Connector / Wafer 4Pin 2.0mm (R/L x1) AV Output x 1
Key Control	Power, Menu, Select, CH+, CH-, Up, Down
OSD Language	English
DC Input	DC +12V
Panel Select	DC +3.3V / +5V / +12V

Environment Compliance

Operating Temp.	-20°C to +60°C
Storage Temp.	-30°C to +70°C
Humidity	Ta=40°C, 95%RH, non-condensing
Shock	Design to meet MIL-STD-810D
Vibration	Design to meet MIL-STD-810E
EMI/EMC	Design to meet MIL-STD461E/F

Environmental performance may vary according to the integration method or final integration scenario.



SLM-MR240K-E

24” Resistive Touch LCD Kit with EMI Mesh & Optical Bonding

Deliverables

1	24” Resistive Touch LCD Module with EMI Mesh & Optical Bonding
2	Touch Control Board
3	Touch USB Cable
4	AD Board
5	LVDS Cable
6	Convert Board
7	Convert Board to AD Board Cable
8	Backlight Cable

Ordering Information

Model Name	Description	Unit
SLM-MR240K-E	24” Resistive Touch LCD Module with EMI Mesh & Optical Bonding	1

Disclaimer

This datasheet is for informational purposes only and does not constitute professional advice, a contractual obligation, or a guarantee of any kind. While efforts have been made to ensure accuracy, ACT POWER TAIWAN makes no representations or warranties, express or implied, regarding its completeness or reliability. ACT POWER TAIWAN reserves the right to update, modify, or withdraw this document at any time without prior notice. Users should verify the suitability of the product for their specific application through independent testing and validation. ACT POWER TAIWAN shall not be liable for any direct, indirect, or consequential damages arising from the use of this document.