


### **LC70 Level Control**

The LC70 is a float operated liquid level control device sometimes referred to as a "trunnion" or a "float nose". The LC70 utilizes a large float, linkage rod and levers to mechanically operate a dump valve via rotational connections.

The LC70 is available in 2 different body styles: Union and Bolted. The levers can easily be changed from the left to right to match the dump valve mount. Multiple parts and accessories are available to fit a wide variety of configurations.

When used with a CV45 mechanical valve, the LC70 can provide a level control/dump system that is completely emissions free!



# **Specifications**

Sizes: 8" and 5" Union Connections, 5" Bolted Connection


Pressure Rating: 500 psi

Temperature Range: -20° F to 400° F (-29° C to 204° C)

Materials:

**Body:** A216 Gr WCC Steel **Float:** Powder Coated Steel

Float Arm: 3/4" SST Shaft: 304 SST Bushings: 304 SST Seals: Viton




Typical installation of LC70 and CV45 mechanical valve.

Parts & Accessories (Sold Separately)		
Category	P/N	Description
Float Arms	57-05-0585	Arm Float 12 Inch LC70 SST
	57-05-0586	Arm Float 24 Inch LC70 SST
Weights	57-05-0580	Weight 1LB LC70
	57-05-0581	Weight 2LB LC70
	57-05-0582	Weight 5LB LC70
	57-05-0583	Weight 10LB LC70
	57-05-0584	Collar Weight LC70
Floats	57-05-0502	7" x 12" CS w/ Powder Coat

#### **Union Connection**

#### **Bolted Connection**




Dimensions in inches.

## **How to Order**

Example Model No. LC70U-8-51218

LC70 Series Liquid Level Controller, 8" Union Connection, Standard Service, 5" Weld Neck, 12" Lever, 18" Linkage Rod



Float & Arm Sold Separately
No Weld Neck Option for Bolted LC70



Phone: 409-225-5863

Fax: 409-242-1005

850 Fannin St.

Beaumont, Texas 77701