


PR55 Pressure Reducing Valve

The PR55 series is a self-contained, non-venting, pilot-operated regulator that uses an outside pressure source to operate. This allows it to be used in liquid applications. It is designed for use in various pressure reducing applications. Typical applications include compressor suction control, and supply or distribution pressure control.

The PR55 is offered in 2", 3", 4", and 6" sizes. The 2" and 3" valve are available in both flanged and female NPT thread end connections. The flanged PR55 valves are pressure rated up to 250 psi, and the threaded end valves are rated up to 300 psi.

Maintenance is made simple via removing the bonnet to reveal the seat, allowing the valve body to remain in place during maintenance.



Specifications

Sizes: 2", 3", 4", and 6"

Connections: Female NPT, Flanged

Body Type: Globe

Trim: Soft Seat

Shutoff: Class VI

Pressure Rating:

300 psi - 2", 3" NPT

250 psi - 2", 3", 4", 6" Flanged

Minimum Differential: 0.5 oz

Spring Range: 10 - 300 psi

Temperature Range: -20° F to 250° F

Body, Bonnet, and Hub Material: Ductile Iron


CV Values

CV Values			
2"	3"	4"	6"
53	117	209	491

Dimensions & Weights (5 - 300 psi)

Valve Size	Valve Weights		
	End Connection	lbs	kg
2"	NPT	39	18
	ANSI 150	43	20
3"	NPT	68	31
	ANSI 150	84	38
4"	ANSI 150	127	58
6"	ANSI 150	348	158


Valve Size	Body Dimension			
	End Connection	A	B	C
2"	NPT	8.5	2.38	13.56
	ANSI 150	9	2.88	13.56
3"	NPT	12.06	3.75	14.5
	ANSI 150	12.19	3.75	14.5
4"	ANSI 150	15.06	4.44	15.21
6"	ANSI 150	22	5.63	21.3



Dimensions & Weights - Low Pressure (0.5 oz -20 psi)

Valve Size	Valve Weights		
	End Connection	lbs	kg
2"	NPT	58	27
	ANSI 150	62	28
3"	NPT	87	39
	ANSI 150	103	46
4"	ANSI 150	146	67
6"	ANSI 150	367	167

Valve Size	Body Dimension			
	End Connection	A	B	C
2"	NPT	8.5	2.38	13.13
	ANSI 150	9	2.88	13.13
3"	NPT	12.06	3.75	14.27
	ANSI 150	12.19	3.75	14.27
4"	ANSI 150	15.06	4.44	14.78
6"	ANSI 150	22	5.63	20.51



How to Order

Example Model No. **PR55-2N1-3F**

PR55 Series Pressure Regulating Valve, 2" Globe Body, NPT End Connection, Standard Service, 1-20 psi spring, Full Port.

PR55 - 2 N 1 - 3 F

Body Size			
2 - 2"	3 - 3"	4 - 4"	6 - 6"
Connection			
N - NPT (1", 2", & 3" Only)		F - RFF*	
Service			
1 - Standard		2 - NACE	
Spring			
6 - 10-300 psi spring			
Trim			
F - Full Port		R - Reduced Port	

Beaumont Manufacturing
bmd
 and Distribution Company
www.beaumontmanufacturing.com

Phone: 409-225-5863
 Fax: 409-242-1005
 850 Fannin St.
 Beaumont, Texas 77701