



# SPECIFICATION SHEET

## DF-A33R



Kevlar® stretch knitted glove, black with black foamed nitrile coating on palm and TCR between thumb and index finger.



### BENEFITS

- Breathable.
- High dexterity and flexibility.
- High abrasion and cut resistance.
- Great grip in lightly oily applications.
- TCR provides longer glove life by protecting the area of greatest wear and abrasive demand.



### OPERATIONS

- Handling of wet or dry ceramic parts where the risk of cutting is present.
- Ideal for spot welding processes, where hot metal parts are handled.



### INDUSTRY



Manufacturing



Metalmechanic



MEDIUM  
DEXTERITY



ROOM  
TEMPERATURE



LOW  
(SLIGHTLY DROPLET-LIKE)



120 pairs /  
box



Size  
5 - 10



ANSI  
CUT LEVEL  
**A3**



EN 388

4X43C



GUANTES INTERNACIONALES

“Safety and comfort for the industrial athlete”



# LIMITATIONS OF USE

## 1. Specific protection:

- Designed for mechanical risks: cuts, abrasion, back-of-hand impact, and light vibration.
- Does not provide protection against electrical risks, fire, high temperatures, or chemicals.
- 
- Not to be used for welding.

## 2. Glove Integrity:

- **Do not use** if there is excessive wear, tears, or significant loss of coating, or if visible damage is present on the palm or fingers