



SPECIFICATION SHEET

DF-B34I

previously HC-300I



Grey knitted glove made of HDPE, coated with black sandy nitrile on the palm, with attachments on the fingers and the back of the hand for impact protection.



BENEFITS

- Fluorescent TPR for enhanced visibility.
- Designed to cushion vibrations effectively.
- Lining made of HPPE for added durability.
- Provides a high level of labor protection.
- Diverts bumps and impacts on the hands.



OPERATIONS

- Ideal for managing heavy pieces that could trap hands or fingers, such as handling pipes, metallic plates, and similar tasks.



INDUSTRY



Metalmechanic



Manufacturing



MEDIUM
DEXTERITY



ROOM
TEMPERATURE



LOW
(SLIGHTLY DROPLET-LIKE)



60 pairs /
box



Size
7 - 10



ANSI / ISEA 138



ANSI
CUT LEVEL
A3



EN 388

4X42CP



LIMITATIONS OF USE

1. Specific protection:

- Designed for mechanical risks: cuts, abrasion, back-of-hand impact, and light vibration.
- Does not provide protection against electrical risks, fire, high temperatures, or chemicals.
-
- Not to be used for welding.

2. Glove Integrity:

- **Do not use** if there is excessive wear, tears, or significant loss of coating, or if visible damage is present on the palm or fingers