



SPECIFICATION SHEET

DF-B3CR



Grey knitted glove made of HDPE, 3/4 coated with grey smooth nitrile and black sandy nitrile on the palmand TCR between thumb and index finger.



BENEFITS

- Provides sufficient grip.
- Effectively disperses grease.
- Offers abrasion resistance.
- High impermeability against lubricants.
- Good protection against cut risks.
- TCR provides longer glove life by protecting the area of greatest wear and abrasive demand.



OPERATIONS

- Ideal for metallic processes where there is a high risk of cuts and a significant presence of grease.
- The sandy coating ensures excellent grip.



INDUSTRY



Metalmechanic



LOW
DEXTERITY



ROOM
TEMPERATURE



MEDIUM
(PRESENCE OF OIL OR GREASE)



120 pairs /
box

Size
6 - 10



EN 388



4X42C



GUANTES INTERNACIONALES

"Safety and comfort for the industrial athlete"



LIMITATIONS OF USE

1. Specific protection:

- Designed for mechanical risks: light cuts and abrasion.
- Does not offer protection against electrical hazards, fire, high temperatures, or chemicals.
- Do not use for welding.

2. Glove Integrity:

- **Do not use** if there is excessive wear, tears, or significant loss of coating, or if visible damage is present on the palm or fingers.