



SPECIFICATION SHEET

DF-B3C

previously HCN5S2



Grey knitted glove made of HDPE, 3/4 coated with grey smooth nitrile and black sandy nitrile on the palm.



BENEFITS

- Provides sufficient grip.
- Effectively disperses grease.
- Offers abrasion resistance.
- High impermeability against lubricants.
- Good protection against cut risks.



OPERATIONS

- Ideal for metallic processes where there is a high risk of cuts and a significant presence of grease.
- The sandy coating ensures excellent grip in slippery applications and on smooth surfaces, such as ceramic and metallic materials.



INDUSTRY



Metalmechanic



LOW
DEXTERITY



ROOM
TEMPERATURE



MEDIUM
(PRESENCE OF OIL OR GREASE)



120 pairs /
box

Size
6 - 10



AVAILABLE WITH
TCR



EN 388



4X42C



LIMITATIONS OF USE

1. Specific protection:

- Designed for mechanical risks: cuts, abrasion, back-of-hand impact, and light vibration.
- Does not provide protection against electrical risks, fire, high temperatures, or chemicals.
-
- Not to be used for welding.

2. Glove Integrity:

- **Do not use** if there is excessive wear, tears, or significant loss of coating, or if visible damage is present on the palm or fingers