



SPECIFICATION SHEET

DF-E63R



Tungsten blend knitted glove, jasper blue colour, with black foamed nitrile coating on palm and TCR between thumb and index finger.



BENEFITS

- Breathable.
- High dexterity and flexibility.
- The TCR provides a longer glove life by protecting the area of greatest wear an abrasive demand.
- With the mechanical resistance properties of a Nitrile, but the dexterity and tactility of a polyurethane.



OPERATIONS

- Handling of sharp parts in dry or slightly oily conditions.
- The foamed nitrile coating provides excellent grip.



INDUSTRY



Manufacturing



Metalmechanic



HIGH
DEXTERITY



ROOM
TEMPERATURE



LOW
(SLIGHTLY DROPLET-LIKE)



120 pairs /
box



Size
6 - 10



EN 388



4X43F



GUANTES INTERNACIONALES

"Safety and comfort for the industrial athlete"



LIMITATIONS OF USE

1. Specific protection:

- Designed for mechanical risks: cuts, abrasion, back-of-hand impact, and light vibration.
- Does not provide protection against electrical risks, fire, high temperatures, or chemicals.
-
- Not to be used for welding.

2. Glove Integrity:

- **Do not use** if there is excessive wear, tears, or significant loss of coating, or if visible damage is present on the palm or fingers