

AUT100

STAND-ON COMPACT TRACK LOADER

With their job-proven technology, easy maintenance, simple controls and impressive performance, Austler mini track loaders are perfect for rental applications. Mini track loaders have a smaller, less-intimidating profile than some other compact equipment models. Additionally, they have easy-to-use controls and impressive rated operating capacities to 1,000 pounds.



ATLAS
IRON CE

- ★ Compact in size, packed with performance and features, **Atlas Irons New Stand-on Compact Loader conquers the toughest of tasks yet is nimble enough to get in tight spaces.**
- ★ **A new Kubota 25HP diesel engine** allows for more torque where it matters so you get more done.
- ★ **The integrated ride-on platform of the AUT100 gives you a wider view** to the side of the machine as well as the bucket cutting edge
- ★ The ISO joystick controls on the AUT100 are **ergonomically designed for comfortable operation and less fatigue.**
- ★ Increased torque to the ground drive speed gives the AUT100 superior power to the attachment, **outperforming the competition to dig, lift, and drive. When working at altitudes, the control system optimizes performance, fuel efficiency and torque.**
- ★ Atlas Irons mini track loaders aren't just for lifting heavy loads. The hydraulic quick couplers make connecting and disconnecting from hydraulic attachments fast and easy. These machines are designed to **run a variety of hydraulic attachments efficiently.**

ENGINE

| | |
|--------------------------------|--|
| Engine Type | Vertical, water-cooled, 4-cycle diesel |
| Model Name | KUBOTA D1105-E4B-CWL |
| Total Displacement | 68 cu.in.(1.123L) |
| Engine Power - SAE J1995 Gross | 25 hp / 3000 rpm |
| Rated Speed | 3000rpm |
| Max. Torque | 52 lb-ft |

DIMENSIONS

| | |
|--|--------------|
| "Overall Length - Transport (w/Std Bucket Parallel To Ground)" | 109in |
| Overall Length (w/o Bucket) | 83in |
| Overall Height | 51.6in |
| Overall Width with standard Bucket | 43.7in |
| Overall Width w/o standard Bucket | 35.87in |
| Weight with standard bucket (w/o Operator) lbs | 3066lb |
| Weight w/o bucket | 2895lb |
| Rated Operating Capacity (35%) | 1,000 lb ROC |
| Tipping Load | 2,857 lb |
| Wheelbase | 42in |
| Hinge Pin Height at Max. Lift | 83.5in |
| Reach at Max. Lift and 45° Dump | 19.2in) |

| | |
|--------------------|-------------|
| Bucket capacity | 6.53 cu ft) |
| Track Width | 7.87in |
| Ground Clearance | 6.30in |
| Angle of Departure | 24.8° |

OPERATION

| | |
|--------------------|---|
| Steering And Drive | Dual axis,pilot-operated joystick |
| Lift And Tilt | Dual axis,manual-operated joystick |
| Transmission | Hydrostatic track drive system |
| Attachment | One levers one with dual direction detent |

PERFORMANCE

| | |
|---------------------------------|---------------------------------|
| Attachment Mounting System | CII (Common Industry Interface) |
| Travel Speed (Fwd/Rev) | 4.16 mph |
| Ground Pressure (with Operator) | 4.12 psi |
| Battery Capacity | 12V |
| Auxiliary Hydraulic Flow | 13.5 gal/min |
| Auxiliary Hydraulic Pressure | 2828 psi |

SERVICE & FILL CAPACITIES

| | |
|--------------------|---------|
| Fuel Tank Capacity | 8.32gal |
| Hydraulic System | 5.54gal |



AUT100 DIMENSIONS

