AUT130

UTILITY TRACK LOADER

1,300-LB CAPACITY. STAND-ON CONTROL.

3 YEAR / 3000 HOUR WARRANTY





A compact stand-on track loader with Yanmar turbo diesel power, 1,300 lb rated capacity and up to 16.4 gpm auxiliary flow.

1,300 LB	16.4 GPM	88.6 IN	4.5 MPH
RATED CAPACITY	MAX. AUXILIARY FLOW	HINGE-PIN HEIGHT	MAX. TRAVEL SPEED

PRODUCT HIGHLIGHTS

1. **YANMAR TURBO DIESEL**
   Liquid-cooled diesel power in a compact machine.
2. **PILOT JOYSTICK CONTROL**
   Hydraulic machine control with an electronic auxiliary system.
3. **ATTACHMENT FLEXIBILITY**
   High and low auxiliary flow settings for a range of tools.



PRELIMINARY - factory specifications and final configuration subject to confirmation.

TECHNICAL SPECIFICATIONS

1,300 LB
RATED CAPACITY

16.4 GPM
MAX. AUXILIARY FLOW

88.6 IN
HINGE-PIN HEIGHT

ENGINE

Engine manufacturer	Yanmar
Engine type	Turbocharged, liquid-cooled diesel
Published engine power*	23.5 hp / 17.3 kW
Engine model / rated rpm	Factory confirmation pending

OPERATING SPECIFICATIONS

Rated operating capacity (ISO 14397-1)	1,300 lb
Maximum travel speed	4.5 mph
Ground pressure	4.73 psi
Published machine weight*	3,345 lb

CAPACITY & LIFT

Bucket hinge-pin height	88.6 in
Maximum operating height	120 in
Bucket dump height	61.4 in
Bucket dump angle	40 degrees
Reach - fully raised	20.9 in

DIMENSIONS

Overall length without bucket	86.8 in
Overall length with bucket	113 in
Overall width without bucket	35.8 in
Overall height without bucket	58.4 in
Ground clearance	7.2 in
Track width	7.87 in

HYDRAULIC SYSTEM

Auxiliary flow - low / high	13.1 / 16.4 gpm
Published hydraulic pressure*	3,046 psi
Traction pump flow (each)	13.8 gpm
Traction system	Dual hydrostatic pump

OPERATION & EQUIPMENT

Machine controls	Hydraulic pilot control
Auxiliary control	Electronic control system
Proposed attachment package*	Bucket + pallet forks

DETAILS



RAISED LIFT ARMS



STANDARD BUCKET

* Supplier-listed preliminary specifications. Confirm engine model and power, weight basis, auxiliary pressure at the couplers, attachment mount, final package and warranty before publication. Inconsistent fuel and fluid-capacity conversions are omitted pending confirmation.