

OGAN[®]
hot melt hoses

BÜHNEN Compatible Hot Melt Glue Hoses





Bühnen compatible hot glue hoses

Our products are 100% Bühnen compatible, high industrial standards compatible with the system technological products.

Polyamide, plastic derivative and other high temperature applications.
For our 250C high UHP3 type heated hoses are recommended.

Operation Voltage:	230V AC 50-60 Hz
Temperature sensor type:	PT100
Standard operation temperature:	200 C
Standard operation max. Pressure:	80-160 bar
High temperature applications:	250 C
High temperature applications max. Pressure:	280 bar
Connection connectors:	Bühnen standard
Production standard internal diameters:	DN6 - DN25

Bühnen Hot Melt Glue Hoses DN8	Length	BÜHNEN P/N	OGAN P/N
	1.2 m		BHN-081200
	1.5 m		BHN-081500
	1.8 m		BHN-081800
	2.4 m		BHN-082400
	3.0 m		BHN-083000
	4.5 m		BHN-084500
	6.0 m		BHN-086000
	7.0 m		BHN-087000

Bühnen Hot Melt Glue Hoses DN13	Length	BÜHNEN P/N	OGAN P/N
	1.2 m		BHN-131200
	1.5 m		BHN-131500
	1.8 m		BHN-131800
	2.4 m		BHN-132400
	3.0 m		BHN-133000
	4.5 m		BHN-134500
	6.0 m		BHN-136000
	7.0 m		BHN-137000