

VANLUSTONE
HUBEI AULICE TYRE CO.,LTD.

.....
TRUCK & BUS TYRE
PROFESSIONAL MANUFACTURER

HUBEI AULICE TYRE CO.,LTD.



Add: East New District, YangXin Industrial Zone, Hubei Province, China.
Tel: +86-27-87775708
Mob: +86-13207128011 (Adora Zhao)
Email: adorazhao@aulicetyre.com info@aulicetyre.com
Web: <http://www.aulicetyre.com>

HUBEI AULICE TYRE CO.,LTD.

COMPANY PROFILE

CERTIFICATE OF HONOR



COMPANY PROFILE

Hubei Aulice Tyre Co., Ltd. is a large leading tire manufacturer established in 1998, which integrates scientific research, design, production, and sales of TBR,OTR and BIAS tires.

As the first established plant of all-steel radial truck tire in 2012, AULICE strive to meet the growing demand in developing markets and ensure our customers enjoy high-quality tires at reasonable prices. AULICE owns an over-20-years experienced R&D team and research institute of formula, structure, technology. Powered by a large number of professional tire technicians and senior engineers, it covered 94 sizes, 67 kinds of patterns, 17 R & D patents and 30 registered trademarks. All of the products have obtained international approvals such as CCC, DOT, ECE, GCC, SNI, SGS ,SONCAP, Produced in compliance with the requirements of ISO9001:2000 and gained recognition in domestic and overseas markets.

Based on a production capacity of 6000 sets of all-steel radial tires and 2500 sets of off-road tires per day, Aulice keep increasing the market shares and sells branded tire AULICE, VANLUSTONE, AOSOWING, AOLAISI, JIASHIBAO, SANTIAN, QUNYING to more than 30 provinces in the domestic market and over 60 overseas countries. In Oct 2019, Aulice invested another new plant in Xianning city, which designed to meet another 10000 sets of all-steel radial tires per day.

In the future Aulice will strive to become the No.1 intelligent tire manufacture using the internet+ concept with mega data technology and AI solution to build a smart and powerful tire solution platform in the tire industry. It will provide a very accurate solution to the end-user with different requirements in various road conditions.



• ISO9001 CERTIFICATE



• ECE R117 CERTIFICATE



• GCC CERTIFICATE



• DOT CERTIFICATE



• CCC CERTIFICATE



• SNI CERTIFICATE



• LISTED RESERVE ENTERPRISES



• EXPORT CERTIFICATE



• TOP 100 MANUFACTURING ENTERPRISES IN HUBEI



• IATF16949 CERTIFICATE



• ISO14001 CERTIFICATE

6.00R13LT
6.00R14LT
6.00R15LT



6.50R16LT
PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR156 AR158

AR156	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	6.00R13LT	10PR	10.0	98/94	D	750(1655)	670(1480)	560(80)	4.50B
	6.00R14LT	10PR	10.0	100/96	D	800(1765)	710(1565)	560(80)	4 1/2J
	6.00R15LT	10PR	10.0	101/97	D	825(1820)	730(1610)	560(80)	4 1/2J

AR158	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	6.00R13LT	10PR	12.8	98/94	D	750(1655)	670(1480)	560(80)	4.50B
	6.00R14LT	10PR	12.8	100/96	D	800(1765)	710(1565)	560(80)	4 1/2J
	6.00R15LT	10PR	12.8	101/97	D	825(1820)	730(1610)	560(80)	4 1/2J



AR101 AR111 AR112 AR313 AR316 AR317

AR101	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	6.50R16LT	12PR	12.0	110/105	L	1060(2335)	925(2040)	670(100)	5.50F

AR111	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	6.50R16LT	12PR	12.0	110/105	L	1060(2335)	925(2040)	670(100)	5.50F

AR112	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	6.50R16LT	12PR	10.5	110/105	G	1060(2335)	925(2040)	670(100)	5.50F

AR313	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	6.50R16LT	12PR	12.0	110/105	G	1060(2335)	925(2040)	670(100)	5.50F

AR316	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	6.50R16LT	12PR	15.5	110/105	K	1060(2335)	925(2040)	670(100)	5.50F

AR317	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	6.50R16LT	12PR	18.5	110/105	J	1060(2335)	925(2040)	670(100)	5.50F

7.00R16LT

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR101



AR111



AR112



AR313



AR316



AR317



AR535



AR565

AR101

Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
					Single	Dual		
7.00R16LT	14PR	12.0	118/114	L	1320(2910)	1180(2600)	770(110)	5.50F

AR111

Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
					Single	Dual		
7.00R16LT	14PR	12.0	118/114	K	1320(2910)	1180(2600)	770(110)	5.50F

AR112

Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
					Single	Dual		
7.00R16LT	14PR	11.5	118/114	G	1320(2910)	1180(2600)	770(110)	5.50F

AR313

Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
					Single	Dual		
7.00R16LT	14PR	13.5	118/114	G	1320(2910)	1180(2600)	770(110)	5.50F

AR316

Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
					Single	Dual		
7.00R16LT	14PR	15.5	118/114	K	1320(2910)	1180(2600)	770(110)	5.50F

AR317

Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
					Single	Dual		
7.00R16LT	14PR	18.5	118/114	J	1320(2910)	1180(2600)	770(110)	5.50F

AR535

Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
					Single	Dual		
7.00R16LT	14PR	20.0	118/114	F	1320(2910)	1180(2600)	770(110)	5.50F

AR565

Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
					Single	Dual		
7.00R16LT	14PR	14.5	118/114	D	1320(2910)	1180(2600)	770(110)	5.50F

7.50R16LT

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR101



AR111



AR112



AR313



AR316



AR317



AR535



AR565



AR587



AR586

AR101	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	7.50R16LT	14PR	13.5	122/118	L	1500(3305)	1320(2910)	770(110)	6.00G
	7.50R16LT	14PR	13.5	122/120	L	1510(3330)	1440(3170)	700(102)	6.00G

AR111	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	7.50R16LT	14PR	13.5	122/118	L	1500(3305)	1320(2910)	770(110)	6.00G
	7.50R16LT	14PR	13.5	122/120	L	1510(3330)	1440(3170)	700(102)	6.00G

AR112	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	7.50R16LT	14PR	12.0	122/118	G	1500(3305)	1320(2910)	770(110)	6.00G
	7.50R16LT	14PR	12.0	122/120	G	1510(3330)	1440(3170)	700(102)	6.00G

AR313	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	7.50R16LT	14PR	14.0	122/118	G	1500(3305)	1320(2910)	770(110)	6.00G
	7.50R16LT	14PR	14.0	122/120		1510(3330)	1440(3170)	700(102)	6.00G

AR316	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	7.50R16LT	14PR	16.0	122/118	K	1500(3305)	1320(2910)	770(110)	6.00G
	7.50R16LT	14PR	16.0	122/120	K	1510(3330)	1440(3170)	700(102)	6.00G

AR317	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	7.50R16LT	14PR	19.0	122/118	J	1500(3305)	1320(2910)	770(110)	6.00G
	7.50R16LT	14PR	19.0	122/120	K	1510(3330)	1440(3170)	700(102)	6.00G

AR535	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	7.50R16LT	14PR	20.0	122/118	F	1500(3305)	1320(2910)	770(110)	6.00G
	7.50R16LT	14PR	20.0	122/120	F	1510(3330)	1440(3170)	700(102)	6.00G

AR565	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	7.50R16LT	14PR	16.5	122/118	D	1500(3305)	1320(2910)	770(110)	6.00G

AR587	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	7.50R16LT	14PR	20.0	122/120	F	1510(3330)	1440(3170)	700(102)	6.00G

AR586	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	7.50R16LT	14PR	20.0	122/120	F	1510(3330)	1440(3170)	700(102)	6.00G

8.25R16LT

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR101	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R16LT	14PR	14.0	126/124	L	1710(3770)	1630(3590)	625(91)	6.50H
	8.25R16LT	16PR	14.0	128/124	L	1800(3970)	1600(3525)	770(110)	6.50H

AR111	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R16LT	16PR	14.0	128/124	L	1800(3970)	1600(3525)	770(110)	6.50H

AR112	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R16LT	16PR	14.0	128/124	G	1800(3970)	1600(3525)	770(110)	6.50H

AR313	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R16LT	16PR	14.5	128/124	G	1800(3970)	1600(3525)	770(110)	6.50H

AR316	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R16LT	14PR	16.0	126/122	K	1700(3750)	1500(3305)	670(100)	6.50H
	8.25R16LT	16PR	16.0	128/124	K	1800(3970)	1600(3525)	770(110)	6.50H

AR317	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R16LT	16PR	19.0	128/124	F	1800(3970)	1600(3525)	770(110)	6.50H

AR535	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R16LT	16PR	21.0	128/124	F	1800(3970)	1600(3525)	770(110)	6.50H

AR565	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R16LT	16PR	17.5	128/124	D	1800(3970)	1600(3525)	770(110)	6.50H

AR399	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R16LT	16PR	18.2	128/124	D	1800(3970)	1600(3525)	770(110)	6.50H

8.25R20

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR101 AR318 AR525 AR535

AR101	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R20	14PR	17.0	136/134	K	2240(4940)	2120(4675)	830(120)	6.5
	8.25R20	16PR	17.0	139/137	K	2430(5360)	2300(5070)	930(135)	6.5

AR318	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R20	14PR	20.0	136/134	K	2240(4940)	2120(4675)	830(120)	6.5
	8.25R20	16PR	20.0	139/137	K	2430(5360)	2300(5070)	930(135)	6.5

AR525	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R20	14PR	21.0	136/134	E	2240(4940)	2120(4675)	830(120)	6.5
	8.25R20	16PR	21.0	139/137	E	2430(5360)	2300(5070)	930(135)	6.5

AR535	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	8.25R20	14PR	21.0	136/134	D	2240(4940)	2120(4675)	830(120)	6.5
	8.25R20	16PR	21.0	139/137	D	2430(5360)	2300(5070)	930(135)	6.5

12.00R24

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AW002 AW003 AW902

AW002	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R24	20PR	14.5	160/157	K	4500(9920)	4125(9090)	900(130)	8.5
	12.00R24	22PR	14.5	162/159	K	4750(10480)	4375(9650)	930(135)	8.5

AW003	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R24	20PR	14.8	160/157	K	4500(9920)	4125(9090)	900(130)	8.5
	12.00R24	22PR	14.8	162/159	K	4750(10480)	4375(9650)	930(135)	8.5

AW902	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R24	20PR	20.0	160/157	F	4500(9920)	4125(9090)	900(130)	8.5
	12.00R24	22PR	20.0	162/159	F	4750(10480)	4375(9650)	930(135)	8.5

9.00R20

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR101 AR112 AR318 AR399 AR525 AR535



AR513 AR366 HL658

AR101	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	9.00R20	14PR	17.5	141/139	K	2575(5675)	2430(5355)	790(115)	7.0
	9.00R20	16PR	17.5	144/142	K	2800(6175)	2650(5840)	900(130)	7.0

AR112	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	9.00R20	14PR	15.0	141/139	J	2575(5675)	2430(5355)	790(115)	7.0
	9.00R20	16PR	15.0	144/142	J	2800(6175)	2650(5840)	900(130)	7.0

AR318	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	9.00R20	14PR	20.0	141/139	J	2575(5675)	2430(5355)	790(115)	7.0
	9.00R20	16PR	20.0	144/142	J	2800(6175)	2650(5840)	900(130)	7.0

AR399	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	9.00R20	14PR	20.0	141/139	D	2575(5675)	2430(5355)	790(115)	7.0
	9.00R20	16PR	20.0	144/142	D	2800(6175)	2650(5840)	900(130)	7.0

AR525	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	9.00R20	14PR	21.0	141/139	E	2575(5675)	2430(5355)	790(115)	7.0
	9.00R20	16PR	21.0	144/142	E	2800(6175)	2650(5840)	900(130)	7.0

AR535	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	9.00R20	14PR	21.0	141/139	D	2575(5675)	2430(5355)	790(115)	7.0
	9.00R20	16PR	21.0	144/142	D	2800(6175)	2650(5840)	900(130)	7.0

AR513	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	9.00R20	14PR	15.2	141/139	F	2575(5675)	2430(5355)	790(115)	7.0
	9.00R20	16PR	15.2	144/142	F	2800(6175)	2650(5840)	900(130)	7.0

AR366	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	9.00R20	14PR	20.0	141/139	J	2575(5675)	2430(5355)	790(115)	7.0
	9.00R20	16PR	20.0	144/142	J	2800(6175)	2650(5840)	900(130)	7.0

HL658	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	9.00R20	14PR	20.0	141/149	A8	2575(5675)	2430(5355)	790(115)	7.0
	9.00R20	16PR	20.0	144/142	A8	2800(6175)	2650(5840)	900(130)	7.0

HL526	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	9.00R20	14PR	23.0	141/139	E	2575(5675)	2430(5355)	790(115)	7.0
	9.00R20	16PR	23.0	144/142	E	2800(6175)	2650(5840)	900(130)	7.0

10.00R20

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR101 AR112 AR318 AR399 AR525 AR535



AR366 AR585 AW001 AR513 AR3137 HL658

AR101	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	10.00R20	16PR	16.0	146/143	K	3000(6610)	2725(6010)	830(120)	7.5
	10.00R20	18PR	16.0	149/146	K	3250(7160)	3000(6610)	930(135)	7.5

AR112	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	10.00R20	16PR	16.0	146/143	J	3000(6610)	2725(6010)	830(120)	7.5
	10.00R20	18PR	16.0	149/146	J	3250(7160)	3000(6610)	930(135)	7.5

AR318	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	10.00R20	16PR	20.0	146/143	J	3000(6610)	2725(6010)	830(120)	7.5
	10.00R20	18PR	20.0	149/146	J	3250(7160)	3000(6610)	930(135)	7.5

AR399	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	10.00R20	16PR	20.0	146/143	D	3000(6610)	2725(6010)	790(115)	7.5
	10.00R20	18PR	20.0	149/146	J	3250(7160)	3000(6610)	930(135)	7.5

AR525	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	10.00R20	18PR	21.0	149/146	F	3250(7160)	3000(6610)	930(135)	7.5
	10.00R20	18PR	21.0	149/146	J	3250(7160)	3000(6610)	930(135)	7.5

AR535	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	10.00R20	18PR	21.0	149/146	D	3250(7160)	3000(6610)	930(135)	7.5
	10.00R20	18PR	21.0	149/146	F	3250(7160)	3000(6610)	930(135)	7.5

AR366	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	10.00R20	18PR	20.0	149/146	D	3250(7160)	3000(6610)	930(135)	7.5

AR585	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	10.00R20	18PR	23.0	149/146	F	3250(7160)	3000(6610)	930(135)	7.5

AW001	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	10.00R20	18PR	16.0	149/146	K	3250(7160)	3000(6610)	930(135)	7.5

AR513	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	10.00R20	18PR	15.8	149/146	F	3250(7160)	3000(6610)	930(135)	7.5

AR3137	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	10.00R20	18PR	19.5	149/146	J	3250(7160)	3000(6610)	930(135)	7.5

HL658	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	10.00R20	16PR	20.0	146/143	A8	3000(6610)	2725(6010)	830(120)	7.5
	10.00R20	18PR	20.0	149/146	A8	3250(7160)	3000(6610)	930(135)	7.5

HL526	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	10.00R20	16PR	23.0	146/143	H	3000(6610)	2725(6010)	830(120)	7.5
	10.00R20	18PR	23.0	149/146	J	3250(7160)	3000(6610)	930(135)	7.5

11.00R20

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR101 AR133 AR188 AR3137 AR318 AR3581



AR412 AR525 AR535 AR5157 AR586 AR587

AR101	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	15.5	150/147	K	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	15.5	152/149	K	3550(7830)	3250(7160)	930(135)	8.0

AR133	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	15.0	150/147	K	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	15.0	152/149	K	3550(7830)	3250(7160)	930(135)	8.0

AR188	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	16.0	150/147	J	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	16.0	152/149	J	3550(7830)	3250(7160)	930(135)	8.0

AR3137	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	19.0	150/147	J	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	19.0	152/149	J	3550(7830)	3250(7160)	930(135)	8.0

AR318	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	18PR	18.2	152/149	J	3550(7830)	3250(7160)	930(135)	8.0

AR3581	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	18.5	150/147	J	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	18.5	152/149	J	3550(7830)	3250(7160)	930(135)	8.0

AR412	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	17.5	150/147	J	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	17.5	152/149	J	3550(7830)	3250(7160)	930(135)	8.0

AR525	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	22.0	150/147	F	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	22.0	152/149	D	3550(7830)	3250(7160)	930(135)	8.0

AR535	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	24.0	150/147	F	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	24.0	152/149	D	3550(7830)	3250(7160)	930(135)	8.0

AR5157	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	18PR	28.0	152/149	A8	3550(7830)	3250(7160)	930(135)	8.0

AR586	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	18PR	24.0	152/149	D	3550(7830)	3250(7160)	930(135)	8.0

AR587	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	18PR	24.0	152/149	D	3550(7830)	3250(7160)	930(135)	8.0

11.00R20

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR585



AR595



AR558



AR581



AR112



AR665



AR666



AR667



HL658

AR585	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	24.5	150/147	D	3350(7385)	3075(6780)	830(120)	8.0

AR595	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	23.0	150/147	A8	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	23.0	152/149	A8	3750(8270)	3450(7610)	930(135)	8.0

AR558	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	24.0	150/147	D	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	24.0	152/149	D	3750(8270)	3450(7610)	830(120)	8.0

AR581	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	23.5	150/147	J	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	23.5	152/149	J	3750(8270)	3450(7610)	830(120)	8.0

AR112	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	16.5	150/147	J	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	16.5	152/149	J	3550(7830)	3250(7160)	930(135)	8.0

AR665	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	18PR	24.0	152/149	D	3550(7830)	3250(7160)	930(135)	8.0

AR666	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	18PR	24.0	152/149	D	3550(7830)	3250(7160)	930(135)	8.0

AR667	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	18PR	24.0	152/149	D	3550(7830)	3250(7160)	930(135)	8.0

HL658	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11.00R20	16PR	20.0	150/147	J	3350(7385)	3075(6780)	830(120)	8.0
	11.00R20	18PR	20.0	152/149	J	3750(8270)	3450(7610)	830(120)	8.0

12.00R20

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR1017



AR1121



AR3137



AR5157



AR3581



AR5251



AR5255



AR535



AR586



AR413



HL338

AR1017	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	15.5	154/151	K	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	15.5	156/153	K	4000(8820)	3650(8050)	900(130)	8.5

AR1121	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	16.5	154/151	J	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	16.5	156/153	J	4000(8820)	3650(8050)	900(130)	8.5

AR3137	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	20PR	19.0	156/153	J	4000(8820)	3650(8050)	900(130)	8.5

HL526	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	22.0	154/151	F	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	22.0	156/153	D	4000(8820)	3650(8050)	930(135)	8.5

AR5157	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	20PR	26.5	156/153	A8	4000(8820)	3650(8050)	900(130)	8.5

AR3581	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	18.5	154/151	J	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	18.5	156/153	J	4000(8820)	3650(8050)	900(130)	8.5

AR5251	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	22.0	154/151	D	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	22.0	156/153	D	4000(8820)	3650(8050)	900(130)	8.5

AR5255	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	22.0	154/151	D	3750(8270)	3450(7610)	830(120)	8.5

AR535	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	24.0	154/151	F	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	24.0	156/153	F	4000(8820)	3650(8050)	900(130)	8.5

AR586	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	24.0	154/151	F	3750(8270)	3450(7610)	830(120)	8.5

AR413	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	17.0	154/151	J	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	17.0	156/153	J	4000(8820)	3650(8050)	900(130)	8.5

HL338	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	18.5	154/151	K	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	18.5	156/153	K	4000(8820)	3650(8050)	930(135)	8.5

12.00R20

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR587



AR332



AR558



AR338



AR418



AR366



AR377



AR585



AR597



AR595



AR415



AR527

AR587	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	24.0	154/151	F	Single	Dual	830(120)	8.5
	12.00R20	18PR	24.0	154/151	F	3750(8270)	3450(7610)	830(120)	8.5

AR332	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	17.0	154/151	D	Single	Dual	830(120)	8.5
	12.00R20	20PR	17.0	156/153	E	4000(8820)	3650(8050)	900(130)	8.5

AR558	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	24.0	154/151	D	Single	Dual	830(120)	8.5
	12.00R20	20PR	24.0	156/153	D	4000(8820)	3650(8050)	900(130)	8.5

AR338	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	21.0	154/151	D	Single	Dual	830(120)	8.5
	12.00R20	20PR	21.0	156/153	F	4000(8820)	3650(8050)	900(130)	8.5

AR418	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	17.5	154/151	D	Single	Dual	830(120)	8.5
	12.00R20	20PR	17.5	156/153	J	4000(8820)	3650(8050)	900(130)	8.5

AR366	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	18.5	154/151	D	Single	Dual	830(120)	8.5
	12.00R20	20PR	18.5	156/153	D	4000(8820)	3650(8050)	900(130)	8.5

AR377	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	18.5	154/151	D	Single	Dual	830(120)	8.5

AR585	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	25.0	154/151	F	Single	Dual	830(120)	8.5
	12.00R20	20PR	25.0	156/153	F	4000(8820)	3650(8050)	900(130)	8.5

AR597	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	24.8	154/151	A8	Single	Dual	830(120)	8.5
	12.00R20	20PR	24.8	156/153	A8	4000(8820)	3650(8050)	900(130)	8.5

AR595	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	23.0	154/151	A8	Single	Dual	830(120)	8.5
	12.00R20	20PR	23.0	156/153	A8	4000(8820)	3650(8050)	900(130)	8.5

AR415	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	18.5	154/151	J	Single	Dual	830(120)	8.5
	12.00R20	20PR	18.5	156/153	J	4000(8820)	3650(8050)	900(130)	8.5

AR527	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
	12.00R20	18PR	22.9	154/151	D	Single	Dual	830(120)	8.5
	12.00R20	20PR	22.9	156/153	D	4000(8820)	3650(8050)	900(130)	8.5

12.00R20

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR665 AR666 AR667 AR417 AR583 AR5158



AR596 AR581 AR412 HL658 HL339

AR665	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	24.0	154/151	D	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	24.0	156/153	D	4000(8820)	3650(8050)	900(130)	8.5

AR666	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	24.0	154/151	D	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	24.0	156/153	D	4000(8820)	3650(8050)	900(130)	8.5

AR667	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	24.0	154/151	D	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	24.0	156/153	D	4000(8820)	3650(8050)	900(130)	8.5

AR417	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	18.5	154/151	J	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	18.5	156/153	J	4000(8820)	3650(8050)	900(130)	8.5

AR583	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	20PR	31.5	156/153	D	3750(8270)	3450(7610)	830(120)	8.5

AR5158	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	20PR	24.5	156/153	A8	3750(8270)	3450(7610)	830(120)	8.5

AR596	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	20PR	26.0	156/153	A8	4000(8820)	3650(8050)	900(130)	8.5

AR581	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	20PR	24.8	156/153	E	4000(8820)	3650(8050)	900(130)	8.5

AR412	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	16.5	154/151	D	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	16.5	156/153	J	4000(8820)	3650(8050)	900(130)	8.5

HL658	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	20PR	20.0	156/153	J	4000(8820)	3650(8050)	900(130)	8.5

HL339	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	20PR	18.0	156/153	K	4000(8820)	3650(8050)	900(130)	8.5

HL537	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	18PR	23.5	154/151	F	3750(8270)	3450(7610)	830(120)	8.5
	12.00R20	20PR	23.5	156/153	D	4000(8820)	3650(8050)	930(135)	8.5

HL702	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12.00R20	20PR	19.0	146/153	G	4000(8820)	3650(8050)	930(135)	8.5

275/70R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AW767

AW767	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	275/70R22.5	16PR	15.0	144/141	K	2800(6175)	2650(5840)	830(120)	8.25
	275/70R22.5	18PR	15.0	146/143	K	3000(6610)	2725(6005)	900(130)	8.25

385/65R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR113

AR113	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	385/65R22.5	18PR	15.5	158	K	4250(9370)	3875(8540)	830(120)	11.75
	385/65R22.5	20PR	15.5	160	K	4500(9930)	4125(9090)	900(130)	11.75

275/80R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



HL300

HL300	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	275/80R22.5	18PR	14.5	149/146	M	3250(7160)	3000(6610)	900(130)	8.25

295/60R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



HL300

HL300	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	295/60R22.5	18PR	15.5	150/147	M	3350(7385)	3075(6780)	900(130)	9.0

11R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AW903 AW817 AW002 AW003 AW767



AW787 AW819 AW901 AR737 AR818

AW903	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R22.5	16PR	23.0	146/143	F	3000(6610)	2725(6005)	830(120)	8.25

AW817	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R22.5	16PR	21.0	146/143	M	3000(6610)	2725(6005)	830(120)	8.25

AW002	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R22.5	16PR	14.5	146/143	K	3000(6610)	2725(6005)	830(120)	8.25
	11R22.5	18PR	14.5	149/146	K	3250(7160)	3000(6610)	930(135)	8.25

AW003	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R22.5	16PR	14.5	146/143	K	3000(6610)	2725(6005)	830(120)	8.25
	11R22.5	18PR	14.5	149/146	K	3250(7160)	3000(6610)	930(135)	8.25

AW767	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R22.5	16PR	14.5	146/143	M	3000(6610)	2725(6005)	830(120)	8.25
	11R22.5	18PR	14.5	149/146	M	3250(7160)	3000(6610)	930(135)	8.25

AW787	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R22.5	16PR	14.5	146/143	M	3000(6610)	2725(6005)	830(120)	8.25
	11R22.5	18PR	14.5	149/146	M	3250(7160)	3000(6610)	930(135)	8.25

AW819	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R22.5	16PR	19.5	146/143	L	3000(6610)	2725(6005)	830(120)	8.25
	11R22.5	18PR	19.5	149/146	L	3250(7160)	3000(6610)	930(135)	8.25

AW901	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R22.5	16PR	21.0	146/143	K	3000(6610)	2725(6005)	830(120)	8.25
	11R22.5	18PR	21.0	149/146	K	3250(7160)	3000(6610)	930(135)	8.25

AR737	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R22.5	16PR	16.5	146/143	K	3000(6610)	2725(6005)	830(120)	8.25
	11R22.5	18PR	16.5	149/146	K	3250(7160)	3000(6610)	930(135)	8.25

AR818	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R22.5	16PR	22.0	146/143	K	3000(6610)	2725(6005)	830(120)	8.25
	11R22.5	18PR	22.0	149/146	K	3250(7160)	3000(6610)	930(135)	8.25

12R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR731



AR737



AR7381



AR766



AR777



AR778



AR815



AR818



AR819



AR868



AR869



AR999

AR731	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	16.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	16.0	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

AR737	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	16.5	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	16.5	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

AR7381	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	16.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	16.5	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

AR766	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	16.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	16.0	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

AR777	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	17.0	150/147	L	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	17.0	152/149	L	3550(7830)	3250(7160)	930(135)	9.00

AR778	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	17.5	150/147	L	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	17.5	152/149	L	3550(7830)	3250(7160)	930(135)	9.00

AR815	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	17.5	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	17.5	152/149	L	3550(7830)	3250(7160)	930(135)	9.00

AR818	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	22.5	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	22.5	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

AR819	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	22.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	22.0	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

AR868	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	18.5	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	18.5	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

AR869	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	17.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	17.0	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

AR999	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	16.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	16.0	152/149	J	3550(7830)	3250(7160)	930(135)	9.00

12R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR916 AR918 AR900 AR888 AR266 AR268



AR112 AR898 AR358 AR878 AR535 AR525

AR916	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	16.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	16.0	152/149	J	3550(7830)	3250(7160)	930(135)	9.00

AR918	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	16.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	16.0	152/149	J	3550(7830)	3250(7160)	930(135)	9.00

AR900	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	14.4	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	14.4	152/149	J	3550(7830)	3250(7160)	930(135)	9.00

AR888	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	20.0	150/147	D	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	20.0	152/149	D	3550(7830)	3250(7160)	930(135)	9.00

AR266	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	15.5	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	15.5	152/149	J	3550(7830)	3250(7160)	930(135)	9.00

AR268	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	16.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	16.0	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

AR112	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	14.5	150/147	J	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	14.5	152/149	J	3550(7830)	3250(7160)	930(135)	9.00

AR898	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	20.0	150/147	D	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	20.0	152/149	D	3550(7830)	3250(7160)	930(135)	9.00

AR358	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	18.0	150/147	F	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	18.0	152/149	F	3550(7830)	3250(7160)	930(135)	9.00

AR878	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	18.0	150/147	F	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	18.0	152/149	F	3550(7830)	3250(7160)	930(135)	9.00

AR535	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	24.0	150/147	A8	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	24.0	152/149	A8	3550(7830)	3250(7160)	930(135)	9.00

AR525	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	24.0	150/147	A8	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	24.0	152/149	A8	3550(7830)	3250(7160)	930(135)	9.00

12R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR216

AR218

HL138

HL139

HL223

HL229



HL239

HL212

HL300

AR216	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	15.5	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	15.5	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

AR218	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	15.5	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	15.5	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

HL138	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	16.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	16.0	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

HL139	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	18.0	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	18.0	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

HL223	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	20.3	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	20.3	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

HL229	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	18.2	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	18.2	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

HL239	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	20.5	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	20.5	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

HL212	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	20.5	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	20.5	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

HL300	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	12R22.5	16PR	17.5	150/147	K	3350(7385)	3075(6780)	830(120)	9.00
	12R22.5	18PR	17.5	152/149	K	3550(7830)	3250(7160)	930(135)	9.00

11R24.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AW737 AW817 AW002

AW737	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R24.5	16PR	14.5	146/143	M	3000(6610)	2725(6005)	830(120)	8.25

AW817	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R24.5	16PR	21.0	146/143	M	3000(6610)	2725(6005)	830(120)	8.25

AW002	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	11R24.5	16PR	14.5	146/143	K	3000(6610)	2725(6005)	830(120)	8.25

295/80R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AW787 AW819 AW767 AW903HD AW002

AW787	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	295/80R22.5	16PR	15.5	150/147	K	3350(7390)	3075(6780)	830(120)	9.00
	295/80R22.5	18PR	15.5	152/149	K	3550(7830)	3250(7160)	900(130)	9.00

AW819	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	295/80R22.5	16PR	19.5	150/147	M	3350(7390)	3075(6780)	830(120)	9.00
	295/80R22.5	18PR	19.5	152/149	M	3550(7830)	3250(7160)	900(130)	9.00

AW767	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	295/80R22.5	16PR	15.0	150/147	M	3350(7390)	3075(6780)	830(120)	9.0
	295/80R22.5	18PR	15.0	152/149	M	3550(7830)	3250(7160)	900(130)	9.0

AW903/HD	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	295/80R22.5	18PR	20.5	152/149	F	3550(7830)	3250(7160)	900(130)	9.75

AW002	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	295/80R22.5	18PR	14.9	152/149	K	3550(7830)	3250(7160)	900(130)	9.00

13R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AR869 AW002 AW903

AR869	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	13R22.5	18PR	17.5	154/151	J	3750(8270)	3450(7610)	830(120)	9.75

AW002	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	13R22.5	18PR	15.5	154/151	K	3750(8270)	3450(7610)	830(120)	9.75

AW903	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	13R22.5	18PR	20.0	154/151	K	3750(8270)	3450(7610)	830(120)	9.75

315/80R22.5

PATTERN DISPLAY

HUBEI AULICE TYRE CO.,LTD.



AW002 AW767 AW819 AW878 AW816 AW797 AW902

AW002	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	315/80R22.5	18PR	15.5	154/151	K	3750(8270)	3450(7610)	830(120)	9.0
	315/80R22.5	20PR	15.5	157/154	K	4125(9100)	3750(8270)	900(130)	9.0

AW767	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	315/80R22.5	18PR	15.0	154/151	L	3750(8270)	3450(7610)	830(120)	9.0
	315/80R22.5	20PR	15.0	157/154	L	4125(9100)	3750(8270)	900(130)	9.0

AW819	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	315/80R22.5	18PR	20.0	154/151	K	3750(8270)	3450(7610)	830(120)	9.0
	315/80R22.5	20PR	20.0	157/154	K	4125(9100)	3750(8270)	900(130)	9.0

AW878	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	315/80R22.5	20PR	18.0	157/154	K	4125(9100)	3750(8270)	900(130)	9.00

AW816	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	315/80R22.5	20PR	20.0	157/154	L	4125(9100)	3750(8270)	900(130)	9.00

AW797	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	315/80R22.5	20PR	15.5	157/154	M	4125(9100)	3750(8270)	900(130)	9.00

AW902	Size	Ply Rating	Tread Depth (mm)	Load Index	Speed Symbol	KG(LBS.)Load Capacity		Pressure kPa(PSI)	Standard Rim
						Single	Dual		
	315/80R22.5	20PR	23.0	157/154	F	4125(9100)	3750(8270)	900(130)	9.0

COMPANY HISTORY

In the future

Aulice always adheres to the brand philosophy that "quality is the foundation of the brand, and trust is the soul of the brand." Actively integrating the concept of "Internet+" and combining with artificial intelligence and big data technology, we are committed to become an intelligent and powerful innovation enterprise and leading new trends in the future development of tire industry.

2020

Established an Internet technology team, primarily dedicated to developing online B2B and B2C platforms. Venturing into the realm of big data, with a focus on data collection and AI intelligent algorithms, aiming to enable users to utilize tyres more scientifically.



2017

In 2017 was selected as "gold seed" reserve listed enterprises Hubei Province, at the same time the Department of Foreign Trade officially operated.



2015

In 2015, passed "GCC", issued by Cooperation Council for the Arab States of the Gulf in Jan and "ISO9001:2000" in June. With the establishing of it's footprint across the global, Aulice's operating income reached 146.23 million RMB in 2015.



2012

The company settled in Yangxin County Economic Development Zone in April 2012, with a total investment of 2 billion RMB.



2014

Passed American quality management system certification "DOT" in Aug 2014.



2016

In 2016 awarded "high-tech enterprise" by Huangshi Technical Supervision Bureau.



2019

Our products have achieved significant sales across more than 30 provinces, cities, and autonomous regions in the domestic market, resulting in a well-established and favored market presence among customers.



2021

Selected as the 'Golden Seed' listed in Hubei Province in 2021, successfully ranked among the top 100 industrial enterprises and top 100 manufacturing enterprises in Huangshi City, Hubei Province. Additionally, and recommended by other Hubei Provincial tyre companies and awarded first place. Company.



2000

Hubei Aulice Tyre Co.,Ltd., Formerly known as Wuhan Aulice Tyre Co., Ltd., which was established in 2000.



湖北奥莱斯轮胎股份有限公司
HUBEI AULICE TYRE CO., LTD

团结协作 实干创新 AOSU 诚信求进 尽心尽职