

InnoVet[®] VERSA

HIGH FREQUENCY RADIOGRAPHIC SYSTEM

Distributed By:



www.vxsimaging.com
281.242.9729



"THE MOST TRUSTED NAME IN VETERINARY RADIOGRAPHY"

INNOVET MEANS INTEGRITY

InnoVet revolutionized veterinary radiography in 1991 with the first x-ray system designed by veterinarians. Since then, InnoVet has manufactured more than 15,000 veterinary x-ray systems, making it the #1 veterinary x-ray manufacturer in the United States.

Add to that, the industry's best warranty and it's no wonder InnoVet is the most trusted name in veterinary radiography.



LOCAL SUPPORT

Capital equipment is a long-term investment that deserves personal attention from a service professional who understands your practice.

Regional InnoVet dealers are factory-trained to install and service your x-ray systems with immediate on site support. Our trusted support network means image quality will never slow down your practice.

INDUSTRY BEST WARRANTY

Our 7-year limited parts warranty secures your investment today and guarantees your investment value tomorrow.

InnoVet®

7555 North Caldwell Ave. • Niles, IL 60714
800-972-9776 • 773-588-2444

www.innovet4vets.com

System Specifications

TABLE / TUBESTAND

- Unique column and covers safeguard staff and patients from exposed electrical wires
- Rounded corners prevent hip-level bruising common to veterinary technicians
- Stationary table top: 56 in. x 24 in.
- Welded base construction
- Transformer mounting shelf
- Grid cabinet with cassette tray
- Grid cabinet / tubestand interlock
- Grid 8:1 ratio, 103 LPI
- Animal restraining device
- Angulation dial and deluxe operator handgrips
- Tubestand handles

COLLIMATOR

- Manual collimator with LED light field and swivel mount
- Field light "on" time – selectable 30, 45 or 60 seconds

HIGH FREQUENCY GENERATOR

- 20 KHz High Frequency technology
- 30 kW rating
- kVp range: 40 – 125, in 1 kV increments
- mA stations: 50s, 100s, 100L, 300L
- mAs range: 0.5 to 400
- mAs/kVp technique selection
- Digital kVp, mA, and mAs readout
- Built-in tube protection and self diagnostics
- Automatic generator "Shut Off" circuit
- Adjustable volume, audible exposure signal
- UL classified

X-RAY TUBE

- 1.0-2.0 mm F.S., 140,000 H.U. with 90° horns

System Options

- Four-way float top table, 67 in. x 32 in.
- Anatomical programmed technique selection
- 500 mA generator upgrade
- Table top fluid trough