

FT1300 - FT1400

AIRBUS: H125, H145,
AS350, AGUSTA
WESTLAND A119, AW119




Tank Capacity
1000-1300L
(264-344gal)



Tank Weight Empty
105kgs
(231lbs)



Tank Weight Full
1405kgs
(3097lbs)



Tank Height
270mm
(10.6")



Foam Retardent Capacity
95L (25gal)



Power Requirements
28Vdc
150Amps



Hover Fill Pump
HP2000
2000L (528gal) per min



Features

Unique Helitak Fire Tank Controller (FTC) controls and records variable application rates, water collection and delivery, and maintenance and operations data telemetry.

Designed for maximum head pressure for the most effective canopy penetration.

Carbon fibre shell construction makes for a light weight, extra strength design.

Hover Pump design prevents water siphoning.

Fully self-contained with an internal foam tank, control system, and on-board compressors and pneumatic system

Failsafe emergency door operation.

25 minute install and removal process – roll under, attached mounting pins and electrical plugs creating a genuine plug and play solution.

The enhanced connectivity of the FTC allows the pilot to operate the Fire Tank from the FTC interface, iPad or other smart device.

Get In Touch

HELITAK FIRE FIGHTING EQUIPMENT

Sales, Manufacturing & Service Sunshine
Coast, Queensland, Australia
Sales@helitak.com.au
+61 753 569 545
www.helitak.com.au

USA Sales & Service
Camarillo, California, USA
SalesUSA@helitak.com.au
+ 1 503 896 9225

