

# FT1800 - FT2500

## BELL MEDIUM RANGE



**Tank  
Capacity**

1800 - 2500L  
(476 - 660gal)



**Tank Weight  
Empty**

146kgs  
(322lbs)



**Tank Weight  
Full**

1946 - 2646kgs  
(4290 - 5820 lbs)



**Tank  
Height**

270mm (11")



**Foam Retardent  
Capacity**

90L (23gal)



**Power  
Requirements**

28Vdc  
150Amps



**Hover Fill  
Pump**

Helitak HP2000  
2000L (528gal) pm





## Features

Unique Helitak Fire Tank Controller (FTC) controls and records variable application rates, water collection and delivery, and maintenance and operations data telemetry.

Designed for maximum head pressure for the most effective canopy penetration.

Carbon fibre shell construction makes for a light weight, extra strength design.

Hover Pump design prevents water siphoning.

Fully self-contained with an internal foam tank, control system, and on-board compressors and pneumatic system

Failsafe emergency door operation.

25 minute install and removal process – roll under, attached mounting pins and electrical plugs creating a genuine plug and play solution.

The enhanced connectivity of the FTC allows the pilot to operate the Fire Tank from the FTC interface, iPad or other smart device.

## Get In Touch

### HELITAK FIRE FIGHTING EQUIPMENT

Sales, Manufacturing & Service Sunshine  
Coast, Queensland, Australia  
Sales@helitak.com.au  
+61 753 569 545  
www.helitak.com.au

USA Sales & Service  
Camarillo, California, USA  
SalesUSA@helitak.com.au  
+ 1 503 896 9225

