

FT4250

AIRBUS SUPER PUMA  
AS332 & H225


FAA STC: SR04509CH  
& EASA STC: 10087605




**Tank Capacity**  
4250L  
(1124gal)



**Tank Weight Empty**  
330kgs  
(726 lbs)



**Tank Weight Full**  
4580kgs  
(10,097lbs)



**Tank Height**  
300mm(12")



**Foam Retardent Capacity**  
215L (56gal)



**Power Requirements**  
20Kva 115Vac3  
Phase | 50Amps  
28Vdc | 30Amps



**Hover Fill Pump**  
Helitak HP6000  
6000L (1585gal) pm





## Features

Unique Helitak Fire Tank Controller (FTC) controls and records variable application rates, water collection and delivery, and maintenance and operations data telemetry.

Designed for maximum head pressure for the most effective canopy penetration.

Carbon fibre shell construction makes for a light weight, extra strength design.

Hover Pump design prevents water siphoning.

Fully self-contained with an internal foam tank, control system, and on-board compressors and pneumatic system

Failsafe emergency door operation.

25 minute install and removal process – roll under, attached mounting pins and electrical plugs creating a genuine plug and play solution.

The enhanced connectivity of the FTC allows the pilot to operate the Fire Tank from the FTC interface, iPad or other smart device.

## Get In Touch

HELITAK FIRE FIGHTING EQUIPMENT

Sales, Manufacturing & Service Sunshine  
Coast, Queensland, Australia  
Sales@helitak.com.au  
+61 753 569 545  
www.helitak.com.au

USA Sales & Service  
Camarillo, California, USA  
SalesUSA@helitak.com.au  
+ 1 503 896 9225

