

FT4500

SIKORSKY: UH60 BLACK HAWK, S70 & T70

FAA STC: SR04461CH



Tank Capacity
4500L
(1190 gal)



Tank Weight Empty
380kgs
(837 lbs)



Tank Weight Full
4880kgs
(10,758 lbs)



Tank Height
300mm(12")



Foam Retardent Capacity
225L
(59 gal)



Power Requirements
20Kva 110Vac 3 Phase
50Amps 28Vdc 30Amps



Hover Fill Pump
Helitak HP6000
6000L (1585gal) pm



The Helitak FT4500 is approved on the type certificates for the following aircraft models: UH60A, EH60A, H60, HH60A, UH60L, S70, S70C S70A, S70M

Features

Unique Helitak Fire Tank Controller (FTC) controls and records variable application rates, water collection and delivery, and maintenance and operations data telemetry.

Designed for maximum head pressure for the most effective canopy penetration.

Carbon fibre shell construction makes for a light weight, extra strength design.

Hover Pump design prevents water siphoning.

Fully self-contained with an internal foam tank, control system, and on-board compressors and pneumatic system

Failsafe emergency door operation.

25 minute install and removal process – roll under, attached mounting pins and electrical plugs creating a genuine plug and play solution.

The enhanced connectivity of the FTC allows the pilot to operate the Fire Tank from the FTC interface, iPad or other smart device.

Get In Touch

HELITAK FIRE FIGHTING EQUIPMENT

Sales, Manufacturing & Service Sunshine
Coast, Queensland, Australia
Sales@helitak.com.au
+61 753 569 545
www.helitak.com.au

USA Sales & Service
Camarillo, California, USA
SalesUSA@helitak.com.au
+ 1 503 896 9225

