

FT11K

Boeing CH-47D
Chinook



Tank Capacity
11000L
(2905gal)



Tank Weight Empty
880kgs
(1940lbs)



Tank Weight Full
11880kgs
(26,190lbs)



Tank Height
360mm
(14")




Foam Retardant Capacity
500L
(132gal)



Power Requirements
40Kva 110Vac
3 Phase / 50Amps
28Vdc 30Amps



Hover Fill Pump
HP10000
10000L (2641gal)
per min



Dimensions
Tank length
7000mm (22.9ft)
Tank width
2200mm (7.2ft)

FEATURES

Unique Helitak Fire Tank Controller (FTC) controls and records variable application rates, water collection and delivery, and maintenance and operations data telemetry.

The enhanced connectivity of the FTC allows the pilot to operate the Fire Tank from the FTC interface, iPad or other smart device.

Carbon fibre shell construction makes for a light weight, extra strength design.

Hover Pump design prevents water siphoning.

Fully self-contained with an internal foam tank, control system, and on-board compressors and pneumatic systems.

Failsafe emergency door operation.

25 minute install and removal process – roll under, attached mounting pins and electrical plugs creating a genuine plug and play solution.

Designed for maximum head pressure for the most effective canopy penetration.



Manufacturing & Service
Sunshine Coast, Queensland, Australia

Service
Camarillo, California, USA

+61 400 350 205
sales@helitak.com.au
www.helitak.com.au

