

# FT1300

## AIRBUS H125 SQUIRREL

## ASTAR AS350




**Tank Capacity**  
1000-1300L  
(264-343gal)



**Tank Weight Empty**  
105kgs  
(231lbs)



**Tank Weight Full**  
1405kgs  
(3097lbs)



**Tank Height**  
270mm  
(11")




**Foam Retardant Capacity**  
95L  
(25gal)



**Power Requirements**  
28 Vdc 150Amps



**Hover Fill Pump**  
HP2000 2000L  
(528gal) per min



**Dimensions**  
Tank length 2000mm  
(6.56ft)  
Tank width 1200mm  
(3.93 ft)



# FEATURES

Unique Helitak Fire Tank Controller (FTC) controls and records variable application rates, water collection and delivery, and maintenance and operations data telemetry.

The enhanced connectivity of the FTC allows the pilot to operate the Fire Tank from the FTC interface, iPad or other smart device.

Carbon fibre shell construction makes for a light weight, extra strength design.

Hover Pump design prevents water siphoning.

Fully self-contained with an internal foam tank, control system, and on-board compressors and pneumatic systems.

Failsafe emergency door operation.

25 minute install and removal process – roll under, attached mounting pins and electrical plugs creating a genuine plug and play solution.

Designed for maximum head pressure for the most effective canopy penetration.



**Manufacturing & Service**  
Sunshine Coast, Queensland, Australia

**Service**  
Camarillo, California, USA

**0400 350 205**  
[sales@helitak.com.au](mailto:sales@helitak.com.au)  
[www.helitak.com.au](http://www.helitak.com.au)

